RX-1M Hi-Meg



Ultra High Resistance High Stability Hermetically Sealed

These Hi-Meg resistors are designed for use in electrometer circuits where a high order of performance is required. These resistors achieve a high degree of accuracy and stability, and operate at this high performance level for an extended period of time. By being vacuum sealed in a glass envelope, these Hi-Megs are suitable for ultra-high vacuum applications.

FEATURES

Glass sealed hermetric resistors

MINIMA TORICKERS AND MANAGEMENT

- · Improved temperature stability
- Improved voltage stability
- Metal oxide resistive elements
- No outgassing
- RoHS compliant
- Calibration available

APPLICATIONS

- Ultra high vacuum
- Medical instrumentation
- Current pulse limiters
- Avionics


CHARACTERISTICS

Resistance	1M to
Range	10,000,000M
Power Rating	0.5W at 25°C
Voltage Rating	1.0KV
Temperature	as low as
Coefficient	50PPM/°C


Handling and Cleaning of RX-1M Resistors:

These glass encapsulated resistors, especially those of higher resistance value, require extraordinary cleanliness. These resistors should be handled by the terminals, unless gloves are worn. Fingerprints on the surface of the resistor will attract contaminants and moisture, which will cause a parallel resistance path, reducing the resistance value of the device. If cleaning should become necessary, use isopropyl alcohol and lightly wipe dry with lint free tissues such as Kimwipes.

DIMENSIONS



ORDERING INFORMATION





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ohmite manufacturer:

Other Similar products are found below:

OG1825 5910E 6017E 608-8E 6112-EP-252E 62645-10/10/10 630HR025 CU1511 D1000K5R0 D100K600 D225K2K2E D25K300

D25K750 EVFL170EN4R7JE EVFT119EM47RJE EVFT170EN100JE F20J25KE F20J3K0E F30J50R F40J200 F55J100 F55J20K 76303

805F10K 805F250 805F2K5 805F75R 80FR499 810F20KE 83FR121 850F250 MOX-5-122002JE MOX-750232506FE MOX-H-021004J

MOX-H-042505JE MOX-J-045006F MOX-J-046004J PFE5K4R50 PFR5K25R0 90J10KE-B 90J12K 90J47K 90J56R 90J5R6E 91J2K2

91J91RE 92J1K0 93J33R 93J470 95J15K