
G9EA-1

DC Power Relays (60-A, 100-A Models)

DC Power Relays Capable of Interrupting High-voltage, High-current Loads

- A compact relay (73 x 36 x 67.2 mm (L x W x H)) capable of switching 400-V 60-A DC loads. (Capable of interrupting 600 A at 300 VDC max.)
- The switching section and driving section are gas-injected and hermetically sealed, allowing these compact relays to interrupt high-capacity loads. The sealed construction also requires no arc space, saves space, and helps ensure safe applications.
- Downsizing and optimum design allow no restrictions on the mounting direction.
- Terminal Cover and DIN Track Adapters are also available for industrial applications.
- UL/CSA standard UL508 approved.



Refer to "DC Power Relays Common Precautions".



G9EA-1 2 3 4

1. Number of Poles

1: 1 pole

2. Contact Form

Blank: SPST-NO

3. Coil Terminals

B: M3.5 screw terminals

Blank: Lead wire output

4. Special Functions

CA: High-current conduction (100 A)

■List of Models

Classification	Terminals		Contact form	Rated coil voltage	Model
	Coil terminals	Contact terminals	Contact form	nated con voltage	woder
Switching/current conduction models	Screw terminals			12 VDC	G9EA-1-B
	Lead wires		SPST-NO	24 VDC	G9EA-1
High-current conduction models	Screw terminals	Screw terminals	SPST-NO 48 VDC 60 VDC	G9EA-1-B-CA	
	Lead wires			100 VDC	G9EA-1-CA

Note 1. Two M5 screws are provided for the contact terminal connection.

■Ratings

●Coil

Rated voltage	Item	Rated current (mA)	Coil resistance (Ω)	Must-operate voltage (V)	Must-release voltage (V)	Maximum voltage (V)	Power consumption (W)	
12 VDC		417	28.8					
24 VDC		208	115.2	Ī		130% of rated	Approx. 5 W	
48 VDC		102	469.3	75% max. of rated voltage		8% min. of rated voltage	voltage (at 23°C	
60 VDC		86.2	695.7		Vollago	within 10 minutes)	Approx. 5.2 W	
100 VDC		53.6	1864	İ			Approx. 5.4 W	

Note 1. The figures for the rated current and coil resistance are for a coil temperature of 23°C and have a tolerance of ±10%.

Note 2. The figures for the operating characteristics are for a coil temperature of 23°C.

Note 3. The figure for the maximum voltage is the maximum voltage that can be applied to the relay coil.

●Contacts

Contacts				
Item	Resistive load			
item	G9EA-1(-B)	G9EA-1(-B)-CA		
Rated load	60 A at 400 VDC, 100 A at 120 VDC	30 A at 400 VDC		
Rated carry current	60 A	100 A		
Maximum switching voltage	400 V	400 V		
Maximum switching current	100 A	30 A		

Note 2. Two M3.5 screws are provided for the coil terminal connection.

■Characteristics

Item Model		G9EA-1(-B)	G9EA-1(-B)-CA	
Contact resistance 1		30 m Ω max. (0.6 m Ω typical)	10 m Ω max. (0.3 m Ω typical)	
Contact voltage drop		0.1 V max. (for a carry current of 60 A)	0.1 V max. (for a carry current of 100 A)	
Operate time		50 ms max.		
Release time		30 ms max.		
Insulation	Between coil and contacts	1,000 MΩ min.		
resistance	Between contacts of the same polarity	1,000 MΩ min.		
Dielectric	Between coil and contacts	2,500 VA	AC, 1 min	
strength *2	Between contacts of the same polarity	2,500 VA	AC, 1 min	
Impulse withstand voltage *3		4,50	00 V	
Vibration Destruction		10 to 55 to 10 Hz, 0.75-mm single amplitude (Acceleration: 2.94 to 88.9 m/s²)		
resistance Malfunction		10 to 55 to 10 Hz, 0.75-mm single amplitude (Acceleration: 2.94 to 88.9 m/s²)		
Shock Destruction		490 m/s ²		
resistance	Malfunction 196 m/s ²		m/s²	
Mechanical er	ndurance *4	200,000 ops. min.		
		120 VDC, 100 A, 3,000 ops. min.	400 VDC, 30 A, 1,000 ops. min.	
Electrical end	urance (resistive load) *5	400 VDC, 60 A, 3,000 ops. min.	120 VDC, 30 A, 2,500 ops. min.	
		400 VDC, 30 A, 30,000 ops. min.	-	
Short-time carry current		100 A (10 min)	150 A (10 min)	
Maximum interruption current		600 A at 300 VDC (5 times)	-	
Overload interruption		180 A at 400 VDC (100 times min.)	100 A at 120 VDC (150 times min.)	
Reverse polarity interruption		-60 A at 200 VDC (1,000 times min.)		
Ambient operating temperature		-40 to 70°C (with no icing or condensation)		
Ambient operating humidity		5% to 85% RH		
Weight (including accessories)		Approx. 310 g		

- Note. The above values are initial values at an ambient temperature of 23°C unless otherwise specified.


 *1. The contact resistance was measured with 1A at 5VDC using the voltage drop method.

 *2. The insulation resistance was measured with a 500-VDC megohmmeter. G 9 E
- The insulation resistance was measured with a 500-VDC megohmmeter.
- *3. *4. Ā The impulse withstand voltage was measured with a JEC-212 (1981) standard impulse voltage waveform ($1.2 \times 50 \,\mu s$).
 - The mechanical endurance was measured at a switching frequency of 3,600 operations/hr.
 - *5. The electrical endurance was measured at a switching frequency of 60 operations/hr.


■Engineering Data

G9EA-1(-B) Switching/Current Conduction Models


Maximum Switching Capacity




● Electrical Endurance (Switching Performance)



● Electrical Endurance (Interruption Performance)




● Carry Current vs Energizing Time




G9EA-1(-B)-CA High-current Conduction Models


Maximum Switching Capacity



Electrical Endurance (Switching Performance)




Carry Current vs Energizing Time




All G9EA-1 Models


Must-operate Voltage and Must-release Voltage Distributions




● Time Characteristic Distributions



Vibration Malfunction




● Vibration Resistance




Characteristics were measured after applying vibration at a frequency of 10 to 55 Hz (single amplitude of 0.75 mm) to the test piece (not energized) for 2 hours each in 3 directions. The percentage rate of change is the average value for all of the samples

Shock Malfunction



The value at which malfunction occurred was measured after applying shock to the test piece 3 times each in 6 directions along 3 axes.

● Shock Resistance




Characteristics were measured after applying a shock of 490 m²/s to the test piece 3 times each in 6 directions along 3 axes. The percentage rate of change is the average value for all of the samples.


■Dimensions (Unit: mm)

Models with Screw Terminals G9EA-1-B(-CA)



Dimension (mm)	Tolerance (mm)
10 or lower	±0.3
10 to 50	±0.5
50 or higher	±1






Terminal Arrangement/ Internal Connections (TOP VIEW)




Note: Be sure to connect terminals with the correct polarity.

Coils do not have polarity.


Mounting Hole Dimensions (TOP VIEW)




Models with Lead Wires G9EA-1(-CA)



Dimension (mm)	Tolerance (mm)
10 or lower	±0.3
10 to 50	±0.5
50 or higher	±1






Terminal Arrangement/ Internal Connections (TOP VIEW)




Note: Be sure to connect terminals with the correct polarity. Coils do not have polarity.

Mounting Hole Dimensions (TOP VIEW)





■Options (Unit: mm)

● Terminal Cover P9EA-C










* Dimensions of cutouts for wiring.

Note: Be sure to remove the cutouts for wiring that are located in the wiring outlet direction before installing the Terminal Cover.

Dimension (mm)	Tolerance (mm)
10 or lower	±0.3
10 to 50	±0.5
50 or higher	±1

● DIN Track Adapter P9EA-D









Dimension (mm)	Tolerance (mm)
10 or lower	±0.3
10 to 50	±0.5
50 or higher	±1

Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
 Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad

Contact: www.omron.com/ecb

Note: Do not use this document to operate the Unit.

OMRON Corporation

Electronic and Mechanical Components Company

Cat. No. J186-E1-01

[•] Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for General Purpose Relays category:

Click to view products by Omron manufacturer:

Other Similar products are found below:

PCN-105D3MH,000 59641F200 LY1SAC110120 5X827E 5X837F 5X840F 5X842F 5X848E LY2N-AC120 LY2S-AC220/240 LY2-US-AC120 LY3-US-AC120 LY4F-UA-DC12 LY4F-UA-DC24 LY4F-US-AC120 LY4F-US-AC240 LY4F-US-DC24 LY4F-VD-AC110 LYQ20DC12 M115C60 M115N010 M115N0150 6031007G 603-12D 61211T0B4 61212T400 61222Q400 61243B600 61243C500 61243Q400 61311BOA2 61311BOA6 61311BOA8 61311COA2 61311COA1 61311COA6 61311F0A2 61311QOA1 61311QOA4 61311T0B6 61311TOA6 61311TOA6 61311TOB3 61311TOB4 61311U0A6 61312Q600 61312T400 61312T600 61313U200 61313U400