

Solid-state Timer

English

H3YN-2 AC200-230

Print Page



Analog Timer, AC200 to 230V

Rated supply voltage	200 to 230VAC 50/60 Hz
Control output (Type)	Time-limit: DPDT
External connection method	Plug-in terminal

[Item list of H3YN](#)

Series

Solid-state Timer
H3YN

[Catalog](#)

[about this Product](#)

[Inquiry of this Product](#)

Image

- Ratings/Performance
- Dimensions
- Time ranges
- Operating chart
- Electrical life

As of November 11, 2015

Rated supply voltage	200 to 230VAC 50/60 Hz
Operating voltage range	85% to 110% of rated supply voltage
Power consumption (Relay ON)	Approx. 2.2VA 1.8W (at 230 VAC, 60 Hz)
Power consumption (Relay OFF)	Approx. 1.5VA 1.1W (at 230 VAC, 60 Hz)
Reset voltage	10% max. of rated supply voltage
Number of time ranges	4
Time ranges	0.1s~1s / 1s~10s / 0.1min~1min / 1min~10min
Operating mode	ON delay, Interval, Flicker OFF start, Flicker ON start, Pulse Operation (use in interval mode, connect power supply terminals as pulse operation)
Control output (Type)	Time-limit: DPDT
Control output (Contact output)	Switching capacities (resistive load (cos(phi) = 1)): 250VAC 5A Minimum applicable load: 1 mA at 5 VDC (failure level: P)
Ambient temperature	Operating: -10 to 50°C Storage: -25 to 65°C
Ambient humidity	使用時: 35~85%
Accuracy of operating time	+/- 1% max.(FS) (+/- 1% +/- 10 ms max. in a ragen of 1 s)
Setting error	-10 to 10% +/- 50 ms max. (FS)
Reset time	0.1 s max. (including halfway reset)
Influence of voltage	+/- 2% FS max.
Influence of temperature	+/- 2% FS max.
Insulation resistance	100 MΩ (at 500 VDC)
Dielectric strength	between current carrying terminals and exposed non-current carrying metal parts: 2000 VAC, 50/60 Hz for 1 min (Terminal screw sections are not excluded) between control output terminals and operating circuit: 2000 VAC, 50/60 Hz for 1 min between contacts of different poles: 2000 VAC, 50/60 Hz for 1 min between non-continuous contacts: 1000 VAC, 50/60 Hz for 1 min
Impulse withstand voltage	between power terminals: 3 kV between exposed non-current-carrying metal parts: 4.5 kV
Noise immunity	+/- 1.5 kV square-wave noise by noise simulator (pulse width: 100 ns/1 us, 1-ns rise)
Static immunity	Mulfuction: 4 kV Destruction: 8 kV
Vibration resistance (Destruction)	10 to 55 Hz, 0.75 mm single amplitude each in X, Y, and Z directions for 1 hours
Vibration resistance	10 to 55 Hz, 0.5 mm single amplitude each in X, Y, and Z directions for 10 min

(Malfunction)	
Shock resistance (Destruction)	1000 m/s**2, 3 times each 6 directions
Shock resistance (Malfunction)	100 m/s**2, 3 times each 6 directions
Mechanical life expectancy (relayoutput)	10000000 operations min. (under no load at 1800 operations/h)
Electrical life expectancy (relay output)	500000 operations min. (5 A at 250 VAC, resistive load at 1800 operations/h)
Degree of protection	IP40
External connection method	Plug-in terminal
Case color	Munsell 5Y7/1 (Light gray)
Weight (Main)	Approx. 50 g

As of November 11, 2015

[▲ Top of page](#)[▶ OMRON Corporation](#)  [▶ Sitemap](#) [▶ Terms of Use](#) [▶ Privacy Policy](#)

© Copyright OMRON Corporation 2007 - 2012. All Rights Reserved.

realizing

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Timers](#) category:

Click to view products by [Omron](#) manufacturer:

Other Similar products are found below :

[79237785](#) [H5AN-4DM DC12-24](#) [H5CN-YAN AC100-240](#) [H5CX-L8S-N AC100-240](#) [H5AN-4D DC12-24](#) [THR2U-110A](#) [81506944](#)
[88225029](#) [H5S-YB4-X](#) [H7AN-2D DC12-24](#) [H5CN-XANS DC12-48](#) [H7AN-W4DM DC12-24](#) [H7AN-4DM DC12-24](#) [H7AN-4D DC12-24](#)
[H7AN-RT6M AC100-240](#) [600DT-CU](#) [7PV1513-1AP30](#) [7PV1538-1AW30](#) [1SVR508100R0000](#) [1SVR550127R4100](#) [1SVR550212R4100](#)
[1SVR730010R3200](#) [1SVR730020R3300](#) [1SVR730120R3100](#) [1SVR730180R3100](#) [1SVR730211R2300](#) [PCU-511UNI](#) [H3C-R](#) [H3CR-A8-301](#)
[24-48AC/12-48DC](#) [H3CR-A8E 24-48AC/DC](#) [H3CR-F8 100-240AC/100-125DC](#) [H3CR-FN 100-240AC/100-125DC](#) [H3DK-G 24-230AC/DC](#)
[H3DK-HBL AC/DC24-48](#) [H3DK-M1A DC12](#) [LT4H-AC24V](#) [LT4HW8-AC240V](#) [LT4HW-AC240V](#) [LT4HW-AC24VS](#) [31L48AP](#)
[31L48TPM240](#) [RC302](#) [RC312](#) [REV-201M](#) [RG](#) [AT78041](#) [AT78051](#) [ATC180041](#) [TMM1](#) [TMP](#)