


PANEL CUTOUT  
MAX.PANEL THICKNESS  
10 mm



Seal Ring

REV. 更改	DESCRIPTION 说明	ENG. 修改人	APPROVE 审核

**SPECIFICATIONS:**

- Rating: 2A/36VDC  
0.5A/220V.
- Electrical Life: ≥200,000cycles.
- Contact Resistance: ≤50mΩ.
- Insulation Resistance: ≥1,000MΩ.
- Dielectric Strength: 2,000V AC 50Hz 5 Seconds.
- Operating Temperature: -25℃ ~ +55℃ (No Freezing).
- Operating Force: About 4N.
- Torque: 0.6Nm max.applied to nut.
- Contact Configuration: 1NO.
- Operation Type: Momentary.
- The Front Shape:Domed .
- IP Class: IP65,IK09.

**MATERIALS:**

- Contact: Silver alloy.
- Button:Stainless Steel.
- Body: Nickel Plated Brass /Stainless Steel.
- Base: PBT.

Part Number: GQ19B-10 / J / ◎

"◎"	Crust Material
N	Nickel Plated Brass
S	Stainless Steel
A	Al Alloy(BLACK)

DIMENSIONS	TOLERANCE
0.00 TO 30.00mm	±0.20mm
30.01 TO 80.00mm	±0.25mm
80.01 TO 150.00mm	±0.30mm
150.01 ↑	±0.40mm

中国·红波按钮制造有限公司  
ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

USED 用途	APPD 审核
FINISH 处理	CHKD 校对
SCALE 比例 1.6 / 1	UNIT 单位 mm
TITLE 名称 Anti-vandal push button	DR. 制图
MATERIAL	DWG NO. 图号 GQ19B-10 / J / ◎
FILE NAME 档案名称 GQ19B-10J◎.DWG	SHEET 张 1 / 1
REV. 更改	APPROVE 审核
1	1

SIZE  
图纸 A4

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [Onpow](#) manufacturer:*

Other Similar products are found below :

[LW1L-M1C10V-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M7E-HRN2](#) [67021K512](#) [67081K512X](#) [701PB580](#) [719-5504-000](#)  
[MDPSSGLFS](#) [810KSV30B](#) [FLT 2U EE 01A](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8646AB6X718UL](#)  
[8646ABUL](#) [FSDWH](#) [9001KXRK](#) [9001T8BK](#) [9533CD4+U574+U4922](#) [1203MRA](#) [A22EM01S](#) [A595](#) [1202A6](#) [12037A2ULCSA](#) [1203A2UL](#)  
[ABD122N-B](#) [1211390004](#) [ABN111-Y](#) [ABN400-R](#) [1211500044](#) [1211580012](#) [1212MRA](#) [1232A6NF](#) [RA3CSH6A](#) [1241.1183.7047](#)  
[1241.2511](#) [1241.3428](#) [1223A2ULCSA](#) [1223MRA](#) [1232AX2119](#) [1241.1183.8000](#) [1241.1183.8029](#) [1241.2506](#) [1241.2606](#) [12MA6](#)  
[1301940184](#) [RELBARF6X10\(PLASTIC\)](#)