

ON Semiconductor DATA SHEET

N-Channel Junction Silicon FET 2SK1069-Low-Frequency

General-Purpose Amplifier Applications

Applications

- · Low-frequency general-purpose amplifiers.
- · Ideal for use in variable resistors, analog switches, low-frequency amplifiers, and constant-current circuits.


Features

- · Adoption of FBET process.
- · Ultrasmall-sized package permitting 2SK1069applied sets to be made smaller and slimmer.

Package Dimensions

unit:mm

2058



Specifications

Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V _{DSX}		40	V
Gate-to-Drain Voltage	V _{GDS}		-40	V
Gate Current	I _G		10	mA
Drain Current	I _D		20	mA
Allowable Power Dissipation	PD		150	mW
Junction Temperature	Tj		150	°C
Storage Temperature	Tstg		-55 to +150	°C

Electrical Characteristics at Ta = 25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	Offic
Gate-to-Drain Breakdown Voltage	V _(BR) GDS	$I_G=-10\mu A, V_{DS}=0$	-40			V
Gate-to-Source Leakage Current	IGSS	V_{GS} =-20V, V_{DS} =0			-1.0	nA
Zero-Gate Voltage Drain Current	IDSS	V _{DS} =10V, V _{GS} =0	1.2*		12.0*	mA
Cutoff Voltage	V _{GS(off)}	V_{DS} =10V, I_D =1 μ A	-0.3	-0.9	-2.0	V
Forward Transfer Admittance	yfs	V_{DS} =10V, V_{GS} =0, f=1kHz	4.5	9.0		mS

 $[\]mbox{\ensuremath{^{*}}}$: The 2SK1069 is classified by I_{DSS} as follows (unit : mA) :


3.0 2.5 1.2 3 4 6.0 5.0 5 12.0

(Note) Marking: FJ I_{DSS} rank : 3, 4, 5 Continued on next page.


[•] For CP package version, use the 2SK771.

Continued from preceding page.

Parameter	Symbol	Conditions	Ratings		Unit
Input Capacitance	Ciss	V _{DS} =10V, V _{GS} =0, f=1MHz	9.0		pF
Reverse Transfer Capacitance	Crss	V _{DS} =10V, V _{GS} =0, f=1MHz	2.1		pF
Noise Figure	NF	V_{DS} =10V, Rg=1k Ω , I $_{D}$ =1mA, f=1kHz	1.5		dB



2SK1069



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. SCILLC strives to supply high-quality high-reliability products and recommends adopting safety measures when designing equipment to avoid accidents or malfunctions. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals," must be validated for each customer application by customer's technical experts. SCILLC shall not be held liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affil liates, and distributors harmless against all claims, costs, dam

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email: orderlit@onsemi.com

Literature Distribution Center for ON Semiconductor P.O. Box 5163, Denver, Colorado 80217 USA **Phone**: 303-675-2175 or 800-344-3860 Toll Free USA/Canada

Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada

N. American Technical Support: 800-282-9855 Toll Free USA/Canada.

Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910

Japan Customer Focus Center Phone: 81-3-5773-3850 ON Semiconductor Website:www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for JFET category:

Click to view products by ON Semiconductor manufacturer:

Other Similar products are found below:

MCH3914-8-TL-H F5606 2SK536-TB-E SMMBF4393LT1G 2SK2394-6-TB-E CPH3910-TL-E CPH5901F-TL-E CPH5901G-TL-E CPH5902H-TL-E 424147G TF202THC-4-TL-H MCH3914-7-TL-H MCH5908H-TL-E DSK5J01R0L CPH5902G-TL-E CPH5905G-TL-E CPH5905H-TL-E 2SK304E-SPA 2SK545-11D-TB-E 2SK771-5-TB-E 2SK2539-7-TB-E 2SK932-22-TB-E 2SK2394-7-TB-E NSVJ2394SA3T1G MMBFJ175LT3G SMPJ270TR 2SK208-GR(TE85L) MMBF4416 MMBF5103 MMBF5484 MMBFJ175 MMBFJ176 MMBFJ270 MMBF4393 NPT1004D 2SK1069-5-TL-E 2SA1781-6-TB-E NSVJ3910SB3T1G 2N5116 2N5116 CMPF4392 TR 2N4092 2N4093 CMPP6028 TR 2N4117 2N3958 SNJ450113 IFN3993 IFN5911 IFN406