

Product Overview

AR0144AT: 1/4" 1.0 MP Global Shutter CMOS Image Sensor

For complete documentation, see the data sheet.

The AR0144AT is a 1/4-inch 1.0 Mp CMOS digital image sensor with an active-pixel array of 1280 (H) × 800 (V). It incorporates a new innovative global shutter pixel design optimized for accurate and fast capture of moving scenes. The sensor produces clear, low noise images in both low-light and bright scenes. It includes sophisticated camera functions such as auto exposure control, windowing, row skip mode, column-skip mode, pixel-binning and both video and single frame modes. It is programmable through a simple two-wire serial interface. The AR0144AT produces extraordinarily clear, sharp digital pictures, and its ability to capture both continuous video and single frames makes it the perfect choice for a wide range of applications, including automotive in-cabin systems.

Features

- · Superior Low-light and IR Performance
- HD Video (720p60)
- · 2-Lane MIPI or Parallel data interface
- · Automatic Black Level Calibration (ABLC)
- Programmable Control for Region Of Interest (ROI)
- · Horizontal and Vertical Mirroring, Windowing and Pixel Binning
- · On-chip Auto Exposure Control for Any Programmable ROI
- · On-chip Slave or Trigger Mode for Synchronization
- Built in Strobe Control
- On-chip Phase Lock Loop (PLL)
 For more features, see the data sheet

Applications

· Automotive In-Cabin / Driver Monitoring System



| Part Electrical Specifications | | | | | | | | | | | | |
|--------------------------------|-------------------|--|--------|------|----------------|------------------------|-------------------|-------------------|-----------------------|---------------------|-------|-----------------|
| Product | Pricing (\$/Unit) | Compliance | Status | Туре | Megapix els | Frame Rate (fps) | Optical Format | Shutter Type | Pixel Size (µm) | Output Interface | Color | Package Type |
| AR0144ATSM20XUD20 | | AEC Qualified PPAP Capable Pb-free Halide free | Active | | 1 | 60 | 1/4 inch | Global Shutter | 3.0 x 3.0 | MIPI Parallel | Mono | |
| AR0144ATSM20XUEA0 -DPBR | | AEC Qualified PPAP Capable Pb-free Halide free | Active | | 1 | 60 | 1/4 inch | Global Shutter | 3.0 x 3.0 | MIPI Parallel | Mono | IBGA-63 |
| AR0144ATSM20XUEA0 -DRBR | | AEC Qualified PPAP Capable Pb-free Halide free | Active | | 1 | 60 | 1/4 inch | Global Shutter | 3.0 x 3.0 | MIPI Parallel | Mono | IBGA-63 |
| AR0144ATSM20XUEA0 -TPBR | | AEC Qualified PPAP Capable Pb-free Halide free | Active | | 1 | 60 | 1/4 inch | Global Shutter | 3.0 x 3.0 | MIPI Parallel | Mono | IBGA-63 |
| AR0144ATSM20XUEA0 -TRBR | | AEC Qualified PPAP Capable Pb-free Halide free | Active | | 1 | 60 | 1/4 inch | Global Shutter | 3.0 x 3.0 | MIPI Parallel | Mono | IBGA-63 |

For more information please contact your local sales support at www.onsemi.com.

Created on: 8/2/2021

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Image Sensors category:

Click to view products by ON Semiconductor manufacturer:

Other Similar products are found below:

 MT9J003I12STCV2-DP
 KAF-4320-AAA-JP-B1
 AR0331SRSC00SUCA0-DPBR
 EKL3104
 MT9J003I12STCU-DP
 MT9P03II12STM-DR

 OV07955-N53V-PE
 AP0202AT2L00XPGA0-DR
 AR0132AT6M00XPEA0-DPBR
 MT9V138C12STC-DP1
 KLI-8023-RAA-ED-AA
 KLI-8023-RAA-ED-AA
 KLI-8023-RAA-ED-AA
 KLI-8023-AAA-ED-AA
 KLI-8023-RAA-ED-AA
 KLI-8023-RAA-ED-AA