# CPH5512

# **PIN Diode** Dual parallel PIN Diode for VHF, UHF and AGC 50V, 50mA, rs=typ 5Ω, CPH5



## Features

- · Composite type with 2 diodes contained in a CPH package currently in use, improving the mounting efficiency greatly
- Small interterminal capacitance (C=0.23pF typ)
- Small forward series resistance ( $r_s=5\Omega$  typ)

## **Specifications**


## Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Reverse Voltage	VR		50	V
Forward Current	IF		50	А
Allowable Power Dissipation	Р		350	V
Junction Temperature	Tj		125	°C
Storage Temperature	Tstg		-55 to +125	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

## Package Dimensions

unit : mm (typ) 7017A-001



## Product & Package Information

- Package
- JEITA, JEDEC : SC-74A, SOT-25

: CPH5

• Minimum Packing Quantity : 3,000 pcs./reel


## Packing Type : TL

#### 

Н	Η	Π
° 2B	[	LOT No.
Ĥ		Н

Marking

## **Electrical Connection**




## Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions		Unit		
	Symbol	Conditions	max			
Reverse Voltage	VR	I <sub>R</sub> =10μA	50			V
Reverse Current	IR	V <sub>R</sub> =50V			0.1	μΑ
Forward Voltage	VF	IF=50mA		0.95		V
Interterminal Capacitance	С	V <sub>R</sub> =50V, f=1MHz		0.23		pF
SeriesResistance	r <sub>S</sub>	IF=10mA, f=100MHz		5		Ω


The specifications shown above are for each individual diode.

## **Ordering Information**

Device	Device Package		memo	
CPH5512-TL-E	CPH5	3,000pcs./reel	Pb Free	








## Embossed Taping Specification CPH5512-TL-E

1. Packing Format

Package Name	Carrier Tape		aximum Number of Packing fo			g format		
	Туре	Reel	Inner box	Outer box	Inner BOX (C-1)		(C-1)	Outer BOX (A-7)
CPH5	CPH6	3,000	15,000	90,000	5 reels contained			6 inner boxes contained
					Dimensions:mm (external)			l) Dimensions:mm (external)
					183	3×72>	< 1 8 5	440×195×210
<u>Reel label, Inner box label</u> <u>Packing method</u> <u>(unit:mm)</u> <u>Reel label, Inner box label</u> (unit:mm) <u>Cuter box label</u> It is a label at the time of factory shipments. The form of a label may change in physical distribution process.								
	Type LOT Quan Orig	No. tity		TYPE   O   O   O     11 <td>                                      </td> <td></td> <td></td> <td>108   TYPE CODE   *CONTRACT   TYPE   QTY   0.000 PCS   LOT   PACKAGE   SPECIAL   #!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!</td>				108   TYPE CODE   *CONTRACT   TYPE   QTY   0.000 PCS   LOT   PACKAGE   SPECIAL   #!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
	<u>Reella</u>	bel	Th	e LEAD Fl eatment	of the –	terminal	is lead	that the surface free.
				Label			Phase	
				LEAD FRE LEAD FRE	-	•	Phase 3. Phase 3	<u>A</u>


2. Taping configuration

2-1. Carrier tape size (unit:mm)




Those with pin 1 index on the feed hole side  $\cdots \cdots TL$ 

## Outline Drawing CPH5512-TL-E



## Land Pattern Example



**CPH5512** 

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for PIN Diodes category:

Click to view products by ON Semiconductor manufacturer:

Other Similar products are found below :

MA45471 MA4SPS502 APD2220-000 APD0810-000 MA4GP907 MA4L032-186 MA4L401-30 MA4P606-258 MA4P7435NM-1091T MA4PK2000 MA4PK2001 MA4PK2004 MADP-007167-12250T MADP-030025-13140P MA4PBL027 MA4AGFCP910 MA4P7101F-1072T MA4L022-30 MA47047-54 BAR 89-02LRH E6327 UM7108B UM9701 1SV308,L3F UM9301SM 5082-3077 GC4723-42 MA4L011-1088 MSW2001-200 SMP1321-000 M17X1008 UM4010SM UM6002B UM7006A UM7006B UM7108C GC4742-42 MADP-000015-000030 MGPN1503-C01A UMX512 LXP1000-23-2 LXP1004-23-2 MPP4201-206 LXP1002-23-0 LXP1004-23-0 MPP4202-206 MPP4205-206 SMP1321-011LF MA4L021-1056 MSW2031-203 MLP7120-11