



Is Now Part of



**ON Semiconductor®**

To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## FSUSB20 — Low-Power, 1-Port, High-Speed USB (480Mbps) Switch

### Features

- -30dB Off Isolation: 250MHz
- -30dB Non-adjacent Channel Crosstalk: 250MHz
- On Resistance: 4.5Ω Typical (R<sub>ON</sub>)
- -3dB Bandwidth: >720MHz
- Low-Power Consumption: 1μA Maximum
- Control Input: LVTTTL Compatible
- Bi-Directional Operation
- USB High-Speed and Full-Speed Signaling Capability

### Applications

- Cell Phones, PDAs, Digital Cameras, Notebook Computers

### Description

FSUSB20 is a low-power, high-bandwidth switch specially designed for switching high-speed USB 2.0 signals in handset and consumer applications; such as cell phone, digital camera, and notebook with hubs or controllers of limited USB I/O. The wide bandwidth (>720MHz) allows signals to pass with minimum edge and phase distortion. Superior channel-to-channel crosstalk results in minimal interference. It is compatible with the high-speed USB 2.0 standard.

### Ordering Information

| Part Number | Operating Temperature Range | Package   | Packing Method |
|-------------|-----------------------------|---|----------------|
| FSUSB20L10X | -40 to +85°C                | 10-Lead MicroPak™, 1.6 x 2.1mm  | Tape and Reel  |
| FSUSB20BQX  | -40 to +85°C                | 14-Terminal Depopulation Quad Very-Thin Flat Pack No Lead (DQFN), JEDEC MO-241, 2.5 X 3.0mm | Tube           |
| FSUSB20MUX  | -40 to +85°C                | 10-Lead Molded Small Outline Package (MSOP), JEDEC MO-187, 3.0mm Wide                       | Tape and Reel  |

## Connection Diagrams




Figure 1. MicroPak™ (Top View)




Figure 2. Analog Symbol




Figure 3. DQFN (Top Through View)




Figure 4. MSOP (Top Through View)

## Pin Descriptions

| Pin # MicroPak™ / MSOP | Pin # DQFN   | Pin Names   | Description       |
|------------------------|--------------|---|-------------------|
| 1                      | 2            | S   | Select Input      |
| 2, 3, 7, 8             | 3, 5, 10, 12 | 1B <sub>1</sub> , 1B <sub>2</sub> , 2B <sub>2</sub> , 2B <sub>1</sub> | Bus B             |
| 5                      | 7            | GND   | Ground            |
| 4, 6                   | 6, 9         | 1A, 2A  | Bus A             |
| 9                      | 12           | OE  | Bus Switch Enable |
| 10                     | 14           | V <sub>CC</sub>   | Supply Voltage    |

## Truth Table

| S          | OE   | Function         |
|------------|------|------------------|
| Don't Care | HIGH | Disconnect       |
| LOW        | LOW  | A=B <sub>1</sub> |
| HIGH       | LOW  | A=B <sub>2</sub> |

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol             | Parameter                             | Min.       | Max.            | Unit |
|--------------------|---------------------------------------|------------|-----------------|------|
| $V_{CC}$           | Supply Voltage                        | -0.5       | 4.6             | V    |
| $V_S$              | DC Switch Voltage                     | -0.5       | $V_{CC} + 0.05$ | V    |
| $V_{IN}$           | DC Input Voltage <sup>(1)</sup>       | -0.5       | 4.6             | V    |
| $I_{IK}$           | DC Input Diode Current, $V_{IN} < 0V$ | -50        |                 | mA   |
| $I_{OUT}$          | DC Output Sink Current                | 50         |                 | mA   |
| $I_{CC} / I_{GND}$ | DC $V_{CC} / GND$ Current             | $\pm 100$  |                 | mA   |
| $T_{STG}$          | Storage Temperature Range             | -65        | +150            | °C   |
| ESD                | Human Body Model, JESD22-A114         | All Pins   | 7000            | V    |
|                    |                                       | I/O to GND | 7000            |      |

**Note:**

- The input and output negative voltage ratings may be exceeded if the input and output diode current ratings are observed.

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

| Symbol     | Parameter                       | Min.                                | Max.     | Unit |      |
|------------|---------------------------------|-------------------------------------|----------|------|------|
| $V_{CC}$   | Power Supply Operating          | 3.0                                 | 3.6      | V    |      |
| $V_{IN}$   | Input Voltage                   | 0                                   | $V_{CC}$ | V    |      |
| $V_{OUT}$  | Output Voltage                  | 0                                   | $V_{CC}$ | V    |      |
| $t_r, t_f$ | Input Rise and Fall Time        | Switch Control Input <sup>(2)</sup> | 0        | 5    | ns/V |
|            |                                 | Switch I/O                          | 0        | DC   |      |
| $T_A$      | Operating Temperature, Free Air | -40                                 | +85      | °C   |      |

**Note:**

- Unused control inputs must be held HIGH or LOW. They may not float.

## DC Electrical Characteristics

Typical values are at  $V_{CC} = 3.0V$  and  $T_A = 25^\circ C$ .

| Symbol          | Parameter                             | Condition  | $V_{CC}$ (V) | $T_A = -40$ to $+85^\circ C$ |      |           | Unit     |
|-----------------|---------------------------------------|--|--------------|------------------------------|------|-----------|----------|
|                 |                                       |  |              | Min.                         | Typ. | Max.      |          |
| $V_{IK}$        | Clamp Diode Voltage                   | $I_{IN} = -18mA$                                       | 3.0          |                              |      | -1.2      | V        |
| $V_{IH}$        | High-Level Input Voltage              |  | 3.0 to 3.6   | 2.0                          |      |           | V        |
| $V_{IL}$        | Low-Level Input Voltage               |  | 3.0 to 3.6   |                              |      | 0.8       | V        |
| $I_{IN}$        | Input Leakage Current                 | $0 \leq V_{IN} \leq 3.6V$                              | 3.6          |                              |      | $\pm 1.0$ | $\mu A$  |
| $I_{OFF}$       | Off-State Leakage Current             | $0 \leq A, B \leq V_{CC}$                              | 3.6          |                              |      | $\pm 1.0$ | $\mu A$  |
| $R_{ON}$        | Switch On Resistance <sup>(3)</sup>   | $V_{IN} = 0.8V, I_{ON} = 8mA$                          | 3.0          |                              | 5    | 7         | $\Omega$ |
|                 |                                       | $V_{IN} = 3.0V, I_{ON} = 8mA$                          | 3.0          |                              | 4.5  | 6.5       |          |
| $\Delta R_{ON}$ | Delta $R_{ON}$                        | $V_{IN} = 0.8V, V_{IN} = 0V - 1.5V,$<br>$I_{ON} = 8mA$ | 3.0          |                              | 0.3  |           | $\Omega$ |
| $R_{FLAT(ON)}$  | On Resistance Flatness <sup>(4)</sup> | $I_{OUT} = 8mA$  | 3.0          |                              | 1    |           | $\Omega$ |
| $I_{CC}$        | Quiescent Supply Current              | $V_{IN} = V_{CC}$ or GND,<br>$I_{OUT} = 0$             | 3.6          |                              |      | 1         | $\mu A$  |

### Notes:

3. Measured by the voltage drop between the A and B pins at the indicated current through the switch. On resistance is determined by the lower of the voltages on the A or B pins.
4. Flatness is defines as the difference between the maximum and the minimum value on resistance over the specified range of conditions.

## AC Electrical Characteristics

Typical values are at  $V_{CC} = 3.3V$  and  $T_A = 25^\circ C$ .

| Symbol     | Parameter                         | Condition                         | $V_{CC}(V)$ | Typ. | Max. | Unit | Figure                |
|------------|-----------------------------------|-----------------------------------|-------------|------|------|------|-----------------------|
| $t_{ON}$   | Turn-On Time<br>S-to-Bus B        | $V_B = 0.8V$                      | 3.0 to 3.6  | 4.8  | 7.0  | ns   | Figure 9<br>Figure 10 |
| $t_{OFF}$  | Turn-Off Time<br>S-to-Bus B       | $V_B = 0.8V$                      | 3.0 to 3.6  | 2.2  | 4.0  | ns   | Figure 9<br>Figure 10 |
| $t_{PD}$   | Propagation Delay                 | $C_L = 10pF$                      | 3.0 to 3.6  | 0.25 |      | ns   | Figure 14             |
| $O_{IRR}$  | Non-Adjacent Off<br>Isolation     | $f = 250MHz,$<br>$R_L = 50\Omega$ | 3.0 to 3.6  | -26  |      | dB   | Figure 11             |
| $X_{TALK}$ | Non-Adjacent<br>Channel Crosstalk | $f = 250MHz,$<br>$R_L = 50\Omega$ | 3.0 to 3.6  | -45  |      | dB   | Figure 12             |
| BW         | -3dB Bandwidth                    | $R_L = 50\Omega, C_L = 0pF$       | 3.0 to 3.6  | 750  |      | MHz  | Figure 13             |
|            |                                   | $R_L = 50\Omega, C_L = 5pF$       |             | 435  |      |      |                       |

## USB Related AC Electrical Characteristics

Typical values are at  $V_{CC} = 3.3V$  and  $T_A = 25^\circ C$ .

| Symbol      | Parameter  | Condition   | $V_{CC} (V)$ | Typ.  | Unit | Figure                 |
|-------------|--|---|--------------|-------|------|------------------------|
| $t_{SK(O)}$ | Channel-to Channel<br>Skew                           | $C_L = 10pF$  | 3.0 to 3.6   | 0.051 | ns   | Figure 14<br>Figure 16 |
| $t_{SK(P)}$ | Skew of Opposite<br>Transition of the<br>Same Output | $C_L = 10pF$  | 3.0 to 3.6   | 0.020 | ns   | Figure 14<br>Figure 16 |
| $T_J$       | Total Jitter   | $R_L = 50\Omega, C_L = 10pF$<br>$t_R = t_F = 750ps$ at 480MPs | 3.0 to 3.6   | 0.170 | ns   |                        |

## Capacitance

Typical values are at  $V_{CC} = 3.3V$  and  $T_A = 25^\circ C$ .

| Symbol    | Parameter                     | Condition                 | Typ. | Unit |
|-----------|-------------------------------|---------------------------|------|------|
| $C_{IN}$  | Control Pin Input Capacitance | $V_{CC} = 0V$             | 2.5  | pF   |
| $C_{ON}$  | A/B On Capacitance            | $V_{CC} = 3.3V, /OE = 0V$ | 12.0 | pF   |
| $C_{OFF}$ | Port B Off Capacitance        | $V_{CC}$ and $/OE = 3.3V$ | 4.5  | pF   |

## Performance Characteristics




Figure 5. Gain vs. Frequency




Figure 6. Off Isolation




Figure 7. Crosstalk






Figure 8.  $R_{ON}$

## AC Loadings and Waveforms




Notes: Input driven by 50Ω source terminated in 50Ω.  
 $C_L$  includes load and stray capacitance.  
 Input PRR-1.0MHz,  $t_w = 500ns$ .


**Figure 9. AC Test Circuit**



**Figure 10. AC Waveforms**



**Figure 11. Off Isolation Test**



**Figure 12. Crosstalk Test**



### AC Loadings and Waveforms




Figure 13. Bandwidth Test




Figure 14. Propagation Delay




Figure 15. Pulse Skew  $t_{SP(P)}$




Figure 16. Output Skew  $t_{SK(O)}$

## Physical Dimensions





Figure 17. 10-Lead MicroPak™, 1.6 x 2.1mm

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:  
<http://www.fairchildsemi.com/packaging/>

For current tape and reel specifications, visit Fairchild Semiconductor's online packaging area:  
[http://www.fairchildsemi.com/products/logic/pdf/micropak\\_tr.pdf](http://www.fairchildsemi.com/products/logic/pdf/micropak_tr.pdf)

## Physical Dimensions



### NOTES:

- A. CONFORMS TO JEDEC REGISTRATION MO-241, VARIATION AA
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994

MLP14ArevA

**Figure 18. 14-Terminal Depopulation Quad Very-Thin Flat Pack No Lead (DQFN), JEDEC MO-241, 2.5 X 3.0mm**

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.


Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:

<http://www.fairchildsemi.com/packaging/>

For current tape and reel specifications, visit Fairchild Semiconductor's online packaging area:

<http://www.fairchildsemi.com/ms/MS/MS-522.pdf>

## Physical Dimensions



**Figure 19. 10-Lead Molded Small Outline Package (MSOP), JEDEC MO-187, 3.0mm Wide**

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:  
<http://www.fairchildsemi.com/packaging/>

For current tape and reel specifications, visit Fairchild Semiconductor's online packaging area:  
[http://www.fairchildsemi.com/products/analog/pdf/msop10\\_tr.pdf](http://www.fairchildsemi.com/products/analog/pdf/msop10_tr.pdf)



**TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

- |  |  |  |   |
|--|--|--|---|
| 2Cool™   | F-PFS™   | PowerTrench®   | The Power Franchise®  |
| AccuPower™   | FRFET®   | PowerXS™   | the <b>power</b> franchise  |
| AX-CAP™*   | Global Power Resource™                         | Programmable Active Droop™   | TinyBoost™  |
| BitSiC™  | GreenBridge™                                   | QFET®  | TinyBuck™   |
| Build it Now™  | Green FPS™                                     | QS™  | TinyCalc™   |
| CorePLUS™  | Green FPS™ e-Series™                           | Quiet Series™  | TinyLogic®  |
| CorePOWER™   | Gmax™  | RapidConfigure™  | TINYOPTO™   |
| CROSSVOLT™   | GTO™   |  ™                | TinyPower™  |
| CTL™   | IntelliMAX™                                    | Saving our world, 1mW/W/kW at a time™  | TinyPWM™  |
| Current Transfer Logic™  | ISOPLANAR™                                     | SignalWise™  | TinyWire™   |
| DEUXPEED®  | Making Small Speakers Sound Louder and Better™ | SmartMax™  | TranSiC™  |
| Dual Cool™   | MegaBuck™                                      | SMART START™   | TriFault Detect™  |
| EcoSPARK®  | MICROCOUPLER™                                  | Solutions for Your Success™  | TRUECURRENT®*   |
| EfficientMax™  | MicroFET™                                      | SPM®   | µSerDes™  |
| ESBC™  | MicroPak™                                      | STEALTH™   |  SerDes™ |
|  Fairchild® | MicroPak2™                                     | SuperFET®  | UHC®  |
| Fairchild Semiconductor®   | MillerDrive™                                   | SuperSOT™-3  | Ultra FRFET™  |
| FACT Quiet Series™   | MotionMax™                                     | SuperSOT™-6  | UniFET™   |
| FACT®  | Motion-SPM™                                    | SuperSOT™-8  | VCX™  |
| FAST®  | mWSaver™                                       | SupreMOS®  | VisualMax™  |
| FastvCore™   | OptoHiT™                                       | SyncFET™   | VoltagePlus™  |
| FETBench™  | OPTOLOGIC®                                     | Sync-Lock™   | XS™   |
| FlashWriter®*  | OPTOPLANAR®                                    |  SYSTEM GENERAL®* |   |
| FPS™   |  |  |   |

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**ANTI-COUNTERFEITING POLICY**

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

**PRODUCT STATUS DEFINITIONS**

**Definition of Terms**

| Datasheet Identification | Product Status        | Definition  |
|--------------------------|-----------------------|---|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.   |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.   |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.  |

Rev. I61

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local  
Sales Representative

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Switch ICs](#) category:*

*Click to view products by [ON Semiconductor](#) manufacturer:*

Other Similar products are found below :

[NLAS7213MUTBG](#) [FSA221UMX](#) [FSUSB31UMX](#) [FSA806UMX](#) [NLAS7222AMTR2G](#) [NL3S2223MUTBG](#) [TC7USB3212WBG\(ELAH](#)  
[PI3USB31531ZLCEX](#) [PI3USB31532ZLCEX](#) [PI5USB31213XEAEX](#) [BD91N01NUX-E2](#) [MP5030DGQH-Z](#) [NL3S22AHMUTAG](#)  
[NL3S22UHMUTAG](#) [FSA9280AUMX](#) [NLAS7242MUTBG](#) [HD3SS460RHRT](#) [TPS2549IRTERQ1](#) [PI2USB4122ZHEX](#) [TS5USBC402IYFPT](#)  
[NS5S1153MUTAG](#) [FSUSB11MTCX](#) [FSUSB42MUX](#) [FT234XD-R](#) [PI3USB102GZLEX](#) [P6KE110A](#) [SMAJ200A](#) [SMAJ70CA](#) [SMAJ11A](#)  
[SMAJ140CA](#) [SMAJ14A](#) [SMAJ160CA](#) [SMAJ250A](#) [SMAJ51CA](#) [SMAJ5.0CA](#) [30KP400CA](#) [1SMB5.0AT3G](#) [MAX4717ETB+T](#)  
[MAX4989ETD+T](#) [MAX4717EBCT](#) [MAX4717EUB+](#) [MAX4906ELB+T](#) [MAX4899EETE+](#) [MAX4906EFELB+T](#) [MAX4907FELA+T](#)  
[MAX4907ELA+T](#) [MAX4983EEVB+T](#) [MAX4984EEVB+T](#) [MAX4899AEETE+T](#) [MAX14618ETA+T](#)