

# **KBL005 - KBL10 Bridge Rectifiers**

May 2009

## **Features**

- Ideal for printed circuit board .
- · Reliable low cost construction.
- · High surge current capability.
- UL certified, UL #E326243.



# **Absolute Maximum Ratings \*** T<sub>A</sub> = 25 °C unless otherwise noted

Symbol	Parameter	Value						Units	
		005	01	02	04	06	08	10	Units
$V_{RRM}$	Maximum Repetitive Reverse Voltage	50	100	200	400	600	800	1000	V
V <sub>RMS</sub>	Maximum RMS Bridge Input Voltage         35         70         140         280         420         560         700		700	V					
V <sub>R</sub>	DC Reverse Voltage (Rated V <sub>R</sub> )	50	100	200	400	600	800	1000	V
I <sub>F(AV)</sub>	Average Recitified Forward Current, @ $T_A = 50$ °C				4.0				Α
I <sub>FSM</sub>	Non-Repetitive Peak Forward Surge Current 8.3ms Single Half-Sine-Wave	200			Α				
T <sub>STG</sub>	Storage Temperature Range	-55 to +150		°C					
T <sub>J</sub>	Operating Junction Temperature	-55 to +150		°C					

<sup>\*</sup> These ratings are limiting values above which the serviceability of any semiconductor device may by impaired.

## **Thermal Characteristics**


Symbol	Parameter	Value	Units	
$P_{D}$	Power Dissipation	6.58	W	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient, * per leg	19	°C/W	
$R_{\theta JL}$	Thermal Resistance, Junction to Lead, * per leg	2.4	°C/W	

<sup>\*</sup> Device mounted on PCB with 0.375 " (9.5 mm) lead length and 0.5 x 0.5" (13 x 13 mm) copper pads.

# **Electrical Characteristics** $T_A = 25$ °C unless otherwise noted

Symbol	Parameter	Value Units	
V <sub>F</sub>	Forward Voltage, per bridge @ 4.0A	1.1	V
I <sub>R</sub>	Reverse Current, total bridge @ Rated $V_R$ $T_A = 25^{\circ}C$ $T_A = 100^{\circ}C$	5.0 500	μ <b>Α</b> μ <b>Α</b>

# **Typical Performance Characteristics**






Figure 3. Forward Voltage Characteristics

 $\begin{array}{ccc} 0.8 & 1 & 1.2 \\ \textbf{Forward Voltage, V}_{\textbf{F}} \textbf{[V]} \end{array}$ 




Figure 2. Forward Current Derating Curve




Figure 4. Reverse Current vs Reverse Voltage

Forward Current, I<sub>F</sub> [A]

0.01





#### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

Auto-SPM™ Build it Now™ CorePLUS™ CorePOWER™

CROSSVOLT™ **CTL™** Current Transfer Logic™ EcoSPARK® EfficentMax™ EZSWITCH™\*

Fairchild<sup>®</sup> Fairchild Semiconductor® FACT Quiet Series™ FAST® FastvCore™

FETBench™ FlashWriter®\* **FPSTM** 

F-PFS™ FRFFT® Global Power Resource SM

Green FPS™ Green FPS™ e-Series™

Gmax™ GTO™ IntelliMAX™ ISOPLANAR™ MegaBuck™ MICROCOUPLER™ MicroFET™

MicroPak™ MillerDrive™ MotionMax™ Motion-SPM™ OPTOLOGIC® OPTOPLANAR®

PDP SPM™ Power-SPM™ PowerTrench® PowerXS™

Programmable Active Droop™

QFĔT<sup>0</sup> QS™ Quiet Series™ RapidConfigure™

Saving our world, 1mW/W/kW at a time™ SmartMax™ SMART START™ SPM<sup>®</sup>

STEALTH™ SuperFET™ SuperSOT™-3 SuperSOT™-6

SuperSOT™-8 SupreMOS™ . SyncFET™ Sync-Lock™

SYSTEM ®\*

GENERAL The Power Franchise®

puwer TinyBoost™ TinyBuck™ TinyLogic<sup>®</sup> TINYOPTO™ TinyPower™ TinyPWM™ TinyWire™ TriFault Detect™ TRUECURRENT™\* μSerDes™

UHC Ultra FRFET™ UniFFT™  $VCX^{TM}$ 

VisualMax™ XSTM

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

## As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- 2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### **ANTI-COUNTERFEITING POLICY**

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### **PRODUCT STATUS DEFINITIONS**

## Definition of Terms

Definition of Terms				
Datasheet Identification	Product Status	Definition		
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		

Rev 140

<sup>\*</sup> Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ON Semiconductor manufacturer:

Other Similar products are found below:

1.5SMC82AT3G 74LCX574WM FST3126MX MC78L08ACP MMBTA42 FDD8424H\_F085A NTZD3154NT1H KSA1015GRTA
BAT42XV2 007851X 702607H MC33079DG MC34072DR2G MC34151P MC78L08ACDG 74VHC14MX 74VHC541MTCX
FAN3111ESX FDMC86262P FDMD8530 FEBFL7733A\_L53U021A FEBFOD8333 MM74HC138MX MMBZ5233B FOD3120SD
FPAB30BH60B FQP2N80 1.5KE16AG MT9V115EBKSTCH-GEVB NB6L295MNGEVB NB7L1008MNGEVB NC7WZ126K8X
NCL30000LED2GEVB NCN9252MUGEVB NCP1075PSRGEVB NCV4274CDT33RKG NCV887100D1R2G NDT2955 1N5339B
NSIC2030JBT3G NV890231MWTXGEVB CAT4101AEVB KA7818ETU S3JB 2SC5569-TD-E FEBFL7734\_L55L008A 1V5KE39CA
FNB33060T AMIS30422DBGEVB AMIS3062XGEVK