




MAC4DLM**Description**

The MAC4DLM is designed for high volume, low cost, industrial and consumer applications such as motor control, process control, temperature, light and speed control.

Features

- Small Size Surface Mount DPAK Package
- Passivated Die for Reliability and Uniformity
- Four-Quadrant Triggering
- Blocking Voltage to 600 V
- On-State Current Rating of 4.0 A RMS at 93°C
- Low Level Triggering and Holding Characteristics
- Epoxy Meets UL 94 V-0 @ 0.125 in
- ESD Ratings: Human Body Model, 3B > 8000 V
Machine Model, C > 400V
- Lead-Free Packages are Available

Pin Out**Functional Diagram**

Thyristors

Surface Mount – 600V > MAC4DLM

Maximum Ratings ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Note 1) (Gate Open, Sine Wave 50 to 60 Hz, $T_J = -40^\circ$ to 110°C)	$V_{DRM'}$ V_{RRM}	600	V
On-State RMS Current (Full Cycle Sine Wave, 60 Hz, $T_c = 93^\circ\text{C}$)	$I_T (\text{RMS})$	4.0	A
Peak Non-Repetitive Surge Current (One Full Cycle Sine Wave, 60 Hz, $T_c = 110^\circ\text{C}$)	I_{TSM}	40	A
Circuit Fusing Consideration ($t = 8.3 \text{ msec}$)	I^2t	6.6	A^2sec
Peak Gate Current (Pulse Width $\leq 20 \mu\text{sec}$, $T_c = 93^\circ\text{C}$)	I_{GM}	4.0	A
Peak Gate Power (Pulse Width $\leq 10 \mu\text{sec}$, $T_c = 93^\circ\text{C}$)	P_{GM}	2.0	W
Peak Gate Voltage (Pulse Width $\leq 20 \mu\text{sec}$, $T_c = 93^\circ\text{C}$)	V_{GM}	5.0	V
Average Gate Power ($t = 8.3 \text{ msec}$, $T_c = 108^\circ\text{C}$)	$P_{G(AV)}$	1.0	W
Operating Junction Temperature Range	T_J	-40 to +110	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-40 to +150	$^\circ\text{C}$

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

Thermal Characteristics

Rating	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case (AC)	$R_{e_{JC}}$	3.5	
Junction-to-Ambient	$R_{e_{JA}}$	88	
Junction-to-Ambient (Note 2)	$R_{e_{JA}}$	80	$^\circ\text{C}/\text{W}$
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 10 seconds	T_L	260	$^\circ\text{C}$

2. These ratings are applicable when surface mounted on the minimum pad sizes recommended.

3. 1/8" from case for 10 seconds.

Electrical Characteristics - OFF ($T_J = 25^\circ\text{C}$ unless otherwise noted ; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
Peak Repetitive Blocking Current ($V_D = V_{DRM} = V_{RRM}$; Gate Open)	$I_{DRM'}$ I_{RRM}	-	-	0.01	mA
$T_J = 25^\circ\text{C}$		-	-	2.0	

Electrical Characteristics - ON ($T_J = 25^\circ\text{C}$ unless otherwise noted; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
Peak On-State Voltage (Note 4) ($I_{TM} = \pm 6.0 \text{ A}$)	V_{TM}	-	1.3	1.6	V
Gate Trigger Current (Continuous dc) ($V_D = 12 \text{ V}$, $R_L = 100 \Omega$)	I_{GT}	MT2(+), G(+)	-	1.8	3.0
		MT2(+), G(-)	-	2.1	3.0
		MT2(-), G(-)	-	2.4	3.0
		MT2(-), G(+)	-	4.2	5.0
Holding Current ($V_D = 12 \text{ V}$, Gate Open, Initiating Current = $\pm 200 \text{ mA}$)	I_H	-	1.5	15	mA
Gate Non-Trigger Voltage (Continuous dc) - ($V_D = 12 \text{ V}$, $R_L = 100 \Omega$, $T_J = 110^\circ\text{C}$) All Four Quadrants	V_{GD}	0.1	0.4	-	V
Latch Current	I_L	($V_D = 12 \text{ V}$, $I_G = 5.0 \text{ mA}$) MT2(+), G(+)	-	1.75	10
		($V_D = 12 \text{ V}$, $I_G = 5.0 \text{ mA}$) MT2(+), G(-)	-	5.2	10
		($V_D = 12 \text{ V}$, $I_G = 5.0 \text{ mA}$) MT2(-), G(-)	-	2.1	10
		($V_D = 12 \text{ V}$, $I_G = 10 \text{ mA}$) MT2(-), G(+)	-	2.2	10
Gate Trigger Voltage (Continuous dc) ($V_D = 12 \text{ V}$, $R_L = 100 \Omega$)	V_{GT}	MT2(+), G(+)	0.5	0.62	1.3
		MT2(+), G(-)	0.5	0.57	1.3
		MT2(-), G(-)	0.5	0.65	1.3
		MT2(-), G(+)	0.5	0.74	1.3

4. Indicates Pulse Test: Pulse Width $\leq 2.0 \text{ ms}$, Duty Cycle $\leq 2\%$.


Dynamic Characteristics

Characteristic	Symbol	Min	Typ	Max	Unit
Rate of Change of Commutating Current ($V_D = 200$ V, $I_{TM} = 1.8$ A, Commutating $dv/dt = 1.0$ V/ μ sec, $T_J = 110^\circ\text{C}$, $f = 250$ Hz, $CL = 5.0$ μ fd, $LL = 80$ mH, $RS = 56$ Ω , CS = 0.03 μ fd) With snubber see Figure 11	$(dl/dt)_C$	-	3.0	-	A/ μ s
Critical Rate of Rise of Off-State Voltage ($V_D = 0.67 \times V_{DRM}$, Exponential Waveform, Gate Open, $T_J = 110^\circ\text{C}$)	dV/dt	10	-	-	V/ μ s

Voltage Current Characteristic of SCR

Symbol	Parameter
V_{DRM}	Peak Repetitive Forward Off State Voltage
I_{DRM}	Peak Forward Blocking Current
V_{RRM}	Peak Repetitive Reverse Off State Voltage
I_{RRM}	Peak Reverse Blocking Current
V_{TM}	Maximum On State Voltage
I_H	Holding Current

Quadrant Definitions for a Triac



All Polarities are referenced to MT1.
With in-phase signals (using standard AC lines) quadrants I and III are used










Figure 1. Typical RMS Current Derating

Figure 2. On-State Power Dissipation

Figure 3. On-State Characteristics

Figure 4. Transient Thermal Response

Figure 5. Typical Gate Trigger Current vs. Junction Temperature

Figure 6. Typical Gate Trigger Voltage vs. Junction Temperature


Figure 7. Typical Holding Current vs. Junction Temperature




Figure 8. Typical Latching Current vs. Junction Temperature




Figure 9. Exponential Static dv/dt vs. Gate-MT1 Resistance, MT2(+)




Figure 10. Exponential Static dv/dt vs. Gate-MT1 Resistance, MT2(-)







Figure 11. Simplified Test Circuit to Measure the Critical Rate of Rise of Commutating Current (di/dt)



Dimensions



Soldering Footprint



SCALE 3:1 (mm/inches)

Dim	Inches		Millimeters	
	Min	Max	Min	Max
A	0.087	0.094	2.20	2.40
A1	0.000	0.005	0.00	0.12
b	0.022	0.030	0.55	0.75
b2	0.026	0.033	0.65	0.85
b3	0.209	0.217	5.30	5.50
c	0.019	0.023	0.49	0.59
c2	0.019	0.023	0.49	0.59
D	0.213	0.224	5.40	5.70
E	0.252	0.260	6.40	6.60
e	0.091		2.30	
H	0.374	0.406	9.50	10.30
L	0.058	0.070	1.47	1.78
L1	0.114		2.90	
L2	0.019	0.023	0.49	0.59
L3	0.053	0.065	1.35	1.65
L4	0.028	0.039	0.70	1.00
Z	0.154	-	3.90	-

1. Dimensioning and tolerancing per ANSI Y14.5M, 1982.

2. Controlling Dimension: Inch. Style 6: Pin 1. MT1

3. MT2

4. Gate


5. MT2

Thyristors


Surface Mount – 600V > MAC4DLM

Dimensions



DPAK-3
Case 369D
T0251-3L POD




Part Marking System



DPAK-3
Case 369C
Style 6



DPAK-3
Case 369D
Style 6



AC4DCx =Device Code
 x =D, M, or N
 Y =Year
 M =Month
 A =Assembly Site
 XX =Lot Serial Code
 G =Pb-Free Package

Dim	Inches		Millimeters	
	Min	Max	Min	Max
A	0.213	0.224	5.40	5.70
B	0.252	0.260	6.40	6.60
C	0.087	0.094	2.20	2.40
D	0.024	0.030	0.60	0.75
E	0.022	0.026	0.55	0.65
F	0.022	0.03	0.58	0.78
G	0.091		2.30	
H	0.046	0.050	1.18	1.28
J	0.019	0.023	0.49	0.59
K	0.291	0.315	7.40	8.00
N	0.030	0.038	0.78	0.98
R	0.209	0.217	5.30	5.50
S	0.063		1.60	
V	0.053	0.065	1.35	1.65
Z	0.150		3.80	

1. Dimensioning and Tolerancing Per ANSI Y14.5M, 1982.

2. Controlling Dimension: Inch.

STYLE 6:Pin 1. MT1

2. MT2

3. Gate

4. MT2

Pin Assignment

1	Main Terminal 1
2	Main Terminal 2
3	Gate
4	Main Terminal 2

Ordering Information

Device	Package Type	Package	Shipping
MAC4DLM-001	DPAK-3	369D	4000 Units / Box
MAC4DLM-001G	DPAK-3 (Pb-Free)	369D	4000 Units / Box
MAC4DLMT4	DPAK-3	369C	2500 / Tape & Reel
MAC4DLMT4G	DPAK-3 (Pb-Free)	369C	2500 / Tape & Reel

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littelfuse.com/disclaimer-electronics

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Triacs](#) category:

Click to view products by [ON Semiconductor manufacturer:](#)

Other Similar products are found below :

[CTA08-1000CW](#) [CTB24-800BW](#) [CTA08-1000C](#) [CTA12-800BWPT](#) [CTA16-1000B](#) [CTB24-800B](#) [BT137-600-0Q](#) [5615](#) [OT415Q](#) [2N6075A](#)
[NTE5629](#) [NTE5688](#) [CTB08-400CW](#) [D31410](#) [BTA425Z-800BTQ](#) [KS100N12](#) [TOPT16-800C0,127](#) [OT408,135](#) [BT134-800E](#) [BT136D](#)
[BTB16Q-600BW](#) [Z0409MF](#) [BTA04-600B](#) [BTA06-600BRG](#) [BTA06-800BWRG](#) [BTA08-600BRG](#) [BTA08-800B](#) [BT136-600,127](#)
[MAC97A6,116](#) [BT137-600E,127](#) [BTB16-600CW3G](#) [BTB16-600CW3G](#) [Z0109MN,135](#) [T825T-6I](#) [T1220T-6I](#) [NTE5638](#) [ACST1235-8FP](#)
[BT136X-600E,127](#) [MAC4DLM-1G](#) [BT134-600D,127](#) [BTA08-600BW3G](#) [NTE56008](#) [NTE56017](#) [NTE56018](#) [NTE56059](#) [NTE5608](#)
[NTE5609](#) [NTE5656](#) [NTE56020](#) [NTE56022](#)