

NTJD4105C

MOSFET – Small Signal, Complementary, SC-88 20 V / -8.0 V, +0.63 A / -0.775 A

Features

- Complementary N and P Channel Device
- Leading -8.0 V Trench for Low $R_{DS(on)}$ Performance
- ESD Protected Gate – ESD Rating: Class 1
- SC-88 Package for Small Footprint (2 x 2 mm)
- Pb-Free Packages are Available

Applications

- DC-DC Conversion
- Load/Power Switching
- Single or Dual Cell Li-Ion Battery Supplied Devices
- Cell Phones, MP3s, Digital Cameras, PDAs

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Value | Unit | |
|---|--------------------------|--------------------------|-----------|------------------|
| Drain-to-Source Voltage | N-Ch | V_{DSS} | 20 | V |
| | P-Ch | | -8.0 | |
| Gate-to-Source Voltage | N-Ch | V_{GS} | ± 12 | V |
| | P-Ch | | ± 8.0 | |
| Continuous Drain Current – Steady State (Based on $R_{\theta JA}$) | N-Ch | $T_A = 25^\circ\text{C}$ | 0.63 | A |
| | | $T_A = 85^\circ\text{C}$ | 0.46 | |
| | P-Ch | $T_A = 25^\circ\text{C}$ | -0.775 | |
| | | $T_A = 85^\circ\text{C}$ | -0.558 | |
| Continuous Drain Current – Steady State (Based on $R_{\theta JL}$) | N-Ch | $T_A = 25^\circ\text{C}$ | 0.91 | |
| | | $T_A = 85^\circ\text{C}$ | 0.65 | |
| | P-Ch | $T_A = 25^\circ\text{C}$ | -1.1 | |
| | | $T_A = 85^\circ\text{C}$ | -0.8 | |
| Pulsed Drain Current | $tp \leq 10 \mu\text{s}$ | I_{DM} | ± 1.2 | A |
| Power Dissipation – Steady State (Based on $R_{\theta JA}$) | $T_A = 25^\circ\text{C}$ | P_D | 0.27 | W |
| | $T_A = 85^\circ\text{C}$ | | 0.14 | |
| Power Dissipation – Steady State (Based on $R_{\theta JL}$) | $T_A = 25^\circ\text{C}$ | | 0.55 | |
| | $T_A = 85^\circ\text{C}$ | | 0.29 | |
| Operating Junction and Storage Temperature | T_J, T_{STG} | -55 to 150 | | $^\circ\text{C}$ |
| Source Current (Body Diode) | N-Ch | I_S | 0.63 | A |
| | P-Ch | | -0.775 | |
| Lead Temperature for Soldering Purposes (1/8" from case for 10 s) | T_L | 260 | | $^\circ\text{C}$ |

THERMAL RESISTANCE RATINGS (Note 1)

| Parameter | Typ | Max | Unit | |
|---|-----|-----------------|------|---------------------------|
| Junction-to-Ambient – Steady State | Typ | $R_{\theta JA}$ | 400 | $^\circ\text{C}/\text{W}$ |
| | Max | | 460 | |
| Junction-to-Lead (Drain) – Steady State | Typ | $R_{\theta JL}$ | 194 | |
| | Max | | 226 | |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.



1. Surface mounted on FR4 board using 1 oz Cu area = 0.9523 in sq.



ON Semiconductor®

<http://onsemi.com>

| $V_{(BR)DSS}$ | $R_{DS(on)}$ TYP | I_D Max |
|---------------|------------------------|-----------|
| N-Ch 20 V | 0.29 Ω @ 4.5 V | 0.63 A |
| | 0.36 Ω @ 2.5 V | |
| P-Ch -8.0 V | 0.22 Ω @ -4.5 V | -0.775 A |
| | 0.32 Ω @ -2.5 V | |
| | 0.51 Ω @ -1.8 V | |



TC = Device Code
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 7 of this data sheet.

NTJD4105C

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

| Parameter | Symbol | N/P | Test Condition | Min | Typ | Max | Units | |
|---|---------------------------------------|-----|---|--------------------------|------------------------|-------|-------|------|
| OFF CHARACTERISTICS | | | | | | | | |
| Drain-to-Source Breakdown Voltage | V _{(BR)DSS} | N | V _{GS} = 0 V | I _D = 250 μA | 20 | 27 | V | |
| | | P | | I _D = -250 μA | -8.0 | -10.5 | | |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | V _{(BR)DSS} / T _J | N | | | | 22 | mV/°C | |
| | | P | | | | | | -6.0 |
| Zero Gate Voltage Drain Current | I _{DSS} | N | V _{GS} = 0 V, V _{DS} = 16 V | T _J = 25 °C | | | 1.0 | μA |
| | | P | V _{GS} = 0 V, V _{DS} = -6.4 V | | | | 1.0 | |
| Gate-to-Source Leakage Current | I _{GSS} | N | V _{DS} = 0 V | V _{GS} = ±12 V | | | 10 | μA |
| | | P | | | V _{GS} = ±8.0 | | | |

ON CHARACTERISTICS (Note 2)

| | | | | | | | | |
|--|--------------------------------------|---|--|--------------------------|-------|-------|-------|--------|
| Gate Threshold Voltage | V _{GS(TH)} | N | V _{GS} = V _{DS} | I _D = 250 μA | 0.6 | 0.92 | 1.5 | V |
| | | P | | I _D = -250 μA | -0.45 | -0.83 | -1.0 | |
| Gate Threshold Temperature Coefficient | V _{GS(TH)} / T _J | N | | | | -2.1 | | -mV/°C |
| | | P | | | | | 2.2 | |
| Drain-to-Source On Resistance | R _{DS(on)} | N | V _{GS} = 4.5 V, I _D = 0.63 A | | | 0.29 | 0.375 | Ω |
| | | P | V _{GS} = -4.5 V, I _D = -0.57 A | | | 0.22 | 0.30 | |
| | | N | V _{GS} = 2.5 V, I _D = 0.40 A | | | 0.36 | 0.445 | |
| | | P | V _{GS} = -2.5 V, I _D = -0.48 A | | | 0.32 | 0.46 | |
| | | P | V _{GS} = -1.8 V, I _D = -0.20 A | | | 0.51 | 0.90 | |
| Forward Transconductance | g _{FS} | N | V _{DS} = 4.0 V, I _D = 0.63 A | | | 2.0 | | S |
| | | P | V _{DS} = -4.0 V, I _D = -0.57 A | | | 2.0 | | |

CHARGES AND CAPACITANCES

| | | | | | | | | | |
|------------------------------|---------------------|---|---|---|-----|-----|-----|----|----|
| Input Capacitance | C _{ISS} | N | f = 1 MHz, V _{GS} = 0 V | V _{DS} = 20 V | | 33 | 46 | pF | |
| | | P | | V _{DS} = -8.0V | | 160 | 225 | | |
| Output Capacitance | C _{OSS} | N | | V _{DS} = 20 V | | 13 | 22 | | |
| | | P | | V _{DS} = -8.0 V | | 38 | 55 | | |
| Reverse Transfer Capacitance | C _{RSS} | N | | V _{DS} = 20 V | | 2.8 | 5.0 | | |
| | | P | | V _{DS} = -8.0 V | | 28 | 40 | | |
| Total Gate Charge | Q _{G(TOT)} | N | | V _{GS} = 4.5 V, V _{DS} = 10 V, I _D = 0.7 A | | 1.3 | 3.0 | | nC |
| | | P | | V _{GS} = -4.5 V, V _{DS} = -5.0 V, I _D = -0.6 A | | 2.2 | 4.0 | | |
| Threshold Gate Charge | Q _{G(TH)} | N | | V _{GS} = 4.5 V, V _{DS} = 10 V, I _D = 0.7 A | | 0.1 | | | |
| | | P | | V _{GS} = -4.5 V, V _{DS} = -5.0 V, I _D = -0.6 A | | 0.1 | | | |
| Gate-to-Source Charge | Q _{GS} | N | V _{GS} = 4.5 V, V _{DS} = 10 V, I _D = 0.7 A | | 0.2 | | | | |
| | | P | V _{GS} = -4.5 V, V _{DS} = -5.0 V, I _D = -0.6 A | | 0.5 | | | | |
| Gate-to-Drain Charge | Q _{GD} | N | V _{GS} = 4.5 V, V _{DS} = 10 V, I _D = 0.7 A | | 0.4 | | | | |
| | | P | V _{GS} = -4.5 V, V _{DS} = -5.0 V, I _D = -0.6 A | | 0.5 | | | | |

SWITCHING CHARACTERISTICS (Note 3)

| | | | | | | | |
|---------------------|---------------------|---|--|--|-------|--|----|
| Turn-On Delay Time | t _{d(ON)} | N | V _{GS} = 4.5 V, V _{DD} = 10 V, I _D = 0.5 A, R _G = 20 Ω | | 0.083 | | μs |
| Rise Time | t _r | | | | 0.227 | | |
| Turn-Off Delay Time | t _{d(OFF)} | | | | 0.786 | | |
| Fall Time | t _f | | | | 0.506 | | |
| Turn-On Delay Time | t _{d(ON)} | P | V _{GS} = -4.5 V, V _{DD} = -4.0 V, I _D = -0.5 A, R _G = 8.0 Ω | | 0.013 | | |
| Rise Time | t _r | | | | 0.023 | | |
| Turn-Off Delay Time | t _{d(OFF)} | | | | 0.050 | | |
| Fall Time | t _f | | | | 0.036 | | |

DRAIN-SOURCE DIODE CHARACTERISTICS

| | | | | | | | | |
|-----------------------|-----------------|---|---|--------------------------|--|-------|-----|----|
| Forward Diode Voltage | V _{SD} | N | V _{GS} = 0 V, T _J = 25°C | I _S = 0.23 A | | 0.76 | 1.1 | V |
| | | P | | I _S = -0.23 A | | 0.76 | 1.1 | |
| | | N | V _{GS} = 0 V, T _J = 125°C | I _S = 0.23 A | | 0.63 | | |
| | | P | | I _S = -0.23 A | | 0.63 | | |
| Reverse Recovery Time | t _{RR} | N | V _{GS} = 0 V, d _{IS} /d _t = 90 A/μs | I _S = 0.23 A | | 0.410 | | μs |
| | | P | | I _S = -0.23 A | | 0.078 | | |

2. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%.

3. Switching characteristics are independent of operating junction temperatures.

NTJD4105C

TYPICAL N-CHANNEL PERFORMANCE CURVES ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Temperature




Figure 4. On-Resistance vs. Drain Current and Temperature




Figure 5. On-Resistance Variation with Temperature




Figure 6. Capacitance Variation

NTJD4105C

TYPICAL N-CHANNEL PERFORMANCE CURVES ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 7. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 8. Diode Forward Voltage vs. Current

NTJD4105C

TYPICAL P-CHANNEL PERFORMANCE CURVES ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 9. On-Region Characteristics




Figure 10. Transfer Characteristics




Figure 11. On-Resistance vs. Drain Current and Temperature




Figure 12. On-Resistance vs. Drain Current and Temperature




Figure 13. On-Resistance Variation with Temperature




Figure 14. Capacitance Variation

NTJD4105C

TYPICAL P-CHANNEL PERFORMANCE CURVES ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 15. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 16. Diode Forward Voltage vs. Current

NTJD4105C

ORDERING INFORMATION

| Device | Package | Shipping† |
|--------------|----------------------|----------------------|
| NTJD4105CT1 | SOT-363 | 3000 / Tape & Reel |
| NTJD4105CT1G | SOT-363 (Pb-Free) | 3000 / Tape & Reel |
| NTJD4105CT2 | SOT-363 | 3000 / Tape & Reel |
| NTJD4105CT2G | SOT-363 (Pb-Free) | 3000 / Tape & Reel |
| NTJD4105CT4 | SOT-363 | 10,000 / Tape & Reel |
| NTJD4105CT4G | SOT-363 (Pb-Free) | 10,000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.



1
SCALE 2:1

SC-88/SC70-6/SOT-363
CASE 419B-02
ISSUE Y

DATE 11 DEC 2012



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
 2. CONTROLLING DIMENSION: MILLIMETERS.
 3. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.20 PER END.
 4. DIMENSIONS D AND E1 AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AND DATUM H.
 5. DATUMS A AND B ARE DETERMINED AT DATUM H.
 6. DIMENSIONS b AND c APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08 AND 0.15 FROM THE TIP.
 7. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 TOTAL IN EXCESS OF DIMENSION b AT MAXIMUM MATERIAL CONDITION. THE DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT.

| DIM | MILLIMETERS | | | INCHES | | |
|-----|-------------|------|------|-----------|-------|-------|
| | MIN | NOM | MAX | MIN | NOM | MAX |
| A | --- | --- | 1.10 | --- | --- | 0.043 |
| A1 | 0.00 | --- | 0.10 | 0.000 | --- | 0.004 |
| A2 | 0.70 | 0.90 | 1.00 | 0.027 | 0.035 | 0.039 |
| b | 0.15 | 0.20 | 0.25 | 0.006 | 0.008 | 0.010 |
| C | 0.08 | 0.15 | 0.22 | 0.003 | 0.006 | 0.009 |
| D | 1.80 | 2.00 | 2.20 | 0.070 | 0.078 | 0.086 |
| E | 2.00 | 2.10 | 2.20 | 0.078 | 0.082 | 0.086 |
| E1 | 1.15 | 1.25 | 1.35 | 0.045 | 0.049 | 0.053 |
| e | 0.65 BSC | | | 0.026 BSC | | |
| L | 0.26 | 0.36 | 0.46 | 0.010 | 0.014 | 0.018 |
| L2 | 0.15 BSC | | | 0.006 BSC | | |
| aaa | 0.15 | | | 0.006 | | |
| bbb | 0.30 | | | 0.012 | | |
| ccc | 0.10 | | | 0.004 | | |
| ddd | 0.10 | | | 0.004 | | |

GENERIC MARKING DIAGRAM*



- XXX = Specific Device Code
- M = Date Code*
- = Pb-Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or position may vary depending upon manufacturing location.

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

RECOMMENDED SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

STYLES ON PAGE 2

| | | |
|------------------|----------------------|--|
| DOCUMENT NUMBER: | 98ASB42985B | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | SC-88/SC70-6/SOT-363 | PAGE 1 OF 2 |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

SC-88/SC70-6/SOT-363
CASE 419B-02
ISSUE Y

DATE 11 DEC 2012

| | | | | | |
|---|---|--|--|--|--|
| STYLE 1: PIN 1. EMITTER 2 2. BASE 2 3. COLLECTOR 1 4. EMITTER 1 5. BASE 1 6. COLLECTOR 2 | STYLE 2: CANCELLED | STYLE 3: CANCELLED | STYLE 4: PIN 1. CATHODE 2. CATHODE 3. COLLECTOR 4. EMITTER 5. BASE 6. ANODE | STYLE 5: PIN 1. ANODE 2. ANODE 3. COLLECTOR 4. EMITTER 5. BASE 6. CATHODE | STYLE 6: PIN 1. ANODE 2 2. N/C 3. CATHODE 1 4. ANODE 1 5. N/C 6. CATHODE 2 |
| STYLE 7: PIN 1. SOURCE 2 2. DRAIN 2 3. GATE 1 4. SOURCE 1 5. DRAIN 1 6. GATE 2 | STYLE 8: CANCELLED | STYLE 9: PIN 1. EMITTER 2 2. EMITTER 1 3. COLLECTOR 1 4. BASE 1 5. BASE 2 6. COLLECTOR 2 | STYLE 10: PIN 1. SOURCE 2 2. SOURCE 1 3. GATE 1 4. DRAIN 1 5. DRAIN 2 6. GATE 2 | STYLE 11: PIN 1. CATHODE 2 2. CATHODE 2 3. ANODE 1 4. CATHODE 1 5. CATHODE 1 6. ANODE 2 | STYLE 12: PIN 1. ANODE 2 2. ANODE 2 3. CATHODE 1 4. ANODE 1 5. ANODE 1 6. CATHODE 2 |
| STYLE 13: PIN 1. ANODE 2. N/C 3. COLLECTOR 4. EMITTER 5. BASE 6. CATHODE | STYLE 14: PIN 1. VREF 2. GND 3. GND 4. IOUT 5. VEN 6. VCC | STYLE 15: PIN 1. ANODE 1 2. ANODE 2 3. ANODE 3 4. CATHODE 3 5. CATHODE 2 6. CATHODE 1 | STYLE 16: PIN 1. BASE 1 2. EMITTER 2 3. COLLECTOR 2 4. BASE 2 5. EMITTER 1 6. COLLECTOR 1 | STYLE 17: PIN 1. BASE 1 2. EMITTER 1 3. COLLECTOR 2 4. BASE 2 5. EMITTER 2 6. COLLECTOR 1 | STYLE 18: PIN 1. VIN1 2. VCC 3. VOUT2 4. VIN2 5. GND 6. VOUT1 |
| STYLE 19: PIN 1. IOUT 2. GND 3. GND 4. V CC 5. V EN 6. V REF | STYLE 20: PIN 1. COLLECTOR 2. COLLECTOR 3. BASE 4. EMITTER 5. COLLECTOR 6. COLLECTOR | STYLE 21: PIN 1. ANODE 1 2. N/C 3. ANODE 2 4. CATHODE 2 5. N/C 6. CATHODE 1 | STYLE 22: PIN 1. D1 (i) 2. GND 3. D2 (i) 4. D2 (c) 5. VBUS 6. D1 (c) | STYLE 23: PIN 1. Vn 2. CH1 3. Vp 4. N/C 5. CH2 6. N/C | STYLE 24: PIN 1. CATHODE 2. ANODE 3. CATHODE 4. CATHODE 5. CATHODE 6. CATHODE |
| STYLE 25: PIN 1. BASE 1 2. CATHODE 3. COLLECTOR 2 4. BASE 2 5. EMITTER 6. COLLECTOR 1 | STYLE 26: PIN 1. SOURCE 1 2. GATE 1 3. DRAIN 2 4. SOURCE 2 5. GATE 2 6. DRAIN 1 | STYLE 27: PIN 1. BASE 2 2. BASE 1 3. COLLECTOR 1 4. EMITTER 1 5. EMITTER 2 6. COLLECTOR 2 | STYLE 28: PIN 1. DRAIN 2. DRAIN 3. GATE 4. SOURCE 5. DRAIN 6. DRAIN | STYLE 29: PIN 1. ANODE 2. ANODE 3. COLLECTOR 4. EMITTER 5. BASE/ANODE 6. CATHODE | STYLE 30: PIN 1. SOURCE 1 2. DRAIN 2 3. DRAIN 2 4. SOURCE 2 5. GATE 1 6. DRAIN 1 |

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

| | | |
|-------------------------|-----------------------------|--|
| DOCUMENT NUMBER: | 98ASB42985B | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | SC-88/SC70-6/SOT-363 | PAGE 2 OF 2 |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [ON Semiconductor](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [JANTX2N5237](#) [FCA20N60_F109](#) [FDZ595PZ](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [TPCC8103,L1Q\(CM](#)
[MIC4420CM-TR](#) [VN1206L](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BUK954R8-60E](#)
[NTE6400](#) [SQJ402EP-T1-GE3](#) [2SK2614\(Te16L1,Q\)](#) [2N7002KW-FAI](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [ECH8691-TL-W](#)
[FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE221](#) [NTE222](#) [NTE2384](#) [NTE2903](#) [NTE2941](#) [NTE2945](#) [NTE2946](#) [NTE2960](#)
[NTE2967](#) [NTE2969](#) [NTE2976](#) [NTE455](#) [NTE6400A](#) [NTE2910](#) [NTE2916](#) [NTE2956](#) [NTE2911](#) [DMN2080UCB4-7](#) [TK10A80W,S4X\(S](#)
[SSM6P69NU,LF](#) [DMP22D4UFO-7B](#)