

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at <u>www.onsemi.com</u>

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or unavteries, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out or i, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor and is officers, employees, weni four in any manner.



MUR840, MUR860, RURP840, RURP860

Data Sheet

November 2013

8 A, 400 V - 600 V, Ultrafast Diodes

Description

The MUR840, MUR860, RURP840, RURP860 is an ultrafast diode with low forward voltage drop. This device is intended for use as freewheeling and clamping diodes in a variety of switching power supplies and other power switching applications. It is specially suited for use in switching power supplies and industrial application.

Ordering Information

| PART NUMBER | PACKAGE | BRAND | | |
|-------------|-------------|---------|--|--|
| MUR840 | TO-220AC-2L | MUR840 | | |
| RURP840 | TO-220AC-2L | RURP840 | | |
| MUR860 | TO-220AC-2L | MUR860 | | |
| RURP860 | TO-220AC-2L | RURP860 | | |

NOTE: When ordering, use the entire part number.

Symbol




Features

- Ultrafast Recovery t_{rr} = 70 ns (@ I_F = 8 A)
- Max Forward Voltage, $V_F = 1.5 V (@ T_C = 25^{\circ}C)$
- 400 V, 600 V Reverse Voltage and High Reliability
- Avalanche Energy Rated
- RoHS Compliant

Applications

- Switching Power Supplies
- Power Switching Circuits
- General Purpose

Packaging



Absolute Maximum Ratings $T_C = 25^{\circ}C$, Unless Otherwise Specified

| | MUR840 RURP840 | MUR860 RURP860 | UNIT |
|---|-------------------|-------------------|------|
| Peak Repetitive Reverse Voltage V _{RRM} | 400 | 600 | V |
| Working Peak Reverse Voltage | 400 | 600 | V |
| DC Blocking VoltageV _R | 400 | 600 | V |
| Average Rectified Forward Current | 8 | 8 | А |
| Repetitive Peak Surge Current I _{FRM} (Square Wave, 20kHz) | 16 | 16 | A |
| Nonrepetitive Peak Surge Current IFSM (Halfwave, 1 Phase, 60Hz) | 100 | 100 | А |
| Maximum Power Dissipation | 75 | 75 | W |
| Avalanche Energy (See Figures 10 and 11) E _{AVL} | 20 | 20 | mJ |
| Operating and Storage Temperature | -65 to 175 | -65 to 175 | °C |
| Maximum Lead Temperature for Soldering | | | |
| Leads at 0.063 in. (1.6mm) from case for 10s | 300 | 300 | °C |
| Package Body for 10s, see Tech Brief 334T _{PKG} | 260 | 260 | Oo |

| | | | MUR840, RURP840 | | MUR860, RURP860 | | | |
|------------------|---|-----|-----------------|-----|-----------------|-----|-----|------|
| SYMBOL | TEST CONDITION | MIN | ТҮР | MAX | MIN | ТҮР | МАХ | UNIT |
| V _F | I _F = 8 A | - | - | 1.3 | - | - | 1.5 | V |
| | I _F = 8 A, T _C = 150 ^o C | - | - | 1.0 | - | - | 1.2 | V |
| I _R | V _R = 400 V | - | - | 100 | - | - | - | μΑ |
| | V _R = 600 V | - | - | - | - | - | 100 | μΑ |
| | $V_{\rm R} = 400 \text{ V}, \text{ T}_{\rm C} = 150^{\rm O} \text{C}$ | - | - | 500 | - | - | - | μΑ |
| | $V_{\rm R} = 600 \text{ V}, \text{ T}_{\rm C} = 150^{\rm O} \text{C}$ | - | - | - | - | - | 500 | μA |
| t _{rr} | $I_F = 1 \text{ A}, dI_F/dt = 200 \text{ A}/\mu\text{s}$ | - | - | 60 | - | - | 60 | ns |
| | $I_{F} = 8 \text{ A}, \ dI_{F}/dt = 200 \text{ A}/\mu \text{s}$ | - | - | 70 | - | - | 70 | ns |
| ta | $I_{F} = 8 \text{ A}, \ dI_{F}/dt = 200 \text{ A}/\mu \text{s}$ | - | 32 | - | - | 32 | - | ns |
| t _b | $I_{F} = 8 \text{ A}, dI_{F}/dt = 200 \text{ A}/\mu \text{s}$ | - | 21 | - | - | 21 | - | ns |
| Q _{rr} | $I_F = 8 \text{ A}, dI_F/dt = 200 \text{ A}/\mu \text{s}$ | - | 195 | - | - | 195 | - | nC |
| CJ | V _R = 10 V, I _F = 0 A | - | 25 | - | - | 25 | - | pF |
| R _{θJC} | | - | - | 2 | - | - | 2 | °C/M |

Electrical Specifications $T_C = 25^{\circ}C$, Unless Otherwise Specified

DEFINITIONS

 V_F = Instantaneous forward voltage (pw = 300 µs, D = 2%).

I_R = Instantaneous reverse current.

 T_{rr} = Reverse recovery time (See Figure 9), summation of $t_a + t_b$.

 t_a = Time to reach peak reverse current (See Figure 9).

 t_b = Time from peak I_{RM} to projected zero crossing of I_{RM} based on a straight line from peak I_{RM} through 25% of I_{RM} (See Figure 9).

Q_{rr} = Reverse recovery charge.


 $C_{J} =$ Junction Capacitance.

 $R_{\theta JC}$ = Thermal resistance junction to case.

pw = pulse width.

D = duty cycle.

Typical Performance Curves








FIGURE 2. REVERSE CURRENT vs REVERSE VOLTAGE

Typical Performance Curves (Continued)






FIGURE 3. trr, ta AND tb CURVES vs FORWARD CURRENT












FIGURE 4. trr, ta AND tb CURVES vs FORWARD CURRENT






FIGURE 6. CURRENT DERATING CURVE

Test Circuits and Waveforms





without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:

http://www.fairchildsemi.com/package/packageDetails.html?id=PN_TT220-002.



SEMICONDUCTOR



TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

| AccuPower™ | F-PFS™ | | Sync-Lock™ |
|--------------------------------------|--|---------------------------------------|------------------------|
| AX-CAP [®] * | FRFET [®] | | SYSTEM ®* |
| BitSiC™ | Global Power Resource SM | PowerTrench [®] | GENERAL |
| Build it Now™ | GreenBridge™ | PowerXS™ | TinyBoost [®] |
| CorePLUS™ | Green FPS™ | Programmable Active Droop™ | TinyBuck [®] |
| CorePOWER™ | Green FPS™ e-Series™ | QFET® | TinyCalc™ |
| CROSSVOLT™ | Gmax™ | QS™ | TinyLogic [®] |
| CTL™ | GTO™ | Quiet Series™ | TINYOPTO™ |
| Current Transfer Logic™ | IntelliMAX™ | RapidConfigure™ | TinyPower™ |
| DEUXPEED [®] Dual Cool™ | ISOPLANAR™ Marking Small Speakers Sound Loude | | TinyPWM™ |
| EcoSPARK® | and Better™ | Saving our world, 1mW/W/kW at a time™ | TinyWire™ |
| EfficentMax™ | MegaBuck™ | SignalWise™ | TranSiC™ |
| ESBC™ | MICROCOUPLER™ | SmartMax™ | TriFault Detect™ |
| | MicroFET™ | SMART START [™] | TRUECURRENT®* |
| | MicroPak™ | Solutions for Your Success™ | µSerDes™ |
| Fairchild® | MicroPak2 [™] | SPM [®] | μ |
| Fairchild Semiconductor [®] | MillerDrive™ | STEALTH™ | / SerDes" |
| FACT Quiet Series™ | MotionMax™ | SuperFET® | UHC® |
| FACT® | mWSaver® | SuperSOT™-3 | Ultra FRFET™ |
| FAST [®] | OptoHiT™ | SuperSOT™-6 | UniFET™ |
| FastvCore™ | OPTOLOGIC® | SuperSOT [™] -8 | VCXTM |
| FETBench™ | OPTOPLANAR® | SupreMOS® | VisualMax [™] |
| FPS™ | | SyncFET™ | VoltagePlus™ XS™ |
| | | | ×0 |
| | | | |
| | | | |

*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS. SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used here in:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.Fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handing and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS **Definition of Terms**

| Datasheet Identification | Product Status | Definition |
|--------------------------|-----------------------|---|
| Advance Information | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design. |
| Obsolete | Not In Production | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only. |
| | | Rev |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <u>www.onsemi.com/site/pdf/Patent-Marking.pdf</u>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor has against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death ass

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910

Japan Customer Focus Center Phone: 81-3-5817-1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

© Semiconductor Components Industries, LLC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by ON Semiconductor manufacturer:

Other Similar products are found below :

RD0306T-H BAQ33-GS18 BAV17-TR BAV19-TR 1N3611 NTE156A NTE525 NTE571 NTE574 NTE5804 NTE5806 NTE6244 1SS181-TP 1SS193,LF 1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR RFUH20TB3S BAS 28 E6327 BAV199-TP BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G SP000010217 ACDSW4448-HF CDSZC01100-HF BAV199E6433HTMA1 BAV70M3T5G SMBT2001T1G NTE5801 NTE5800 NTE5808 NTE6240 NTE6248 DLM10C-AT1 BAS28-7 BAW56HDW-13