

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild <a href="general-regarding-numbers-n

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



November 2013

SGP23N60UF 600V PT IGBT

General Description

Fairchild's UF series IGBTs provide low conduction and switching losses. UF series is designed for the applications such as general inverters and PFC where High Speed Switching is required feature.

Features

- High Input Impedance





Applications

General Inverter, PFC

Absolute Maximum Ratings $T_C = 25^{\circ}C$ unless otherwise noted

| Symbol | Description | | Ratings | Unit | |
|---------------------|---|--------------------------|-------------|------|--|
| V _{CES} | Collector-Emitter Voltage | | 600 | V | |
| V _{GES} | Gate-Emitter Voltage | | ± 20 | V | |
| | Collector Current | @ $T_C = 25^{\circ}C$ | 23 | А | |
| IC | Collector Current | @ T _C = 100°C | 12 | А | |
| I _{CM (1)} | Pulsed Collector Current | | 92 | А | |
| P _D | Maximum Power Dissipation | @ $T_C = 25^{\circ}C$ | 100 | W | |
| | Maximum Power Dissipation | @ T _C = 100°C | 40 | W | |
| TJ | Operating Junction Temperature | | -55 to +150 | °C | |
| T _{stg} | Storage Temperature Range | | -55 to +150 | °C | |
| TL | Maximum Lead Temp. for Soldering Purposes, 1/8" from Case for 5 Seconds | | 300 | °C | |

Notes:(1) Repetitive rating: Pulse width limited by max. junction temperature

Thermal Characteristics

| Symbol | Parameter | Тур. | Max. | Unit |
|-----------------|---|------|------|------|
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case | | 1.2 | °C/W |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | | 62.5 | °C/W |

Electrical Characteristics of the IGBT T_C = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Тур. | Max. | Unit |
|-----------------------------------|--|---|------|------|-------|------|
| Off Chai | racteristics | | | | | |
| BV _{CES} | Collector-Emitter Breakdown Voltage | $V_{GE} = 0 \text{ V}, I_{C} = 250 \text{ uA}$ | 600 | | | V |
| $\Delta B_{VCES}/$ ΔT_{J} | Temperature Coefficient of Breakdown Voltage | V _{GE} = 0 V, I _C = 1 mA | | 0.6 | | V/°C |
| I _{CES} | Collector Cut-Off Current | V _{CE} = V _{CES} , V _{GE} = 0 V | | / | 250 | uA |
| I _{GES} | G-E Leakage Current | $V_{GE} = V_{GES}, V_{CE} = 0 V$ | | | ± 100 | nA |
| On Char | racteristics | | | | | |
| V _{GE(th)} | G-E Threshold Voltage | $I_C = 12 \text{ mA}, V_{CE} = V_{GE}$ | 3.5 | 4.5 | 6.5 | V |
| | Collector to Emitter | $I_C = 12 \text{ A}, V_{GE} = 15 \text{ V}$ | | 2.1 | 2.6 | V |
| V _{CE(sat)} | Saturation Voltage | I _C = 23 A, V _{GE} = 15 V | | 2.6 | | V |
| C _{ies} | C Characteristics Input Capacitance | V _{CF} = 30 V V _{GF} = 0 V, | | 720 | | pF |
| C _{ies} | Input Capacitance | ., | | 720 | | pF |
| C _{oes} | Output Capacitance | f = 1 MHz | | 100 | | pF |
| C _{res} | Reverse Transfer Capacitance | 1 111112 | | 25 | | pF |
| Switchir | ng Characteristics | | | | | |
| t _{d(on)} | Turn-On Delay Time | | | 17 | | ns |
| t _r | Rise Time | | | 27 | | ns |
| t _{d(off)} | Turn-Off Delay Time | $V_{CC} = 300 \text{ V}, I_{C} = 12 \text{ A},$ | | 60 | 130 | ns |
| t _f | Fall Time | $R_G = 23 \Omega, V_{GE} = 15 V,$ | | 70 | 150 | ns |
| E _{on} | Turn-On Switching Loss | Inductive Load, T _C = 25°C | | 115 | | uJ |
| E _{off} | Turn-Off Switching Loss | | | 135 | | uJ |
| E _{ts} | Total Switching Loss | | | 250 | 400 | uJ |
| t _{d(on)} | Turn-On Delay Time | | | 23 | | ns |
| t _r | Rise Time | $V_{CC} = 300 \text{ V}, I_{C} = 12 \text{ A},$ $R_{G} = 23 \Omega, V_{GE} = 15 \text{ V},$ | | 32 | | ns |
| t _{d(off)} | Turn-Off Delay Time | | | 100 | 200 | ns |
| t _f | Fall Time | | | 220 | 250 | ns |
| E _{on} | Turn-On Switching Loss | Inductive Load, T _C = 125°C | | 205 | | uJ |
| | | | | | | |

 $\mathsf{E}_{\mathsf{off}}$

 E_{ts}

Turn-Off Switching Loss

Total Switching Loss

uJ

uJ

320

525

800




Fig 1. Typical Output Characteristics




Fig 2. Typical Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case
Temperature at Variant Current Level




Fig 4. Load Current vs. Frequency




Fig 5. Saturation Voltage vs. V_{GE}






Fig 6. Saturation Voltage vs. V_{GE}



Common Emitter $V_{CC} = 300V, V_{GE} = \pm 15V$ $I_{C} = 12A$ $T_{C} = 25C$ $T_{C} = 125C$ $T_{C} = 100$ $T_{C} = 100$

Fig 7. Capacitance Characteristics

Fig 8. Turn-On Characteristics vs.
Gate Resistance







Fig 9. Turn-Off Characteristics vs.

Gate Resistance

Fig 10. Switching Loss vs. Gate Resistance







Fig 11. Turn-On Characteristics vs. Collector Current

Fig 12. Turn-Off Characteristics vs. Collector Current







Fig 13. Switching Loss vs. Collector Current

Fig 14. Gate Charge Characteristics






Fig 15. SOA Characteristics

Fig 16. Turn-Off SOA Characteristics




Fig 17. Transient Thermal Impedance of IGBT

Mechanical Dimensions




Figure 18. TO-220 3L - TO-220, MOLDED, 3LEAD, JEDEC VARIATION AB

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:

http://www.fairchildsemi.com/package/packageDetails.html?id=PN TT220-003





TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

F-PFS™ AccuPower™ AX-CAP® FRFET® BitSiC™ Global Power ResourceSM

Build it Now™ GreenBridge™ Green FPS™ CorePLUS™

CorePOWER™ Green FPS™ e-Series™ CROSSVOLT™ Gmax™

CTL[™] Current Transfer Logic™ DEUXPEED®

Dual Cool™ Marking Small Speakers Sound Louder EcoSPARK[®] and Better™ MegaBuck™

GTO™

IntelliMAX™

MicroFET™

MicroPak™

MicroPak2™

MillerDrive™

MotionMax™ mWSaver®

OPTOLOGIC®

OPTOPLANAR®

OptoHiT™

ISOPLANAR™

MICROCOUPLER™

EfficentMax™ ESBC™

Fairchild[®] Fairchild Semiconductor® FACT Quiet Series™ FACT

 $\mathsf{FAST}^{\mathbb{R}}$ FastvCore™ FETBench™ FPS™

® PowerTrench® PowerXS™

Programmable Active Droop™

QFET® QSTM Quiet Series™ RapidConfigure™

Saving our world, 1mW/W/kW at a time™

SignalWise™ SmartMax™ SMART START™

Solutions for Your Success™

SPM® STEALTH™ SuperFET® SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS® . SyncFET™

Sync-Lock™ SYSTEM®*
GENERAL TinyBoost[®] TinyBuck[®] TinyCalc™ TinyLogic[®] TIŃYOPTO™ TinyPower™ TinyPWM™ TinyWire™ TranSiC™ TriFault Detect™ TRUECURRENT®* μSerDes™

UHC® Ultra FRFET™ UniFET™ VCX™ VisualMax™ VoltagePlus™ XSTN

*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY
FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE
EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.Fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handing and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS **Definition of Terms**

| Datasheet Identification | Product Status | Definition |
|--------------------------|-----------------------|---|
| Advance Information | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design. |
| Obsolete | Not In Production | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only. |

Rev. 166

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdt/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and exp

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800-282-9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for IGBT Transistors category:

Click to view products by ON Semiconductor manufacturer:

Other Similar products are found below:

 748152A
 APT20GT60BRDQ1G
 APT50GT60BRG
 NGTB10N60FG
 STGFW20V60DF
 APT30GP60BG
 APT45GR65B2DU30

 GT50JR22(STA1ES)
 TIG058E8-TL-H
 VS-CPV364M4KPBF
 NGTB25N120FL2WAG
 NGTG40N120FL2WG
 RJH60F3DPQ-A0#T0

 APT40GR120B2SCD10
 APT15GT120BRG
 APT20GT60BRG
 NGTB75N65FL2WAG
 NGTG15N120FL2WG
 IXA30RG1200DHGLB

 IXA40RG1200DHGLB
 APT70GR65B2DU40
 NTE3320
 IHFW40N65R5SXKSA1
 APT70GR120J
 APT35GP120JDQ2

 IKZA40N65RH5XKSA1
 IKFW75N65ES5XKSA1
 IKFW50N65ES5XKSA1
 IKFW50N65EH5XKSA1
 IKFW40N65ES5XKSA1

 IKFW60N65ES5XKSA1
 IMBG120R090M1HXTMA1
 IMBG120R220M1HXTMA1
 XD15H120CX1
 XD25H120CX0
 XP15PJS120CL1B1

 IGW30N60H3FKSA1
 STGWA8M120DF3
 IGW08T120FKSA1
 IGW75N60H3FKSA1
 HGTG40N60B3
 FGH60N60SMD_F085

 FGH75T65UPD
 STGWA15H120F2
 IKA10N60TXKSA1
 IHW20N120R5XKSA1
 RJH60D2DPP-M0#T2
 IKP20N60TXKSA1

 IHW20N65R5XKSA1
 IDW40E65D2FKSA1