

Type ANR58-UL Automotive Blade Fuse Standard - Voltage 58V w/ UR Approval



www.optifuse.com (619) 593-5050

Specifications:

- Voltage: 58VDC 250VAC
- Amperage: 500mA, 1A, 2A, 3A, 4A, 5A, 6A, 7A, 7.5A, 8A, 10A, 12A, 15A, 16A, 20A, 25A, 30A, 35A, 40A
- Material:
 - Body – Nylon 66 with 30% Fiber Glass UL94V-0
 - Terminals – Copper Alloy, Tin plated
- Interrupt Rating: 1000A @ 58 VDC
400A @ 250 VAC

Standards: UL248-1 Special Purpose Fuse

Time Characteristics:


| % of Rated Current | Min Hold Time | Max Hold Time |
|--------------------|-------------------|---------------|
| 100% | Carry (35A~40A) | --- |
| 110% | Carry (500mA~30A) | --- |
| 135% | 750ms | 3600s |
| 200% | 150ms | 60s |
| 350% | 40ms | 1s |
| 600% | 10ms | 100ms |

Working Temperature: -40°C~125°C

Agency Standards and Listings:



Mechanical Dimensions: Inches [mm]



| Part Number | Amperage | Body Color | Voltage Drop (mV) | Cold Resistance | I ² T |
|----------------|----------|--------------|-------------------|-----------------|------------------|
| ANR58-UL-500MA | 500mA | Dark Blue | 150 | 290 mΩ | 0.3 |
| ANR58-UL-1A | 1A | Black | 125 | 100 mΩ | 2.3 |
| ANR58-UL-2A | 2A | Gray | 120 | 43.0 mΩ | 9.6 |
| ANR58-UL-3A | 3A | Violet | 110 | 30.0 mΩ | 16.2 |
| ANR58-UL-4A | 4A | Pink | 110 | 22.0 mΩ | 36.8 |
| ANR58-UL-5A | 5A | Tan | 110 | 16.0 mΩ | 62.5 |
| ANR58-UL-6A | 6A | Light Red | --- | --- | --- |
| ANR58-UL-7A | 7A | Light Orange | --- | --- | --- |
| ANR58-UL-7.5A | 7.5A | Brown | 90 | 9.00 mΩ | 73.1 |
| ANR58-UL-8A | 8A | Light Yellow | --- | --- | --- |
| ANR58-UL-10A | 10A | Red | 90 | 6.50 mΩ | 210 |
| ANR58-UL-12A | 12A | Light Pink | --- | --- | --- |
| ANR58-UL-15A | 15A | Blue | 90 | 4.00 mΩ | 270 |
| ANR58-UL-16A | 16A | Light Green | --- | --- | --- |
| ANR58-UL-20A | 20A | Yellow | 90 | 3.00 mΩ | 360 |
| ANR58-UL-25A | 25A | Clear | 80 | 1.90 mΩ | 813 |
| ANR58-UL-30A | 30A | Green | 80 | 1.65 mΩ | 1530 |
| ANR58-UL-35A | 35A | Blue Green | 70 | 1.45 mΩ | 1960 |
| ANR58-UL-40A | 40A | Orange | 70 | 1.25 mΩ | 3200 |

Warning:



-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.

-Avoid contact of device with chemical solvent. Prolonged contact will damage the device performance.

Note: All specifications subject to change without notice.


Rev D 11/2019-page 1/2
Code G02-01H

Type ANR58-UL
Automotive Blade Fuse
Standard - Voltage 58V
w/ UL Approval



www.optifuse.com (619) 593-5050

Time Current Curve Graph



Note: All specifications subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Optifuse manufacturer](#):

Other Similar products are found below :

[FSC-3.5A](#) [TSA-250MA](#) [BLR-304](#) [BLR-504](#) [BLC-05-GTA](#) [BLR-I-504](#) [BLM-304](#) [CBW57-EL4-10A](#) [FPK-10A](#) [FPK-1A](#) [FPK-30A](#) [LPM-08](#)
[LPX-23B-08R-LOOP](#) [FPK-12A](#) [FPK-15A](#) [FPK-20A](#) [FPK-25A](#) [FPK-2A](#) [FPK-3A](#) [FPK-4A](#) [FPK-5A](#) [FPK-6A](#) [FPK-7A](#) [FPK-8A](#) [FPK-R-](#)
[1.5A](#) [FPK-R-10A](#) [FPK-R-15A](#) [FPK-R-1A](#) [FPK-R-20A](#) [FPK-R-25A](#) [FPK-R-2A](#) [FPK-R-30A](#) [FPK-R-3A](#) [FPK-R-4A](#) [FPK-R-5A](#) [FPK-R-6A](#)
[FPK-R-8A](#) [PMG-KB-01-Q2S](#) [LPM-01B-12R](#) [ACB-12-V-50A](#) [LPR-13C-10R](#) [ACBP4-PM-5A](#) [BLR-306](#) [ACB-12-V-30A](#) [CBW57-EL4-5A](#)
[CBW57-ES-5A](#) [CBW57-PB-10A-5X](#) [CBW57-PS-10A-5X](#) [CBW57-PS-3A-1X](#) [CBW28-1A](#)