Type LPR-05 Water-Proof In-Line Fuse Holder **Automotive Blade Type**

Mechanical Dimensions: Inches [mm]



www.optifuse.com

(619) 593-5050

Specifications:		1	7
Rating: 32VDC	Wire	Max.	
IP Rating: IP67	Gauge	Amperage	
Body Material: PVC	#12	30A	
For use w/ Type APR, ANR Fuse (Regular-Automotive Blade)	#16	15A	
Water-proof with Inter-Locking Cap Attached Mounting Bracket Standard Wire: #12AWG – 5" - Orange Color (Other wire sizes and colors available as special order)	Part number format LPR-05B-##Z Where ## = Wire Gauge (12,16 AWG) Z = Wire Color		

Orange or Red

CAP 0.68 ± 0.01 +1.74 ± 0.01→ [44.20 ± 0.25] 1.08 ± 0.01 [27.43 ± 0.25] 0.46 ± 0.01 [11.68 ± 0.25] 0.78 ± 0.01 -[19.81 ± 0.25] -0.33 ± 0.01 [8,38 ± 0,25] Ø 0.24 ± 0.01 [5.97 ± 0.25] 1.17 ± 0.01 [29.72 ± 0.25] 1.06 ± 0.01 [26.92 ± 0.25] Н 5.27 ± 0.01 [133,86 ± 0,25] - 0,68 ± 0,01 [17,27 ± 0,25] ΝM

-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical Warning: arcing and/or flame. -Device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated. -Avoid contact of device with chemical solvent. Prolonged contact will damage the device performance. - Not intended for submersible water applications.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Optifuse manufacturer:

Other Similar products are found below :

570-290-741P40 570-290-751P40 020417G 020418E 6R30A1B F600A3B 80910030 8601.2020 G15A2SPQ 9-3557-GP REV A HDJ-B R6J30A3S HFH-1 RF30A1S RF30A2B RF30A3SP 15600-08-10 BK/FHN19G BK/HHM BK/HKP-CCHH BK/HKP-JJ BK/HTJ-LES-FUSE HMG-241 HTJ-LES-FUSE C4044-1 2086-1 2193 2602 2650 178.000100 FHN31G1 T30A2B G4PB8 2660 2799 CQ-209V HKP-CCHH R6F30A2S 341001A 345621A CVRMCC 4202 4407 4408 4413 4423 4532 4537 TSD1404-12 BK/FHN31G1