Type MID Fast Acting Automotive (MIDI®)¹ **Limiter Fuse** 30mm Center to Center Bolt-On



www.optifuse.com

(619) 593-5050

Interrupting Rating (IR): 1000A @ 32VDC Operating Temperature: -40°C ~ 125°C


Electrical Characteristics:

Rating A (In)	100% In	110% In	150% In	200% In	300% In
Time	Min 100 hr.	Min 4 hr.	60 sec ~ 3600 sec	1 sec ~ 100 sec	.03 ~ 15sec

Product Information

Part Number	Ampere Rating	Voltage Rating (VDC)	Stamp Color Code	Nominal Cold Resistance (mΩ)
MID-030	30	32	Orange	N/A
MID-040	40	32	Green	1.3
MID-050	50	32	Red	1.04
MID-060	60	32	Yellow	0.87
MID-070	70	32	Brown	0.72
MID-080	80	32	Clear	0.56
MID-100	100	32	Blue	0.45
MID-125	125	32	Pink	0.40
MID-150	150	32	Gray	0.33
MID-200	200	32	Violet	N/A

MID Product Dimensions: Inches[mm]



Note: All specifications subject to change without notice.

Rev B 04/2011 - Page: 1/2

Code: J01-01W


Type MID Fast Acting Automotive (MIDI®) Limiter Fuse 30mm Center to Center Bolt-On



www.optifuse.com

(619) 593-5050

Average Time Current Curves:



Warning:

-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.



- -Limiter Fuses are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
- -Avoid contact of Limiter Fuses with chemical solvent. Prolonged contact will damage the device performance.

Note: All specifications subject to change without notice.

Rev B 04/2011 - Page: 2/2 Code: J01-01W

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Fuses category:

Click to view products by Optifuse manufacturer:

Other Similar products are found below:

HBO-10 HBO-100 HBO-150 HBO-40 HBO-50 AFX-150 AT-10 AT-30 AT-5 ATM-10ID ATM-4LP ACL-50 AFX-50 299080 HBO-15 AT-20 AT-3 0287015 142.7010.5502 FMM-15 0MIN015.HXGLO A70QS350-4 0695030.PXPS 0695040.PXPS 0297003.WXT 0297002.WXT 0297004.WXT 0297010.WXT 0297015.WXT 0297020.WXT 0297025.WXT 0297030.WXT 0297030.WXT 029707.5WXT 0602925 0602930 0602935 0602940 0602950 0602960 0611100 0611125