Type MRCBP-24-N Manual Reset Circuit Breaker Automotive Type III Plastic Without Bracket



www.optifuse.com

(619) 593-5050

Specifications:

Manual Reset Type Circuit Breaker

Voltage: 24VDC

Amperage: 10A, 15A, 20A, 25A, 30A, 35A, 40A, 50A

Terminals: Battery – Copper Plate (0.58"), Auxiliary – Zinc Plate (0.66")

Conforms to American National Standard SAE J553


Body: PBT


Operating Temperature: $-10^{\circ} \text{ F} \sim 150^{\circ} \text{ F}$ Storage Temperature: $-20^{\circ} \text{ F} \sim 200^{\circ} \text{ F}$


Current Rating:

Rating	Open Time
$100\% \pm 1.5\%$	> 30 Min
$135\% \pm 1.5\%$	< 30 Min
200% ± 1.5%	< 1 Min

Mechanical Dimensions: Inches [mm]







Warning:

-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.



- -Device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
- -Avoid contact of device with chemical solvent. Prolonged contact will damage the device performance.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Fuses category:

Click to view products by Optifuse manufacturer:

Other Similar products are found below:

HBO-10 HBO-100 HBO-150 HBO-40 HBO-50 AFX-150 AT-10 AT-30 AT-5 ATM-10ID ATM-4LP ACL-50 AFX-50 299080 HBO-15
AT-20 AT-3 0287015 142.7010.5502 FMM-15 0MIN015.HXGLO 2010T1.25A250V 0695030.PXPS 0695040.PXPS 0297003.WXT

0MIN025.HXGLO 0MIN030.HXGLO 0695025.PXPS 0695015.PXPS 0695050.PXPS 0695060.PXPS MRBF-075 02400106P

0297002.WXT 0297004.WXT 0297010.WXT 0297015.WXT 0297020.WXT 0297025.WXT 0297030.WXT 029707.5WXT 0602925

0602930 0602935 0602940 0602950 0602960 0611100 0611125 0611150