Type PMA-DB-04-Q1S Panel Mount Fuse Holder 1/4" x 11/4" (6.3 x 32mm) Fuses Driver / Bayonet



www.optifuse.com

(619) 593-5050

Electrical Rating: 10A, 250V AC **Fuse Style:** 1/4" x 11/4" (6.3 x 32mm)

Material:

Frame: Nylon (UL flame: 94V-2) Cap: PBT (UL flame: 94V-0) Terminals: Tin-plated brass

Cap: Slotted Driver type, Bayonet type


Mounting: Snap-in mounting


Terminal: Solder/Quick-Connect – 4.8mm/0.187"


Panel Thickness: 0.7 ~ 2.5mm **Agency Standards and Listings:**


B

Product Dimensions: Inches [mm]









Warning:

-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.



- -Fuse Holders are not intended for circuit disconnect. All power should be disconnected before removing fuse.
- -Avoid contact of Fuse Holder with chemical solvent. Prolonged contact may damage the device performance.

Note: All specifications subject to change without notice.

Rev A 12/2007 - Page: 1/1 Code S02-02D

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Optifuse manufacturer:

Other Similar products are found below:

570-290-741P40 570-290-751P40 020417G 020418E 6R30A1B F600A3B 80910030 8601.2020 G15A2SPQ 9-3557-GP REV A HDJ-B R6J30A3S HFH-1 RF30A1S RF30A2B RF30A3SP 15600-08-10 BK/FHN19G BK/HHM BK/HKP-CCHH BK/HKP-JJ BK/HTJ-LES-FUSE HMG-241 HTJ-LES-FUSE C4044-1 2086-1 2193 2602 2650 178.000100 FHN31G1 T30A2B G4PB8 2660 2799 CQ-209V HKP-CCHH R6F30A2S 341001A 345621A CVRMCC 4202 4407 4408 4413 4423 4532 4537 TSD1404-12 BK/FHN31G1