Type PMA-DS-05-Q1R Panel Mount Fuse Holder ¼" x 1¼" (6.3 x 32mm) Fuses Driver / Screw



www.optifuse.com (619

(619) 593-5050


Electrical Rating: 15A, 250V AC Fuse Style: ¹/₄" x 1¹/₄" (6.3 x 32mm) Material: Frame and Cap: PBT (UL flame: 94V-0) Terminals: Tin-plated brass Cap: Slotted Driver type, Screw type Mounting: by nut Terminal: Solder/Quick-Connect 4.8mm / 0.187" Panel Thickness: 0.5 ~ 4.5mm Agency Standards and Listings:


97


Product Dimensions: Inches [mm]

 0.19 ± 0.002

[4.8 ± 0.05]







Mounting Hole



-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.

-Fuse Holders are not intended for circuit disconnect. All power should be disconnected before removing fuse. -Avoid contact of Fuse Holder with chemical solvent. Prolonged contact may damage the device performance.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Optifuse manufacturer:

Other Similar products are found below :

570-290-741P40 570-290-751P40 020417G 020418E 6R30A1B F600A3B 80910030 8601.2020 G15A2SPQ 9-3557-GP REV A HDJ-B R6J30A3S HFH-1 RF30A1S RF30A2B RF30A3SP 15600-08-10 BK/FHN19G BK/HHM BK/HKP-CCHH BK/HKP-JJ BK/HTJ-LES-FUSE HMG-241 HTJ-LES-FUSE C4044-1 2086-1 2193 2602 2650 178.000100 FHN31G1 T30A2B G4PB8 2660 2799 CQ-209V HKP-CCHH R6F30A2S 341001A 345621A CVRMCC 4202 4407 4408 4413 4423 4532 4537 TSD1404-12 BK/FHN31G1