Type TFLF Automotive Fuse Link Female Terminals



www.optifuse.com

(800) 621-0326

Specifications:

Voltage: Up to 32VDC

Amperage: 20A, 30A, 40A, 50A, 60A, 70A, 80A Current Cycling (Ambient temperature: 24°C):

The fuses satisfy the performance requirements after 50% of the rated current is applied for 10,000 Cycles.

Each cycle consists of an interrupted current with the pattern of 5 min. On and 10 min. Off.

% Change in Fuse Current Carrying Capacity:

With change in ambient temperature: -0.075%/°C.

Slow Blow Fuse Table:


Part	Ampere	Housing
Number	Rating	Color
TFLF-20A	20A	Light Blue
TFLF-30A	30A	Pink
TFLF-40A	40A	Green
TFLF-50A	50A	Red
TFLF-60A	60A	Yellow
TFLF-70A	70A	Brown
TFLF-80A	80A	Black


Time-Current Characteristics:

(Ambient temperature: 24°C)

% of Ampere	Operating Time	
Rating	Minimum	Maximum
110%	10 Hours	
200%	5 Sec.	100 Sec.
350%	0.2 Sec.	7 Sec.
600%	0.04 Sec.	1 Sec.

Mechanical Dimensions: Inches[mm]





Warning:

-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.



- -Device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
- -Avoid contact of device with chemical solvent. Prolonged contact will damage the device performance.

Note: All specifications subject to change without notice. Rev C 07/2021 - Page: 1/1

Code: J01-01H

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Fuses category:

Click to view products by Optifuse manufacturer:

Other Similar products are found below:

HBO-10 HBO-100 HBO-150 HBO-40 HBO-50 AFX-150 AT-10 AT-30 AT-5 ATM-10ID ATM-4LP ACL-50 AFX-50 299080 HBO-15 AT-20 AT-3 0287015 142.7010.5502 FMM-15 0MIN015.HXGLO 2010T1.25A250V 0695030.PXPS 0695040.PXPS 0297003.WXT 0297002.WXT 0297004.WXT 0297010.WXT 0297015.WXT 0297020.WXT 0297025.WXT 0297030.WXT 0297030.WXT 029707.5WXT 0602925 0602930 0602935 0602940 0602950 0602960 0611100 0611125