

MULTI-POSITION TOGGLE PLUS PUSHBUTTON, COMMERCIAL & MILITARY GRADES

The T2 series provides two functions in one compact switch: toggle and pushbutton action. Features toggle lockout when pushbutton mode is actuated and pushbutton lockout when in toggle mode. A resilient seal in the plunger provides splashproof and dusttight seal.

**T2-0004**

**Operating Force:** 24 +/- 10 oz  
**Circuit:** DPDT-NO, ON-OFF-ON  
 No pushbutton function  
**Rating:** 5 amps Resistive  
 3 amps Inductive  
 1 amp Lamp  
 Low Level: 2mA @ 15VDC  
**Mechanical Life:** 100,000 cycles  
**Electrical Life:** 100,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Gray thermoplastic  
**Case:** Black anodized aluminum



**T2-0034**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: SPNO double break  
**Rating:** 1A to 50mA Resistive @ 4-28VDC  
**Electrical Life:** 100,000 cycles  
**Seal:** Enclosure Design 2, dusttight per MIL-PRF-8805  
**Button:** Gray nylon  
**Case:** Black anodized aluminum alloy



**T2-0008**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** Toggle: 10 amps Resistive / 5 amps Inductive  
 Pushbutton: 10 amps Resistive / 3 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Button:** Black nylon  
**Case:** Black anodized aluminum



**T2-0018**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 1 amp Resistive  
 0.5 amp Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0009**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** Toggle: 10 amps Resistive / 5 amps Inductive  
 Pushbutton: 10 amps Resistive / 3 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0047**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 0.1mA to 500mA Resistive @ 5-32VDC  
 0.1mA to 500mA Inductive @ 5-32VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Dry black chrome plated aluminum alloy



**T2-0015**

**Operating Force:** Toggle: 5.0 lbs.  
 Pushbutton: 4.0 lbs.  
**Circuit:** Toggle: SPST-NO, 4-position, center OFF, momentary  
 Pushbutton: DPST-NO  
**Rating:** 2 amps Resistive  
 2 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0044**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 3.75 lbs.  
**Circuit:** Toggle: DPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 0.1mA to 500mA Resistive @ 5-32VDC  
 0.1mA to 500mA Inductive @ 5-32VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 2, dusttight per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Dry black chrome plated aluminum alloy



**T2-0016**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO  
**Rating:** 1mA to 250mA Resistive @ 12-28VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0045**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 1mA to 250mA Resistive @ 12-28VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-S-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Basic / Snap Action Switches](#) category:*

*Click to view products by [OTTO](#) manufacturer:*

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#) [6HM89](#) [6SE1](#)  
[6SX1-H58](#) [70500216](#) [70599106](#) [MBD5B1](#) [MBH2731](#) [73-316-0012](#) [EXD-AR20](#) [79211923](#) [79218589](#) [7AS12](#)  
[MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#) [831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#)  
[914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#) [11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#)  
[11SM76-T](#) [11SM77-H58](#) [11SM77-T](#) [11SM863-T](#) [11SM866](#) [A7CN-1M-1-LEFT](#) [A831700C7.0](#) [121EN188-R](#) [1245.0120](#)