

MULTI-POSITION TOGGLE PLUS PUSHBUTTON, COMMERCIAL & MILITARY GRADES

The T2 series provides two functions in one compact switch: toggle and pushbutton action. Features toggle lockout when pushbutton mode is actuated and pushbutton lockout when in toggle mode. A resilient seal in the plunger provides splashproof and dusttight seal.

**T2-0004**

**Operating Force:** 24 +/- 10 oz  
**Circuit:** DPDT-NO, ON-OFF-ON  
 No pushbutton function  
**Rating:** 5 amps Resistive  
 3 amps Inductive  
 1 amp Lamp  
 Low Level: 2mA @ 15VDC  
**Mechanical Life:** 100,000 cycles  
**Electrical Life:** 100,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Gray thermoplastic  
**Case:** Black anodized aluminum



**T2-0034**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: SPNO double break  
**Rating:** 1A to 50mA Resistive @ 4-28VDC  
**Electrical Life:** 100,000 cycles  
**Seal:** Enclosure Design 2, dusttight per MIL-PRF-8805  
**Button:** Gray nylon  
**Case:** Black anodized aluminum alloy



**T2-0008**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** Toggle: 10 amps Resistive / 5 amps Inductive  
 Pushbutton: 10 amps Resistive / 3 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Button:** Black nylon  
**Case:** Black anodized aluminum



**T2-0018**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 1 amp Resistive  
 0.5 amp Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0009**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** Toggle: 10 amps Resistive / 5 amps Inductive  
 Pushbutton: 10 amps Resistive / 3 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0047**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 0.1mA to 500mA Resistive @ 5-32VDC  
 0.1mA to 500mA Inductive @ 5-32VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Dry black chrome plated aluminum alloy



**T2-0015**

**Operating Force:** Toggle: 5.0 lbs.  
 Pushbutton: 4.0 lbs.  
**Circuit:** Toggle: SPST-NO, 4-position, center OFF, momentary  
 Pushbutton: DPST-NO  
**Rating:** 2 amps Resistive  
 2 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0044**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 3.75 lbs.  
**Circuit:** Toggle: DPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 0.1mA to 500mA Resistive @ 5-32VDC  
 0.1mA to 500mA Inductive @ 5-32VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 2, dusttight per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Dry black chrome plated aluminum alloy



**T2-0016**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO  
**Rating:** 1mA to 250mA Resistive @ 12-28VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



**T2-0045**

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 1mA to 250mA Resistive @ 12-28VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-S-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [OTTO](#) manufacturer:*

Other Similar products are found below :

[8940K2012](#) [LW1L-M1C10V-A](#) [LW1L-M1C70-A](#) [LW2L-A1C20M-GD](#) [LW2L-M1C20M-A](#) [60324L](#) [M22-D-R-GB0/K11](#) [M7E-HRN2](#)  
[67021K512](#) [67081K512X](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#)  
[MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#) [861K13810T00A14](#) [861K13911](#)  
[8646AB6X718UL](#) [8646ABUL](#) [9001KXRK](#) [907AYY100](#) [PMHD155A1](#) [9533CD4+U574+U4922](#) [95-414.000](#) [99-450.837](#) [99-453.837](#)  
[PV3H2B0NN-341](#) [1203MRA](#) [A22NZBGANGA](#) [A22NZBNANGA](#) [A22NZMPATRA](#) [A2PMA1X03EC56](#) [A3A-5123-02](#) [A3A-7140](#) [A3A-7310](#) [A3A-7340](#) [A3U-TMW-A2C-5M](#) [A595](#) [12037A2ULCSA](#) [ABD122N-B](#) [1211390004](#)