

Tuotetiedot


Tuotekoodi	VG03-0009	Sähkönumero	1912095	EAN-koodi	6410019120950
Tuotenimi	OJL-liitin 400 FBB	ETIM-luokka	EC000276		
Johtimet	IN: Busbar Cu 10x(1x24) OUT: 3xCu(6-50 mm ²) / 4xCu (2,5-35mm ²)				

Tekniset tiedot

Nimellisvirta (IEC)	Cu	425	A
	Al	380	A
Nimellisjännite (IEC)		1000	V
		-	
		-	
Napaluku		1	kpl
Max. Johdinkoko		10x(1x24)	mm ²
Kiristysmomentti			
	2,5-35 mm ²	6	Nm
	6-50 mm ²	10	Nm
	10xCu(1x24)	10	Nm
		-	
Input	Virtakisko Cu 10x(1x24)		
Output	3xCu(6-50 mm²) / 4xCu (2,5-35mm²)		
		-	
Käyttölämpötila		80	°C
Paino		247	g
IP-suojaus		IP20	
Standardit	EN 61238-1:2003; EN 60947-7-1:2009		
Väri / Materiaali	Harmaa kansi, Harmaa kotelo RAL 7035 PA66/V0, Runko tinapinnoitettua alumiinia		
Kiinnitys / KytKentä	DIN-kiskokiinnitys ja 4x ruuviKiinnitys (M5)		


Kuvaus

1-napainen OJL-liitin on tarkoitettu sähkölaitteiden haaroituskytkentöihin. Liittimessä 1 kytKentäaukko joustavalle virtakiskolle (max. 10x Cu(1x24)/kytkentätila) ja 7 haaroitusjohdinaukkoa. Liitinrunko on tinapinnoitettua alumiinia.

Mittakuva

Pakkaus

Pakkausmuoto	Laatikko	Kpl / Pakkaus	8	Paino [kg]	2,10
Pituus [mm]	210	Leveys [mm]	155	Korkeus [mm]	105

Ouneva Oy

Teollisuustie 21
 FI-82730 Tuupovaara
 Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducs.fi

Product data

Product code	VG03-0009	STK-code	1912095	EAN-code	6410019120950
Product name	OJL-connector 400 FBB		ETIM class	EC000276	
Wires	IN: Busbar Cu 10x(1x24) OUT: 3xCu(6-50 mm ²) / 4xCu (2,5-35mm ²)				

Technical data

Nominal current (IEC)	Cu	425	A
	Al	380	A
Nominal voltage (IEC)		1000	V
		-	
		-	
Number of poles		1	pcs
Max. Cross section		10x(1x24)	mm ²
Tightening torque			
	2,5-35 mm ²	6	Nm
	6-50 mm ²	10	Nm
	10xCu(1x24)	10	Nm
		-	
Input	Busbar Cu 10x(1x24)		
Output	3x Cu(6-50 mm²) / 4x Cu (2,5-35mm²)		
	-		
Operating temperature		80	°C
Weight		247	g
IP-protection		IP20	




Standards	EN 61238-1:2003; EN 60947-7-1:2009
Color / Material	Grey Cover, Grey Housing RAL 7035 PA66/V0, Connector part tin plated aluminium
Mounting / Connection	DIN-rail and 4x screw (M5) mounting

Description

Single pole distribution block for branching connections. The OJL distribution block is compact and distributes the current through 7 output cables. Input connection with flexible busbar. Max 10x(Cu 1x24).

Drawing



Package

Package	Box	Pcs / Package	8	Weight [kg]	2,10
Length [mm]	210	Width [mm]	155	Height [mm]	105

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIN Rail Terminal Blocks](#) category:

Click to view products by [Ouneva](#) manufacturer:

Other Similar products are found below :

[00110420202](#) [8WA1011-1BH23](#) [9123140000](#) [RBO 5-T-B-HEX](#) [HSL-TB64-DIN](#) [90.070](#) [90.202](#) [912314](#) [260-301_NR](#) [280-560](#) [280-564](#)
[281-611/281-542](#) [281-673/281-411](#) [281-994](#) [283-317](#) [283-607](#) [264-724](#) [264-726](#) [280-530](#) [280-555](#) [280-619](#) [281-610](#) [281-622/281-417](#) [284-](#)
[317](#) [2907033](#) [35956](#) [USK 10](#) [102510](#) [5520682](#) [EMH 25-ZE30](#) [1SNK705210R0000](#) [1SNK705151R0000](#) [1SNK705020R0000](#)
[1SNK506066R0000](#) [1SNK506061R0000](#) [1SNK506012R0000](#) [1SNK505060R0000](#) [UM 45-SEFE M.NUT BK](#) [1SNK506013R0000](#)
[1SNK506030R0000](#) [1SNK506062R0000](#) [1SNK506065R0000](#) [1SNK508062R0000](#) [1SNK508065R0000](#) [1SNK508066R0000](#)
[1SNK705010R0000](#) [1SNK705012R0000](#) [1SNK705150R0000](#) [1SNK705152R0000](#) [1SNK705310R0000](#)