

ODP Series Programmable DC Power Supply

- + tow independent controllable channels
- + max output resolution : 1mV / 1mA
- + low ripples / low noise
- + up to 100 group timers



- + over-voltage / over-current protection
- + data-logging function: could record the output voltage, and current; and display recorded data in chart

- + 4 inch high resolution (480 x 320 pixels) LCD
- + multi- CI: USB, RS232, and LAN
- + auto-cooling system
- + SCPI, and LabVIEW supported

+ Performance Specifications

Model	ODP3122	ODP6062
Channel	2 (independent controllable channel)	
Max Output Power	378W	
Output Range	0 - 30V / 12A , 0 - 6V / 3A	0 - 60V / 6A, 0 - 6V / 3A

The specifications based upon the instrument having run for at least 30 minutes continuously, under the specified operating environment

Model		ODP3122	ODP6062	all 2 models
Channel		CH 1	CH 1	CH 2
Output Ratings (0°C - 40°C)	Voltage	0 - 30V	0 - 60V	6V
	Current	12A	3A	3A
Load Regulation	Voltage	≤0.01% + 3mV		
	Current	≤0.01% + 3mA		
Line Regulation	Voltage	≤0.01% + 3mV		
	Current	≤0.01% + 3mA		
Settings Resolution	Voltage	1mV		
	Current	1mA		
Read Back Resolution	Voltage	1mV		
	Current	1mA		
Settings Accuracy (25°C ± 5°C) (within 12 months)	Voltage	≤0.03% + 10mV		
	Current	≤0.1% + 8mA		≤0.1% + 5mA
Read Back Accuracy (25°C ± 5°C)	Voltage	≤0.03% + 10mV		
	Current	≤0.1% + 8mA		≤0.1% + 5mA
Noise and Ripple (20Hz - 20MHz)	Voltage (Vp-p)	≤4mVp-p		≤3mVp-p
	Voltage (rms)	≤1mVr		

	Current (rms)	≤5mArms	≤4mArms
Temperature Coefficient (0°C - 40°C)	Voltage	≤0.03% + 10mV	
	Current	≤0.1% + 5mA	
Read Back Temperature Coefficient	Voltage	≤0.03% + 10mV	
	Current	≤0.1% + 5mA	
Parallel Settings Accuracy	Voltage	≤0.02% + 5mV	
	Current	≤0.1% + 30mA	
Programmable Output	Storage	100 groups	
	Time Setting	second	
Data Recording	10 K groups (of voltage, current and power data) recording capacity		
Working Temperature	0 - 40°C		
Communication Interface	USB, RS232, and LAN		

Specifications subject to change without prior notice.

Display	ODP3122	ODP6062
LCD Type	4 inch color LCD	
Display Resolution	480 x 320 pixels, 65536 colors	

Mechanical Specifications	ODP3122	ODP6062
Dimension (W x H x D)	250 x 158 x 358 (mm)	
Device Weight	12.00 kg	

+ Application

R&D laboratory QC test industrial automation test
 automobile, and electronic circuit test education / teaching experimentation


+ Accessories The accessories subject to final delivery.



Power Cord




CD




Manual



USB Cable



Fuse



Test Leads (optional)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Benchtop Power Supplies](#) category:

Click to view products by [OWON](#) manufacturer:

Other Similar products are found below :

[NL200](#) [PR20](#) [ZUPNC403](#) [ZUP/W](#) [ZUPNC402](#) [TL89F2](#) [TL89K1](#) [TL89T1](#) [1332A-NIST](#) [ACC-GENH/RM](#) [P 6300](#) [SPE3102](#) [SPE3103](#)
[SPE6103](#) [GEN-150-10](#) [GEN-20-38/LN](#) [GEN-300-5](#) [GEN-40-19/LN](#) [GEN-50-30/LN](#) [GEN-60-12.5/LN](#) [GEN-60-55-1P230](#) [GEN-600-1.3](#)
[GENH-60-12.5/LN](#) [P 5995](#) [CPX200DP](#) [AX-3003P](#) [AX-6003P](#) [AX-8450A](#) [TPM-3003](#) [HMP2020](#) [HMP2030](#) [HMP4040](#) [1350](#) [UT804](#) [1410](#)
[XLNRC](#) [1513](#) [1514](#) [1550](#) [1651A](#) [1652](#) [1665](#) [1666](#) [1667](#) [1693](#) [1694](#) [1698](#) [MX100TP](#) [1739](#) [1762](#)