



## SDS1000 Series

**super- economical type digital storage oscilloscope**

- + Bandwidth : 20MHz - 200MHz
- + 2-Channel
- + Sample rate : 100MS/s - 1GS/s
- + Ultra-thin body
- + 7 inch high resolution LCD
- + SCPI, and LabVIEW supported

### + Performance Specifications

Model	SDS1022	SDS1052	SDS1102	SDS1202
Bandwidth	20MHz	50MHz	100MHz	200MHz
Sample Rate	100MS/s	500MS/s	1GS/s	
Horizontal Scale (s/div)	5ns/div - 1000s/div, step by 1 - 2 - 5		2ns/div - 1000s/div, step by 1 - 2 - 5	
Rise Time (at input, typical)	≤17.5ns	≤7ns	≤3.5ns	≤1.7ns
Channel	2			
Display	7" color LCD, 800 x 480 pixels			
Input Impedance	1MΩ ± 2%, in parallel with 20pF±5pF			
Channel Isolation	50Hz : 100 : 1, 10MHz : 40 : 1			
Max Input Voltage	400V (PK - PK) (DC+AC, PK - PK)			
DC Gain Accuracy	±3%			
Record Length	10K			
DC Accuracy (average)	Average≥16: ±(3% reading + 0.05 div) for ΔV			
Probe Attenuation Factor	1X, 10X, 100X, 1000X			
LF Respond (AC, -3dB)	≥10Hz (at input, AC coupling, -3dB)			
Sample Rate / Relay Time Accuracy	±100ppm			
Interpolation	sin (x) / x			
Interval (ΔT) Accuracy (full bandwidth)	Single : ±(1 interval time + 100ppm x reading + 0.6ns), Average>16 : ±(1 interval time + 100ppm x reading + 0.4ns)			
Input Coupling	DC, AC , and GND			
Vertical Resolution (A/D)	8 bits (2 channels simultaneously)			
Vertical Sensitivity	5mV/div - 5V/div (at input)			
Trigger Type	Edge, Video			
Trigger Mode	Auto, Normal, and Single			
Trigger Level	±5 divisions from screen center			
Line / Field Frequency (video)	NTSC, PAL and SECAM standard			
Cursor Measurement	ΔV, and ΔT between cursors			

Automatic Measurement	Vpp, Vavg, RMS, Frequency, Period, Vmax, Vmin, Vtop, Vbase, Width, Overshoot, Pre-shoot, Rise time, Fall time, +Width, -Width, +Duty, -Duty, Delay A→B  , Delay A→B  , area, cycle area	
Waveform Math	+, -, x, ÷, invert, FFT	
Waveform Storage	16 waveforms	
Lissajous	Bandwidth	Full bandwidth
Figure	PhaseDifference	±3 degrees
Communication Interface	USB host, USB device	
Frequency Counter	available	
Power Supply	100V - 240V AC, 50/60Hz, CAT II	
Power Consumption	< 15W	
Fuse	2A, T class, 250V	
Dimension (W x H x D)	301 x 152 x 70 mm	
Device Weight	1.10 kg	

Specifications subject to change without prior notice.

### + Application

electronic circuit debugging  
education and training

circuit testing

design and manufacture

automobile maintenance and testing

### + Accessories

The accessories subject to final delivery.



Power Cord



CD Rom



Manual



USB Cable



Probe



Probe Adjust



Soft Bag (optional)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Benchtop Oscilloscopes](#) category:*

*Click to view products by [OWON](#) manufacturer:*

Other Similar products are found below :

[UTD2072CL](#) [UPO1104](#) [MSO3354E-S](#) [UPO1202CS](#) [RTB-BNDL](#) [UTD2102CL+](#) [MSO3504E](#) [XDS4502](#) [P 1331](#) [UTD2202CEX+](#)  
[UTD2152CL](#) [P 1326](#) [UPO1102CS](#) [MSO2202-S](#) [MSO2202](#) [MSO2104-S](#) [P 1286](#) [UPO2074E](#) [UPO1204](#) [MSO2102-S](#) [FDS1102](#) [MSO2204-S](#)  
[FDS1102A](#) [UTD2052CEX+](#) [MSO2104](#) [T3DSO2204HD](#) [UPO1054](#) [UPO2104](#) [DSO3064A](#) [MSO5062D](#) [CC-650](#) [GDS-2204E](#) [2555](#) [2557](#)  
[2568](#) [BK2190E](#) [2563-MSO](#) [2565-MSO](#) [DSOX2MSO](#) [DSC-5300](#) [HDO4104A](#) [HDO4024A](#) [2540C](#) [2569-MSO](#) [2190E](#)  
[DSOX2002A/DSO0000-903](#) [MSOX2024A/DSO0000-903](#) [WAVESURFER 3104Z](#) [MDO-2204EX](#) [HANTEK DSO4084B](#)