



XSA1000TG Series Spectrum Analyzer

- + Frequency Range from 9 kHz up to 7.5 GHz
- + -160dBm Displayed Average Noise Level
- + Phase Noise -98dBc/Hz @1Gz and offset at 10KHz
- + Total Amplitude Accuracy < 1.5dB
- + 10Hz Minimum Resolution Bandwidth (RBW)

+ Performance Specifications

Model	XSA1015 (TG)	XSA1032(TG)	XSA1036(TG)	XSA1075(TG)
Frequency				
Range	9kHz-1.5 GHz	9kHz-3.2 GHz	9kHz-3.6 GHz	9kHz-7.5 GHz
Resolution	1Hz			
Frequency span				
Range	0 Hz , 100 Hz to maximum frequency of device			
Accuracy	$\pm \text{span} / (\text{swept points} - 1)$			
Internal reference				
Reference frequency	10.000000 MHz			
Reference frequency accuracy	$\pm [(\text{days from last calibrate} \times \text{freq aging rate}) + \text{temperature stability} + \text{initial accuracy}]$			
Temperature stability	<2.5ppm (15°C to 35°C)			<1ppm (15°C to 35°C)
Aging rate	<1ppm/year			
Readout				
Marker frequency resolution	$\text{span} / (\text{the number of swept points} - 1)$			
Uncertainty	$\pm (\text{freq indication} \times \text{freq reference uncertainty} + 1\% \times \text{span} + 10\% \times \text{resolution bandwidth} + \text{Marker Frequency Resolution})$			
Frequency counter				

Resolution	1 Hz , 10 Hz , 100 Hz , 1 kHz
Accuracy	\pm (marker freq \times freq reference uncertainty + counter resolution)

Bandwidth

Resolution bandwidth (-3 dB)	10Hz to 500kHz (in 1 to 10 sequence) , 1MHz , 3MHz
Resolution filter shape factor	<5 : 1 nominal (Digital implement, similar to Gauss Pattern)
Accuracy	<5% nominal
Video bandwidth (-3 dB)	10Hz to 3MHz

Amplitude Specification

Amplitude and electric level

Amplitude measurement range	DANL to +20 dBm , close the preamplifier	
Reference electric level	-80 dBm to +30 dBm , 0.01dBm steps	
Preamplifier	20 dB , nominal	
Input attenuator range	0~40 dB , 1 dB steps	0~50 dB , 1 dB steps
Max input DC voltage	50 VDC	
Max continuous power	+30dBm , average continuous power	

Displayed average noise level (DANL) Input attenuation 0 dB , 1Hz resolution bandwidth

Preamp off	1 MHz~10 MHz -140dBm (nominated)
	10 MHz~1GHz -140dBm (nominated)
	XSA1015TG:1GHz~1.5 GHz -138 dBm(nominated)
	XSA1032TG:1GHz~3.2GHz -138 dBm(nominated)
Preamp on	XSA1036TG:1GHz~3.6 GHz -138 dBm(nominated)
	XSA1075TG:1GHz~3.6GHz -138dBm(nominated) ; 4GHz~5GHz,-133dBm(nominated)
	5GHz~6GHz,-128dBm(nominated) ; 6GHz~7GHz-123dBm(nominated) ;
	7GHz~7.5GHz,-118dBm(nominated)
Preamp on	1 MHz~10 MHz -160dBm (nominated)
	10 MHz~1GHz -160dBm (nominated)
	XSA1015TG: 1GHz~1.5 GHz -158 dBm(nominated)
	XSA1032TG: 1GHz~3.2 GHz -158 dBm(nominated)

	XSA1036TG: 1GHz~3.6 GHz -158 dBm(nominated)	
	XSA1075TG: 1GHz~4GHz -158dBm(nominated);4GHz~5GHz -153dBm(nominated)	
	5GHz~6GHz -148dBm(nominated);6GHz~7GHz -143dBm(nominated)	
	7GHz~7.5GHz -138dBm(nominated)	
Phase noise	20 °C ~30 °C , fc=1 GHz	
Phase noise	<-82 dBc/Hz @10 kHz offset	<-98 dBc/Hz @10 kHz offset
	<-100 dBc/Hz @100 kHz offset	
	<-110 dBc/Hz @1 MHz offset	
Level display range		
Log scale coordinate	1dB ~255dB	
Linear scale coordinate	0 to reference level	
level unit	dBm, dBuW, dBpW, dBmV, dBuV, W,V	
Points	201~1001	
Number of traces	5	
Detectors	Positive-peak, negative-peak, sample, normal, RMS	
Trace functions	Clear write, Max Hold, Min Hold, View, Blank, Average	
Frequency response		
	20°C ~30°C , 30%~70% relative humidity, 20 dB input attenuation, reference 50 MHz	
Preamp off	±0.8 dB ;	
Preamp on	±0.9 dB ;	
Accuracy		
Input Attenuation Switching Uncertainty	20°C ~30°C , fc=50 MHz , Preamplifier Off , 20dB RF attenuation , input signal 1~40 dB ±0.5 dB	
Absolute Amplitude Uncertainty	20°C ~30°C , fc=50 MHz , RBW=1 kHz , VBW=1 kHz , peak detector, 20 dB RF attenuation , Preamplifier Off ±0.4 dB , input signal= -20dBm Preamplifier On ±0.5 dB, input signal= -40dBm	
Uncertainty	input signal range 0dbm~-50dbm	
	±1.5 dB	
VSWR	input 10 dB RF attenuation , 1 MHz~1.5GHz	input 20 dB , 1 MHz~7.5GHz

	<1.5 , nominal
--	----------------

Distortion and spurious response

Second harmonic distortion	$f_c \geq 50 \text{ MHz}$, Preamp off, signal input -30 dBm, 0 dB RF attenuation, 20 °C to 30 °C
	-65dbc
Third-order intermodulation	$f_c \geq 50 \text{ MHz}$
	+2 dBm (NSA1015/NSA1032/NSA1036)
	+10dBm(NSA1075)
1 dB Gain Compression	$f_c \geq 50 \text{ MHz}$, 0 dB RF attenuation , Preamp off , 20 °C to 30 °C
	+2 dBm, nominal
Residual response	connect 50 Ω load at input port , 0 dB input attenuation , 20 °C to 30 °C
	<-85dBm , nominated
Input related spurious	-30 dBm signal at input mixer , 20 °C to 30 °C
	<-60 dBc

Sweep time and triggering

Span range	$100\text{Hz} \leq \text{SPAN} \leq 3\text{GHz}$ 10ms to 3000s
	zero sweep width 1ms to 3000s
Mode	Continue, single
Trigger	Free run, video

Tracking generator

Output frequency range	100 kHz~1.5 GHz	100 kHz~3.2 GHz	100 kHz~3.6 GHz (Tracking generator) 35 MHz~3.6 GHz (Tracking generator)	100 kHz~7.5 GHz (Tracking generator)
Output power level range	-30 dBm~0 dBm ,	-40 dBm~0 dBm ,		
Output power level resolution	1dB			
Output flatness	+/-3 dB			
Maximum safe reverse level	Average total power : +30 dBm , DC : $\pm 50 \text{ VDC}$			

Inputs and Outputs

Front panel RF input connector	50 Ω , N-type female
--------------------------------	-----------------------------

Front panel track generator output	50 Ω , N-type female
10 M reference input	50 Ω , N-type female
Communication port	USB HOST, USB DEVICE, LAN, earphone port, REF and VGA

General technical specification

Display	TFT LCD , 10.4 inches
Weight (without package)	About 5 kg
Dimension (W x H x D)	421 x 221 x 115 (mm)
Working temperature	0~40 °C
Storage temperature	-20 °C to +60 °C
Power	100V~240V 50/60Hz

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Spectrum Analysers](#) category:

Click to view products by [OWON](#) manufacturer:

Other Similar products are found below :

[GSP-730](#) [N9323C/PLG/N9322C-900](#) [N9324C/PLG/N9322C-900](#) [N9321C/PLG/N9322C-900](#) [N9322C](#) [N9322CK-SEC](#) [N9323C/N9322C-903](#)
[N9321C/N9322C-903](#) [N9324C/N9322C-903](#) [PSA1303](#) [PSA U02](#) [114991829](#) [114991830](#) [SNYPER-LTE+ \(USA\)v2](#) [T3SA3100](#) [T3SA3200](#)
[XSA1015-TG](#) [XSA810-TG](#) [PSA6005](#) [2682](#) [2683](#) [PR262](#) [109990009](#) [109990011](#) [109990014](#) [109990018](#) [109990035](#) [109990063](#)
[114990162](#) [RSA306B](#) [T3SA3000-NFP](#) [T3VNA1500](#)