


New
BK200SCP
 4/5SC size (HR23/34)

Old
 (HHR200SCP)

High rate discharge & rapid charge type

P type

■ **Dimensions** (with tube)




■ **Specifications**



Diameter		23.0 +0 / -1.0 mm	
Height		34.0 +0 / -1.5 mm	
Approximate Weight		42 g	
Nominal Voltage		1.2 V	
Discharge Capacity	Average ^{*1}	2100 mAh	
	Rated (min.)	1900 mAh	
Approx. Internal impedance at 1000Hz at charged state.		5 mΩ	
Charge	Standard	190 mA X 16 hrs.	
	Rapid ^{*3}	2000 mA X 1.2 hrs.	
Ambient Temperature	Charge	Standard	0 °C to 45 °C
		Rapid	0 °C to 40 °C
	Discharge		-10 °C to 65 °C
	Storage	<1 year	-20 °C to 35 °C
<6 months		-20 °C to 45 °C	
<1 month		-20 °C to 55 °C	
<1 week		-20 °C to 65 °C	

*1 After charging at 0.1 It for 16 hours, discharging at 0.2 It.
 *2 For reference only.
 *3 Need specially designed control system. Please contact Panasonic for details.

■ **Typical charge characteristics**



■ **Typical discharge characteristics**



Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic when determining charge/discharge specs, warning label contents and unit design.

*The data in this document are for descriptive purposes only and are not intended to make or imply any guarantee or warranty.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [NiMH - Nickel Metal Hydride Battery category](#):

Click to view products by [Panasonic manufacturer](#):

Other Similar products are found below :

[NH-2100A](#) [NH-600AAA](#) [NH-B320](#) [HHR-450AB21](#) [HHR-26SCPYP01](#) [HHR-300SCPYP20](#) [NH-1500AA](#) [HHR-210AHA01](#) [BK-110FHB01](#)
[NH1250AA](#) [NH-3000SC](#) [NH-1250AAL](#) [NH-7000D](#) [BK-120AAHA01](#) [BK-200AAB9B](#) [BK-250AB01](#) [BK-80AAAB9B](#) [HHR-200AB20](#)
[HHR-210AAC48](#) [HHR-210AB18](#) [HHR-25SCHY03](#) [HHR-300CHA03](#) [HHR-30SCPYP20](#) [HHR-370AHA05](#) [HHR-380A](#) [HHR-450A](#) [HHR-60AAAHB2](#) [HHR-75AAAB5B](#)