VALVE-REGULATED LEAD ACID BATTERIES: INDIVIDUAL DATA SHEET

LC-R121R3P



Specifications

Nom	12V	
Rated Cap	1.3Ah	
Dimensions	Length	3.819 inches (97.0 mm)
	Width	1.870 inches (47.5 mm)
	Height	1.969 inches (50.0 mm)
	Total Height	2.165 inches (55.0 mm)
Ар	1.30 lbs. (0.59 kg)	
Standard Terminals and Resin	UL94HB Faston 187	LC-R121R3P


Characteristics

Capacity ^(note) 77°F (25°C)		20 hour rate (65mA) 10 hour rate (120mA) 5 hour rate (210mA) 1 hour rate (850mA)	1.3Ah 1.2Ah 1.05Ah 0.85Ah	
		1.5 hour rate discharge Cut-off voltage 10.5 V	0.6A	
Internal Resistance		Fully charged battery 77°F (25°C)	Approx. 90mΩ	
Temperature		104°F (40°C)	102%	
dependency		77°F (25°C)	100%	
of capacity		32°F (0°C)	85%	
(20 hour rate)		5°F (-15°C)	65%	
Self discharge 77°F (25°C)		Residual capacity after standing 3 months	91%	
		Residual capacity after standing 6 months	82%	
		Residual capacity after standing 12 months	64%	
Charge Method (Constant Voltage)	Cycle use (Repeating use)	Initial current	0.52 A or smaller	
		Control voltage	14.5V to 14.9V (per 12V cell 25°C)	
	Trickle use	Initial current	0.195 A or smaller	
		Control voltage	13.6V to 13.8V (per 12V cell 25°C)	


(Note) The above characteristics data are average values obtained within three charge/discharge. Cycles not the minimum values.

For main and standby power supplies. Expected trickle life: 3-5 years at 25°C, Approx. 5 years at 20°C.


Dimensions (mm)



Discharge characteristics 77°F (25°C) (Note)



Duration of discharge vs. Discharge current (Note)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Sealed Lead Acid Battery category:

Click to view products by Panasonic manufacturer:

Other Similar products are found below:

1109004 0809-0012 0819-0012 0850-0004 0859-0012 0800-0004 LC-R0612P PS-1250F1 APCRBC123 APCRBC124 LCRA1212P NP12-12 NP3.2-12 LC-P127R2P LC-P0612P LC-R063R4P LC-R067R2P1 LC-R121R3P LC-R127R2P1 LC-X1220AP UP-VW1245P1 2320296 2320306 2320319 2320322 2320335 2320416 2320429 2908237 RBC32 RBC11A RBC36-SLT