LNJ426W83RA

Hight Bright Surface Mounting Chip LED

USS Type

■ Absolute Maximum Ratings $T_a = 25$ °C

Parameter	Symbol	Rating	Unit	
Power dissipation	P _D	40	mW	
Forward current	I_{F}	15	mA	
Pulse forward current *	I _{FP}	40	mA	
Reverse voltage	V _R	4	V	
Operating ambient temperature	T _{opr}	-30 to +85	°C	
Storage temperature	T _{stg}	-40 to +100	°C	

Note) *: The condition of I_{FP} is duty 10%, Pulse width 1 msec.

■ Lighting Color


Amber

■ Electro-Optical Characteristics $T_a = 25$ °C±3°C


Parameter	Symbol	Conditions	Min	Тур	Max	Unit
Luminous intensity *1	I _O	$I_F = 10 \text{ mA}$	12.0	35.0	102.0	mcd
Reverse current	I_R	$V_R = 4 V$		Work in	100	μΑ
Forward voltage	V _F	$I_F = 10 \text{ mA}$		2.05	2.5	V
Dominant emission wavelength *2	$\lambda_{ m d}$	$I_F = 10 \text{ mA}$	585	589	596	nm
Peak emission wavelength	$\lambda_{ m P}$	$I_F = 10 \text{ mA}$	10 1180	595		nm
Spectral half band width	Δλ	$I_F = 10 \text{ mA}$	dille	15		nm

Note) *1: Measurement tolerance: ±20%

^{*2:} Measurement tolerance: ±3 nm



■ Package (Unit: mm)



注記/Notes

1.パッケージ寸法については電極バリを含まない。

Measurement of the package doesn't include electrode projection.

2.単位:mm/Unit:mm

2 Ver. BEK

Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information de-scribed in this book.
- (3) The products described in this book are intended to be used for general applications (such as office equipment, communications equipment, measuring instruments and household appliances), or for specific applications as expressly stated in this book.
 - Please consult with our sales staff in advance for information on the following applications, moreover please exchange documents separately on terms of use etc.: Special applications (such as for in-vehicle equipment, airplanes, aerospace, automotive equipment, traffic signaling equipment, combustion equipment, medical equipment and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Unless exchanging documents on terms of use etc. in advance, it is to be understood that our company shall not be held responsible for any damage incurred as a result of or in connection with your using the products described in this book for any special application.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most upto-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
 Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. We do not guarantee quality for disassembled products or the product re-mounted after removing from the mounting board. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) When reselling products described in this book to other companies without our permission and receiving any claim of request from the resale destination, please understand that customers will bear the burden.
- (8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard LEDs - SMD category:

Click to view products by Panasonic manufacturer:

Other Similar products are found below:

LTST-C190KYKT LTST-C19GD2WT LTST-N683GBEW LTW-170ZDC LTW-M140SZS40 LTW-M140ZVS 598-8110-100F 598-8170100F 598-8610-202F 67-22VRVGC/TR8 AAAF5060QBFSEEZGS HLMA-QG00-S0021 HLMP-6305-L0011 ALMD-LB36-SV002

APT1608QGW 15-21UYC/S530-A3/TR8 EAST2012YA0 EASV1803BA0 LG M67K-H1J2-24-0-2-R18-Z LS A676-P2S1-1

SML310BATT86 SML-512VWT86A SML-LX0606SISUGC/A SML-LXL1307SRC-TR SML-LXR851SIUPGUBC LT1ED53A FAT801-S

AM27ZGC03 APB3025SGNC APFA3010SURKCGKQBDC APHK1608VGCA APT2012QGW CLX6D-FKB-CN1R1H1BB7D3D3 LTST
C250KGKT LTW-010DCG LTW-020ZDCG LTW-21TS5 LTW-220DS5 JANTXM19500/521-02 UYGT801-S 42-21UYC/S530-A3/TR8

LO T67F-V1AB-24-1 YGFR411-H 598-8330-117F SML-LX0402IC-TR CMDA20AYAA7D1S CMDA16AYDR7A1X 598-8040-100F 598-8070-100F 598-8140-100F