Panasonic ideas for life

TOGGLE SWITCH

T-06/T-03 SERIES SWITCHES





FEATURES

Depth of 18.6 mm saves space.

This space-saving switch has body dimensions of 25 (W) x 14.8 (D) x 18.6 (H). (63% that of our previous T-15 series switch.)

PRECAUTIONS WHEN USING CADMIUM-FREE CONTACT TYPE


Models with cadmium-free contacts have been introduced in order to reduce environmentally harmful substances. ("F" is affixed to the end of the part number.) We ask customers who are currently using products with cadmium-containing contacts (no "F" at the end of the part number) to please make the switch to models with cadmium-free contacts. When switching, operating life may differ depending on the load. Please be sure to verify this by conducting an evaluation using actual equipment.

RoHS Directive compatibility information http://www.nais-e.com/

DATA (Life curve)

Tested sample: T-06 series

Tested condition: 125 V AC, 250 V AC, Power factor: 0.6 and 10 cpm



PRODUCT TYPES

1) T-06 series

Number of poles	Kind of operation	Solder terminal
		Product No.
1-pole	ON-OFF	T106A-F
	ON-ON	T106D-F
2-pole	ON-OFF	T206K-F
	ON-ON	T206N-F

Remark: The product comes with standard installation accessories. However, keying washer is sold separately.

2) T-03 series

Number of poles	Kind of operation	Solder terminal
		Product No.
1-pole	ON-OFF	T103A-F
	ON-ON	T103D-F
2-pole	ON-OFF	T203K-F
	ON-ON	T203N-F

Remark: The product comes with standard installation accessories. However, keying washer is sold separately.

T06/T03

SPECIFICATIONS

1. Contact rating

Kind of load	T-06 series	T-03 series
Resistive load	6A 125V AC,6A 30V DC, 3A 250V AC	3A 125V AC, 2A 250V AC
Inductive load 6 A 125 V AC (Power factor: 0.6), 3 A 250 V AC (Power factor: 0.6)		3 A 125 V AC (Power factor: 0.6), 2 A 250 V AC (Power factor: 0.6)
Motor load (single phase) 100W 125V AC, 100W 250V AC		<u> </u>

2. Characteristics


Mechanical expected life	Min. 5×10 ⁴
Electrical expected life	T-06 series: Min. 3×10 ⁴ (10 cpm) at rated load, T-03 series: Min. 10 ⁴ (10 cpm) at rated load
Overload life	Min. 50 (5 cpm) (Rated load×1.5)
Insulation resistance	Min. 100 MΩ (at 500 V DC measured by insulation resistive meter)
Breakdown voltage	1500 Vrms (at detection current: 10mA)
Vibration resistance	10 to 55 Hz at double amplitude of 1.5 mm (contact opening: Max. 1 ms)
Contact resistance	Initial, Max. 20 mΩ (By voltage drop at 1 A, 2 to 4 V DC)
Actuator strength (static load)	112.7N for 1 min.
Terminal strength (static load)	24.5N for 1 min.
Ambient temperature	-25°C to +70°C
Contact material	AgZnO alloy


ELECTRICAL CIRCUIT DIAGRAM (for T-06 and T-03 series)

			1-pole	2-pole
Terminal arrangement (As seen from terminal side)			1 — 2 — 3 — Keyway	1— 4— 2— 5— 3— 6—
Handle position and contact terminal number	ON-OFF	R _{Keyway}	2-3	2-3, 5-6
		_	_	_
		Keyway	_	_
	ON-ON	R _{Keyway}	2-3	2-3, 5-6
		_	_	_
		Keyway	1-2	1-2, 4-5
Remark			ON-OFF type does not have a terminal No. 1.	ON-OFF type does not have terminal No. 1 and 4.

DIMENSIONS (for T-06 and T-03 series) (mm) (General tolerance: ± 0.5)







Remark: ON-OFF type does not have terminal No. 1 and 4.

MOUNTING DIMENSIONS (for T-06 and T-03 series) 12.3 dia. 12.5 dia Panel cutout (mm)

Max. 2.5 mm* Panel thickness Max. 3.5 mm Max. 3.5 mm (Using separately sold keying washer.)

Remarks: 1. For panel installations, use the back hex nut. 2. * Keying washer (separately sold) Part No.: AJ3083

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Toggle Switches category:

Click to view products by Panasonic manufacturer:

Other Similar products are found below:

8928K478 020017-13 60012L 6006L CS115W CS120W 6663 7101SPDV30BE 7103SDV30BE 7105D 7108P3YAV2BE 71YY50282
7300K36 7301K38 7306K36 7310K36 7506K4 7592K6 7660K12 7691K14 7700K1 8391K108 8396K108 8811K17 8824K14 8828K13
8835K3 8858K44 PS83-121G 1-1825192-0 A201SCWZB04 A207SYCB04 A208J61ZQ0004 A221T1TCQ A323S1CWZQ
A423S1CWZG-M8 1201W 12156AX408 12147AGKX679 12246X778 12TW49-3D 130312 13037L 13001X AE101MD1W4B04
AE208SD1W4B04 MS24659-22D MS27407-5 1520230-9 1520231-1