# <sup>®</sup> PHYSICAL INFRASTRUCTURE SOLUTIONS



A. System

**Overview** 

С. Fiber

Optic

Systems

D. Power

over Ethernet

Ε. Zone Cabling

F. Wireless

G. **Outlets** 

H. Media Distribution

> ١. Physical

Infrastructure

Management

J. Overhead &

Underfloor Routing

K.

Surface

Raceway

L. Cabinets, Racks & Cable Management

Μ. **Grounding** & Bonding

(ŸL

### Surge Suppressor Jumper Kit

- · Bonds power or data line surge suppressor to grounding strip or grounding busbar
- · Both ends factory terminated to provide a bolt-on solution



Part Number	Part Description	Std. Pkg. Qty.
SSGK-1	#10 AWG (6mm <sup>2</sup> ) jumper; 24" (.61m) length; factory terminated on both ends; one-hole lug on surge suppressor to two-hole lug on grounding strip/busbar side; provided with .16 oz. (5cc) of antioxidant and two each #12-24 x 1/2", M6 x 12mm, #10-32 x 1/2" and M5 x 12mm thread-forming screws.	1

grounding requirements

### Armored Cable Grounding Kit

- · Provides a secure bond to the armor sheath on indoor and indoor/outdoor fiber optic cables at both cassette and enclosure ends
  - · Worm-gear design evenly distributes forces across the armor
- · Made from steel and aluminum material is compatible with common armor for long term reliability
- Black insulating cover protects and hides the connection for an aesthetically pleasing work area
- · Complies with industry requirements ensuring a high level of reliability and safety

· Engineered to comply with US and International

<u> . .</u>

Std.

Dka

Ó

Part Number	Part Description	Qty.
ACG24K	#6 AWG (16mm <sup>2</sup> ) jumper for armored cable diameter up to 0.84" (21.3mm); 24" (609.6mm) length; factory terminated on one end with LCC6 two-hole copper compression lug and the other end with grounding terminal; provided with two each #12-24 and M6 thread-forming screws and a black polypropylene terminal cover.	1
ACG24K-500	#6 AWG (16mm <sup>2</sup> ) jumper for armored cable diameter 0.85" (21.3mm) to 1.03" (26.2mm); 24" (609.6mm) length; factory terminated on one end with LCC6 two-hole copper compression lug and the other end with grounding terminal; provided with two each #12-24 and M6 thread-forming screws and a black polypropylene terminal cover.	1
ACGK	Armored cable grounding kit with one grounding terminal for #6 AWG and one #10 mechanical clamp, 9/16" – 1 1/16" diameter range.	1

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fibre Optic Cable Assemblies category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

7-21002-9 760-1518 FA04390-50-M-72-LC-N MLB 501 V RED MLB 501 V YELLOW 1-3636-600-5208 2061529-7 1-6693182-0 1754898-1 21055-6 FXBSCSCE2LM002 3000005 3-21053-2 MLB 200/1 V BLACK 5492011-6 106284-7000 5492011-5 5492011-8 5492011-9 8-21007-5 2123524-2 2123524-1 106386-4447 DFSM-SCSC-2M 2123909-4 2123909-8 106273-0629 2125046-1 2821236-3 2821310-2 2821310-3 2821313-4 FX2ERLNLNSNM0.5 CF-980062-074 CF-901200-394 CF-980062-073 CF-980062-071 CF-980062-075 CF-980062-072 17-300310-100 2821236-2 2821313-1 G-FC-FC-S-002.0-DX-A-18-Y G-E2A-E2A-S-003.0-SX-A-18-Y 956-322-502214 FA04474 1083665 1111540 1111843 1115533