Bridle Rings and Fastening Clip

- Multiple diameters, thread sizes, and configurations
- Threaded and non-threaded sizes are compatible with spring steel clip (BR-MPCL) clamp providing a solid securing point for the bridle ring
- · Other unique labor saving assemblies differentiate from competition - including pre-assemblies with powder actuated fasteners, toggle wings, and clearance holes for user supplied fasteners

A. System **Overview**

B1. **Cable Ties**

B2.

Cable

D3. Grounding Connectors

E1. Labeling

Systems

E2. Labels

E3. **Pre-Printed** & Write-On Markers

E4. Permanent Identification

Std.





Non-Threaded #8 Wire



Wood Screw Thread



User Supplied Nail or Fastener

Power Actuated

Fastener

Integrated **Toggle Screw**


Part Number	Part Description	Pkg. Qty.	Cable Accessories
Bridle Rings			
BR50	Bridle ring, .50" dia., non-threaded #8 wire (.162).	100	B3. Stainless Steel Ties
BR75	Bridle ring, .75" dia., non-threaded #8 wire (.162).	100	
BR-1.25	Bridle ring, 1.25" dia., non-threaded #8 wire (.162).	100	
BR-2.0	Bridle ring, 2.00" dia., non-threaded #8 wire (.162).	100	C1. Wiring Duct
BR50-10-24	Bridle ring, .50" dia., 10 - 24 threaded.	100	
BR75-10-24	Bridle ring, .75" dia., 10 - 24 threaded.	100	
BR-1.25-10-24	Bridle ring, 1.25" dia., 10 - 24 threaded.	100	C2. Surface Raceway
BR-2.0-10-24	Bridle ring, 2.00" dia., 10 - 24 threaded.	100	
BR-1.25-1/4-20	Bridle ring, 1.25" dia., 1/4 - 20 threaded.	100	
BR-2.0-1/4-20	Bridle ring, 2.00" dia., 1/4 - 20 threaded.	100	C3. Abrasion Protection
BR-4.0-1/4-20	Bridle ring, 4.00" dia., 1/4 - 20 threaded.	50	
BR-1.25-14WS	Bridle ring, 1.25" dia., 16 wood screw thread.	100	
BR-2.0-14WS	Bridle ring, 2.00" dia., 16 wood screw thread.	100	
BR-1.5-PAF	Bridle ring, 1.50" dia., with powder actuated fastener.	50	C4. Cable Management
BR-2.0-PAF	Bridle ring, 2.00" (50.8mm) dia., with powder actuated fastener.	50	
BR-1.5-SN	Bridle ring, 1.50" dia., user supplied nail or fastener.	100	
BR-2.0-SN	Bridle ring, 2.00" dia., user supplied nail or fastener.	100	D1. Terminals
BR-1.5-TW	Bridle ring, 1.50" dia., with integrated toggle screw.	25	
BR-2.0-TW	Bridle ring, 2.00" dia., with integrated toggle screw.	25	
General Purpos	e Clip		
BR-MPCL	Multi-purpose clip; accommodates beam flange from $1/8"$ to $1/2"$, standard $1/4 - 20$ or $#10 - 24$ threaded bridle rings, standard drive rings, as well as non-threaded #8 wire bridle rings.	100	D2. Power Connectors

Low Voltage Mounting Brackets

· Choose design styles for new install or retrofit install



New Install



Retrofit Install

Part Number	Part Description	Std. Pkg. Qty.
LV-S-1G	Low voltage integral mounting bracket for new installations, single gang stud bracket.	25
LV-S-2G	Low voltage integral mounting bracket for new installations, double gang stud bracket.	25
LV-W-1G	Low voltage mounting bracket for retrofit installations; single gang box with screws; suitable for wall material thicknesses of 1/2" to 1 1/2".	100
LV-W-2G	Low voltage mounting bracket for retrofit installations; double gang box with screws; suitable for wall material thicknesses of 1/2" to 1 1/2".	50

· Available in both single and double gang configurations

E5. Lockout/ Tagout & Safety Solutions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Mounting & Accessories category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

582603-1
009333-000
727844N003
747
809090N001
843188-000
8666
967279N002
DB-11
1300840039
1300900096
1301800416

1302264450
1300830184
1300830729
1300900039
1301580036
1301850553
1301860939
1302261315
1302264431

1337706-2
APA18-AK
1724
1-787307-1
185491N001
1868
HP-6N
C-202-C
202C221-13-0
CA7308-000
8S23-75FR-CS8184
2684
9648

3089
988382-000
A72821-000
AA401
173506-000
1823
202C292-13-0
202C302-13-0
2109
300625
3330
3412
356247-1
M9142

M9143
M9143
M9143
M9144
M91