

Specifications

| Performance Level | Category 6A |
|-------------------|-----------------|
| Connector Type | Jack Module |
| Termination Style | TG Style |
| Body Material | ABS |
| Contact Material | Phosphor Bronze |

🔇 Choose Language 💪 Contact Us 🛛 🔒 My Account

Bill of Materials

Top of Page 🔨

| Module Type | Mini-Com T568A/T568B | | |
|------------------------------------|-------------------------|--|--|
| Wiring Scheme | | | |
| Number of Contacts | 8 | | |
| Number of Positions | 8 | | |
| Shield Type | Unshielded (UTP) | | |
| Connector 1 Type | RJ45 | | |
| Connector 2 Type | Wire Cap | | |
| Sub Brand | PanNet | | |
| Maximum Operating Temperature (°C) | 65 | | |
| Maximum Operating Temperature (°F) | 149 | | |
| Minimum Operating Temperature (°C) | -10 | | |
| Minimum Operating Temperature (°F) | 14 | | |
| Maximum Storage Temperature (°C) | 70 | | |
| Maximum Storage Temperature (°F) | 158 | | |
| Minimum Storage Temperature (°C) | -40 | | |
| Minimum Storage Temperature (°F) | -40 | | |
| Resistance Properties | Heat-Resistant | | |
| Color | Orange | | |
| Product Type | UTP Jack Module | | |
| RoHS Compliancy Status | Compliant | | |
| Min. Order Qty. | 1 | | |
| | | | |

Packaging Detail

| UPC | 61305644946 |
|-----------------------|-------------|
| Std. Pkg. Qty. | 1 |
| Std. Pkg. Volume (cf) | 0.0032 |

| Std. Ctn. Qty. | 50 |
|-----------------------|--------|
| Std. Ctn. Volume (cf) | 0.1604 |

Resources

| Part Drawings | TX6A 10Gig Category 6a Jack Module with Left/Right Wire Cap Assembly | US English | View DWG (460.79KB) | Download DWG |
|----------------------|---|------------|------------------------|-----------------|
| Part Drawings | TX6A 10Gig Category 6a Jack Module with Left/Right Wire Cap Assembly | US English | View DXF (3.75MB) | Download DXF |
| Specification Sheets | 45° Angled Wire Caps for Mini-Com UTP Jack Modules | US English | View PDF (795.37KB) | Download PDF |

Related Products



CJ688TGBU

The Category 6, RJ45, 8-position, 8wire, UTP Mini-Com® universal jack module has TG-style termination and is blue.



CJ688TGBL

The Category 6, RJ45, 8-position, 8wire, UTP Mini-Com® universal jack module has TG-style termination and is black.



CJS6X88TGY

Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.





800-777-3300

Company Profile

Media Resources

Panduit Code of

Case Studies

Conduct

Monday through Thursday 7:00 am-6:30 pm CST Friday 7:00 am-6:00 pm CST



Where to Buy

Find a Panduit Distributor or Partner

About Us

Research and Development

Awards Partner Ecosystem

World Headquarters

f G+ You Tube in **(y)**

Careers at Panduit The Hub – Partner Portal **Product Registration** Panduit Connections Blog

Get Our Catalog

Which catalog would you like?

Copyright 2019 Panduit

Download the PDF or request a copy be mailed to you. Download

Legal Information Privacy Policy Unsubscribe

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

 RJE231881317T
 MP1010RX-1000
 MP44RX-1000
 GAX-3-66
 GAX-8-62
 93606-0253
 GD-A-44
 GDCX-PA-66-50
 GDCX-PN-64
 GDCX-PN-64

 PN-66
 GDCX-PN-66-50
 GDLX-A-66
 GDLX-A-88
 GDLX-N-66
 GDLX-S-88K
 GDTX-S-88-50
 GDX-PA-1010
 GLX-N-1010M-BLK

 GLX-N-44M
 GLX-S-88M-BLK
 GMX-N-1010
 GMX-S-1010
 GMX-S-66
 GMX-SMT2-N-1010
 GMX-SMT2-N-64-50
 GMX-SMT2-S6-88

 GMX-SMT4-N-88
 GPX-2-64
 GRT1-BT1-5
 GSGX-N-2-88
 GSX-NS2-88-3.05
 GSX-NS2-88-3.05-50
 GSX-NS-88-3.05-30
 GSX-NS-88-3.05-30

 3.05-50
 GSX-NS-88-3.68
 1-1775629-2
 GWLX-S-88-GR
 GWLX-S9-88-YG
 1300500326
 1300500227
 1300530003
 1300570002
 1324640-4

 RJ11FTVC2G
 RJ11FTVC2N
 RJFTVX2SA1G
 132764-001
 1400000
 1413176
 1413235