B. Copper Systems

C. Fiber Optic Systems

D. Power over **Ethernet**

E. Zone Cabling

Wireless

G. **Outlets**

H. Media Distribution

ı. Physical Infrastructure Management

J. Overhead & Underfloor Routing

Surface Raceway

Cabinets, Racks & Cable

Μ. Grounding & **Bonding**

N. Industrial

0. Labeling & Identification

Cable Management Accessories

> Q. Index

Rack Mount Cable Management Accessories

- · Bend radius control fingers support cables as they transition to the vertical pathway
- · Finger spacing aligns with rack units

- Attach to patch panels or equipment mounting screws
- Lightweight plastic construction provides durability and easy installation



CMBRC1



Part Number	Part Description	No. of Rack Spaces^	Std. Ctn. Qty.
CMBRC1	Kit of two bend radius control fingers; for use with patch panels. Maintains $1/2$ " bend radius control. Dimensions: 1.7 "H x .8" W x 3.0 "D (44mm x 19mm x 77mm).	1	10
CMBRC1E	Kit of two bend radius control fingers, for use with patch panels. Maintains 1/2" bend radius control. Dimensions: 1.7"H x 1.0"W x 5.1"D (44mm x 25mm x 129mm).	1	10
CMBRC5	One-piece unit with five bend radius control fingers; for use with active equipment. Maintains 1/4" bend radius control. Dimensions: 8.7"H x 1.0"W x 3.3"D (222mm x 26mm x 84mm).	5	10
CMBRC5E	One-piece unit with five bend radius control fingers; for use with active equipment. Maintains 1/4" bend radius control. Dimensions: 8.7"H x 1.0"W x 5.1"D (222mm x 26mm x 129mm).	5	10

[^]One rack space = 1.75" (44.45mm).

All product color is black.

Hinged Wall Brackets

- Mount to wall or standard EIA 19" rack
- · Cable tie slots
- Standard 19" EIA hole spacing

- Panel rotates from one side for easy access to cabling
- · Include write-on labeling area
- · Accept 19" patch panels, horizontal managers, and equipment



WBH4E

Part Number	Part Description	Rack Spaces^	Pkg. Qty.
6" Deep Wall	Brackets		
WBH1	Dimensions: 1.8"H x 20.2"W x 6.3"D (44mm x 513mm x 159mm). Load rating 10 lbs.	1	1
WBH2	Dimensions: 3.5"H x 20.2"W x 6.3"D (89mm x 513mm x 159mm). Load rating 20 lbs.	2	1
WBH3	Dimensions: 5.3"H x 20.2"W x 6.3"D (133mm x 513mm x 159mm). Load rating 30 lbs.	3	1
WBH4	Dimensions: 7.0"H x 20.2"W x 6.3"D (178mm x 513mm x 159mm). Load rating 40 lbs.	4	1
15" Deep Wa	III Brackets		
WBH2E	Dimensions: 3.5"H x 20.4"W x 15.8"D (89mm x 519mm x 402mm). Load rating 20 lbs.	2	1
WBH4E	Dimensions: 7.0"H x 20.4"W x 15.8"D (177mm x 519mm x 402mm). Load rating 40 lbs.	4	1
WBH6E	Dimensions: 10.5"H x 20.4"W x 15.8"D (267mm x 519mm x 402mm). Load rating 60 lbs.	6	1

^One rack space = 1.75" (44.45mm).

All product color is black.

No. of Std.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Ducting & Raceways category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

```
800A-LB 801I-LSP 802A-ECSP 802I-ICSP 923223-000 PRAF6WH-X A0405538 1301150342 1301160034 1301170070 1301180011 1301230083 1301230153 1301240273 1301250006 1302261238 1302261321 1302262552 1302263103 1302263178 1302263259 1302263816 1302263860 1302264375 1302264390 1301150343 1301160030 1301170050 1301170051 1301170061 1301180013 1301230086 1301230130 1301240054 1302260055 1302260376 1302261343 1302261344 1302262674 1302263095 1302263166 1302263209 1302263513 1302263851 1302263870 1302264137 1302264218 DD1/J AX101472 AX102007
```