

NOTES, UNLESS OTHERWISE SPECIFIED:

PANDUIT CT-1550 TOOL:

TOOL WEIGHT: 27.2 oz. [77] kg

Crimps most Panduit #22-#10 AWG insulated terminals & splices; and specific insulated

Reduced crimp effort advantage for #22-#14 AWG terminations.

Provides UL Listed and CSA Certified terminations with applicable Panduit terminals.

DIMENSIONS SHOWN IN BRACKETS [] ARE METRIC, AND ARE FOR REFERENCE ONLY.

	ENG	GLISH	METRIC			
CRIMP	GO / NO	GO GAGE	GO / NO GO GAGE			
POCKET	MEN	1BERS	MEMBERS			
AWG / mm²	"G" Dia.	"NG" Dia.	"G" Dia.	"NG" Dia.		
	(GO)	(NO GO)	(GO)	(NO GO)		
22-14/0,5-2,5	0.101"	0.109"	2,56 mm	2,76 mm		
12-10/4,0-6,0	0.147"	0.155"	3,73 mm	3,93 mm		

							CT-1550 Contour Crimp™ Crimping Tool CUSTOMER DRAWING						
					ADDED GO – NO GO CHART		TP27602B01_01 UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:			D, M	PANDUT MATERIAL:		
01	12/12/16	BWG	BJPU	JADE	REMOVED GLOBAL LOGO MOVED MADE IN GERMANY TO FRAME.	4857/ 02	(.x) ± (.xx) ±	(1500)	± .ES ±				
00	5-07-15	BLR	BJPU	ABJ	RELEASED	4857	THIRD ANGLE PROJECTION			-	DRAWING NUMBER: TP27602B01		
REV	DATE	ВҮ	СНК	APR	DESCRIPTION	ECN	DRAWN BY: BLR	DATE: 5-07-15	CHK BJPU	SCALE NONE	SHT 1 OF 1	SIZE B	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Crimpers / Crimping Tools category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

010-0096 M225202-37 6-1579015-5 CT150-2-D02 622-6441LF M322 6-304052-1 63456-0054 63484-3701 63800-8355 63819-1875
63819-2875 63819-4475 63823-3475 63827-5375 64001-0975 64001-4175 64005-0175 662903-2 690602-6 7-1579001-9 7-23471-1
762637-1 808714-1 811242-5 999-50-020083 1-21002-3 1-21002-7 12085270 1-21002-6 1-21113-6 1-22548-4 125442-1
DCE.91.073.BVC DCE.91.090.3MVM DCE.91.130.5MVU DCE.91.202.BVCM 1338300-1 1-354003-0 1338301-1 DF62/RE-MD 142321
1456088-1 1490794-1 1-45804-6 1490357-2 1490357-3 AX100749 1-59619-7 1596970-1