



NOTES:

- MATERIAL:
BODY - COPPER
◇ DENOTES BODY IS TIN PLATED COPPER
SCREW - STEEL, ZINC PLATED
- UL LISTED & CSA CERTIFIED FOR USE UP TO 600V & TEMPERATURE RATED 90°C
- RATED FOR USE WITH COPPER STRANDED CODE CONDUCTOR ONLY
- THESE PARTS ARE RoHS COMPLIANT
- SEE PACKAGING LABEL FOR TIGHTENING TORQUE INFORMATION
- PROFILE OF COLLAR MAY VARY BETWEEN CURVED AND FLAT.
- PKG QTY:
C = 100
D = 250
Q = 25



PANDUIT PART NUMBER	WIRE RANGE COPPER	CURRENT RATING (AMPS)	STUD SIZE IN	DIMENSIONS - IN [mm] +/- .02 [.5]									HEX SIZE*
				G	W	K	A	M	T	H	L	C (MAX)	
CX35-36-CY	#14 AWG - #6 AWG	35	3/16"	0.23 [5.8]	0.38 [9.7]	0.19 [4.8]	1.04 [26.4]	0.38 [9.7]	0.07 [1.8]	0.49 [12.4]	0.38 [9.7]	0.22 [5.6]	SLOTTED
CX35-36-DY	#14 AWG - #6 AWG	35	3/16"	0.23 [5.8]	0.38 [9.7]	0.19 [4.8]	1.04 [26.4]	0.38 [9.7]	0.07 [1.8]	0.49 [12.4]	0.38 [9.7]	0.22 [5.6]	SLOTTED
◇ CX35-36T-CY	#14 AWG - #6 AWG	35	3/16"	0.23 [5.8]	0.38 [9.7]	0.19 [4.8]	1.04 [26.4]	0.38 [9.7]	0.07 [1.8]	0.49 [12.4]	0.38 [9.7]	0.22 [5.6]	SLOTTED
◇ CX35-36T-DY	#14 AWG - #6 AWG	35	3/16"	0.23 [5.8]	0.38 [9.7]	0.19 [4.8]	1.04 [26.4]	0.38 [9.7]	0.07 [1.8]	0.49 [12.4]	0.38 [9.7]	0.22 [5.6]	SLOTTED
CX70-14-CY	#14 AWG - #4 AWG (2) #14 AWG (2) #12 AWG	70	1/4"	0.31 [7.9]	0.50 [12.7]	0.25 [6.4]	1.27 [32.3]	0.50 [12.7]	0.08 [2.03]	0.57 [14.5]	0.46 [11.7]	0.28 [7.1]	SLOTTED
◇ CX70-14T-CY	#14 AWG - #4 AWG (2) #14 AWG (2) #12 AWG	70	1/4"	0.31 [7.9]	0.50 [12.7]	0.25 [6.4]	1.27 [32.3]	0.50 [12.7]	0.08 [2.03]	0.57 [14.5]	0.46 [11.7]	0.28 [7.1]	SLOTTED
CX125-14SL-QY	#4 AWG - #1/0 AWG	125	1/4"	0.43 [10.9]	0.62 [15.7]	0.31 [7.9]	1.53 [38.9]	0.62 [15.7]	0.11 [2.7]	0.77 [19.6]	0.57 [14.5]	0.41 [10.4]	SLOTTED
◇ CX125-56SLT-QY	#4 AWG - #1/0 AWG	125	5/16"	0.43 [10.9]	0.62 [15.7]	0.31 [7.9]	1.53 [38.9]	0.62 [15.7]	0.11 [2.7]	0.77 [19.6]	0.57 [14.5]	0.41 [10.4]	SLOTTED
◇ CX225-56HK-QY	#2 AWG - #4/0 AWG	225	5/16"	0.56 [14.2]	.99 [25.2]	0.50 [12.7]	2.19 [55.6]	1.00 [25.4]	0.11 [2.7]	1.13 [28.7]	0.85 [21.6]	0.50 [12.7]	3/16
◇ CX225-56HKT-QY	#2 AWG - #4/0 AWG	225	5/16"	0.56 [14.2]	.99 [25.2]	0.50 [12.7]	2.19 [55.6]	1.00 [25.4]	0.11 [2.7]	1.13 [28.7]	0.85 [21.6]	0.50 [12.7]	3/16
◇ CX225-38HKT-QY	#2 AWG - #4/0 AWG	225	3/8"	0.56 [14.2]	.99 [25.2]	0.50 [12.7]	2.19 [55.6]	1.00 [25.4]	0.11 [2.7]	1.13 [28.7]	0.85 [21.6]	0.50 [12.7]	3/16

* HEX STYLE & SIZE MAY DIFFER FROM CHART. DIFFERENCE IN SIZE WILL NOT AFFECT FIT, FORM, OR FUNCTION OF PART

						TITLE CX SERIES COPPER MECHANICAL CONNECTORS CUSTOMER DRAWING	
						ITEM REVISION NAME N41664BA-C41664/12	
						DATASET FILE NAME C41664/12.SLDDRW	
						UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .X ± .XXX ± .XX ± ANGLES ±	
						MATERIAL SEE NOTES	
						DRAWING NUMBER C41664_12	
						THIRD ANGLE PROJECTION	
						DRAWN BY JHNU	
						DATE 3/06	
						CHK JHNU	
						SCALE NONE	
						SHEET 1 OF 1	
						SIZE B	

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
12	4/13	JHNU	JHNU	RGB	REPLACED MISSING "A" DIMENSION REVISED HEX SIZE FOR CX225: 3/16 WAS 9/16	N41664BA-C41664
11	2/13	JHNU	JHNU	RGB	REVISED TITLE BLOCK	N41664BA-C41664

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [panduit manufacturer](#):

Other Similar products are found below :

[PK10-56R-L](#) [PCMBR-13](#) [PCPA11IW](#) [CRE32](#) [M200X042UPT](#) [M200X050ACT](#) [M200X050Y7T](#) [M200X080FQT](#) [M200X100ACT](#)
[M200X100AIT](#) [CRTW](#) [CSVBP](#) [CT-1000](#) [CT-1004](#) [CT-1104](#) [CT-2550CH](#) [CT-2570CH](#) [M300X050ACT](#) [M300X100ACT](#) [CT-900HPH](#)
[CUFB48BL](#) [CVED32VE](#) [CVED32VEPG](#) [CVED40VEN](#) [CVED40VEPG](#) [CWF400](#) [CWMPV2340](#) [CWMPV2440](#) [CWMPV3340](#)
[CWMPV3440](#) [MBEH-TLR](#) [MBH-MR](#) [MBH-MR316](#) [MBH-TLR316](#) [MBSH-TR](#) [MBS-MR](#) [MBS-MR316](#) [MBS-TLR316](#) [F512B10-NM1](#)
[F512B10-NM2](#) [F512D5-5F140Y](#) [F512D5-5F15Y](#) [F512D5-5F200Y](#) [F512D5-5F26Y](#) [F512D5-5F30Y](#) [F512D5-5F33Y](#) [F512D5-5F34Y](#)
[F512D5-5F45Y](#) [F512D5-5F50Y](#) [F512D5-5F54Y](#)