

Notes:


1. 600V max voltage rating
2. 257°F (125°C) max temperature rating of insulation material .
3. Stranded copper wire only
4. Material:
 - A. Stamping - brass, tin plated
 - B. Sleeve - copper or brass, tin plated.
 - C. Housing - Nylon type 6/6. Colors are translucent.
5. Packaging: Std. - L = 50 C = 100 ²
Bulk - D = 500 M = 1000
6. Dimensions in bracket are in mm Or mm


CERTIFIED
 LR31212


LISTED
 20H3
 E78522

Base part number	Package Code	Wire range AWG (mm ²)	Tab size	Housing color	A ±.03 (.8)	W ±.02 (.5)	Max. Insul.	F ±.02 (.5)	Wire Strip length +1/32, -0 (+0.8, -0)	Crimp tools
										DNF18-250FI
DNF14-250FI	-C -M	16-14 (1,5-2,5)	.250X.032 (6,3X,8)	Blue	.94 (23,9)	.36 (9,1)	.16 (4,1)	.24 (6,1)	CT-2400 W/CT-2455 CRIMP HEAD	
DNF10-250FI	-L -D	12-10 (4,0-6,0)	.250X.032 (6,3X,8)	Yellow	.95 (24,1)	.36 (9,1)	.22 (5,6)	.27 (6,9)	CT-100 & CT-550 CT-460	

A41672_03

03	01/06	DAW	DAW	REMOVED DNF18-187,188FI, and DNF14-187,188FI	TR00075			 CORP. TINLEY PARK, ILLINOIS FULLY INSULATED (STD NYLON) FEMALE DISCONNECTS SLEEVED BARREL (LOOSE PIECE)
02	1/05	KLFU	SKB	DNF10-250FI WAS .23(5,8) ADDED: (A) NOTE & GEOMETRY	12406	TRO	SKB	
01	5/01	KMD	SKB	ADDED DNF10-250FI TO TABLE. UDATED NOTE 5	09411	TRO	JAC	
00	3/99	ES	RLS	RELEASED	07540	TRO	JCJ	
REV	DATE	BY	CHK	DESCRIPTION	ECN #	PM	CUST	DRAWN BY ES CHK'D SCALE NONE DRAWING NO. A41672

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular MIL Spec Connector](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)
[60-042022-23P](#) [60-042217-10P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-207-2302](#) [6104-](#)
[208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-210-11149P](#) [6131-](#)
[211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-472](#) [CS3100A-36-](#)
[77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-32-17P](#) [CS3102A32-25S](#) [CS3102C18-4P-472](#)
[CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#) [M243082296Z](#)
[M2884010AC1S1](#) [CT0-24-10SC](#) [CT0M20-7PCAU](#) [M28840/17AC1G3](#)