
CERTIFIED LR31212


Panduit Part number	Wire range	Housing color	Dim. "F"	Minimum Wire	Maximum Wire	Tools	
Prefix	AWG (mm²)			Insulation Diameter	Insulation Diameter		
DNG18-250FL	22-18 (0,5-1,0)	Red	.24 (6,1)	.060 (1,52)	.126 (3,20)	CT-1014	
DNG14-250FL	16-14 (1,5-2,5)	Blue	.25 (6,4)	.080 (2,03)	.150 (3,81)	C1-1014	



Notes:

- 1. Used for:
 - A. 300 V maximum rating
 - B. Temperature Rating of Insulation: 105°C (221°F)
 - C. Stranded copper wire only

- 2. Wire strip length: 1/4 0 (6,4 0)
- 3. Material:
 - A. Stamping Tin plated brass
 - B. Housing Nylon
- 4. Tab size .250 X .032 (6,3 X ,8) Hole type detent
- 5. Packaging:
 - A. -X = 10 pieces
 - B. -C = 100 pieces
 - C. -M = 1000 pieces
- 6. Dimensions in brackets are in millimeters or mm²





07	10/06	DAW	DAW	ADDED -X PACKAGING CODE	TR00171	TRO	LCA		
06	6/04	JHNU		REVISED PART GEOMETRY IN VIEW.	011922	TRO	SKB	A41572_	07
05	1/01	EJS	SKB	WIRE RANGE FOR PART DNG18-250FL was (0,5-1,5), NOTE 1-B WAS 257°F(125°C) MAX TEMP RATING,FILE SPEC WAS N41569AA_PCD_04	08966	ССН	JAC		VII
04	1/97	JAMB	RLS	ADDED TO NOTES,"MIN. WIRE INSULATION DIA."	05405	DBH	LA		ЛГ
03	12/95	ED	RLS	REVISION TO NOTES AND UL RECOGNIZED	03835	TFKE	LA		
02	2/95	MS	JW	WIRE STRIP LNGTH WAS 3/16, TOOL NO. WAS CT-1000	03003	KS	LA	Fully	y In
REV	DATE	ВҮ	CHK	DESCRIPTION	ECN #	PM	CUST	BDK	CHK 'D



TINLEY PARK, ILLINOIS

Funnel wire entry

Wire

Crimp

Area

Disco-Lok[™] Loose piece Fully Insulated Locking Female Disconnect

BDK None JAW A41572

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

HT-13-10 71M-250-32-NB 01-2065-1-0216 00581P0075 M10-10RX M10BCK 60205-1 604200-1 60598-1-CUT-TAPE 60617-1-C 60873-1 M14-516R/SK M14-6RSX M18-8FBX M18-8R/LX M18BCK 61314-6-C 61-S 61-SN-A 62-NBM-A 63-S 640179-1 640917-2-CUT-TAPE 6501550002 66107-2-C 696683-1 696834-1 696861-1 696931-1 696999-1 M8-516RK M86700006 MA250DMFMX-A 701-2007 701-2307 701-7761-03 70F-110-32-PB 718-N-A 71M-187-20-NBL 71M-250-32-NBL 72F-187-20-NBL 72M-250-32-NBL 7310 73F-250-32 73F-250-32-NL F14-10C F-1M 751-250 76650-5002 76828-149