
+

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



NOTES:

- 1. SEE SHEET 2 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS.
- 2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY.
- 3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON.
- 4. TESTED TO EIA/TIA 568-B.3.
- 5. PATCH CORD ROUTING CONFIGURATION A TO B.
- 6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF ROHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE ROHS TECHNICAL ADAPTATION COMMITTEE.

REV	DATE	BY	СНК	DESCRIPTION	ECN -	R	CUST	SUP	ОТН	CHK 'D		(SHT. 1 of 2)	$\mid A \mid$		
R	06-04-07	MC		RELEASED TO PRODUCTION	02779-35	5				05-23-07		02779 - 35	SIZE		
										MC		SEE TABLE, SI	HT. 2		
										THIRD ANGLE PROJECTION	(.XX) (.XXX)±.010 (0.3) (.XX)±.03 (0.8) ANGLES	NONE			
											ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: DIMENSIONAL TOLERANCES ARE:				
											TINLEY PARK, ILL 60477				
·															
										CUSTOMER DRAWING					
										SI	SIMPLEX FIBER OPTIC PATCH CORD LC TO LC CONFIGURATION				

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

SIMPLEX FIBER OPTIC LC TO LC PATCH CORD											
PANDUIT		CABLE	LC CONNECTOR								
PART NO.	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	RL	COLOR				
FXF10-10M*Y		10GbE 50/125um 0M3		AQUA	0.30dB	26dB	ELECTRIC IVORY				
F5F10-10M*Y	RISER	50/125um OM2	SIMPLEX	ORANGE	0.30dB	20dB	ELECTRIC IVORY				
F6F10-10M*Y	(OFNR)	62.5/125um OM1	1.6mm	ORANGE	0.30dB	20dB	ELECTRIC IVORY				
F9F10-10M*Y		9/125um OS1		YELLOW	0.35dB	55dB	BLUE				

* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

										SIMPLEX FIBER OPTIC PATCH CORD LC TO LC CONFIGURATION CUSTOMER DRAWING						
										THERD ANGLE	TINLEY PARK, ILL 60477 ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: LXXXI: 010 10.31					
										DRAWN BY MC	REVIEW DRAWING NUMBERS	PART NO. SEE TA	BLE			
R	06-04-07	мС		RELEASED TO PRODUCTION	02779-35					05-23-07		drawing no. 02779 - 35	SIZE			
REV	DATE	BY	СНК	DESCRIPTION	ECN -	R	CUST	SUP	отн	CHK 'D		(SHT. 2 of 2)	A			

4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Ducting & Raceways category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

```
800A-LB 801I-LSP 802A-ECSP 802I-ICSP 923223-000 PRAF6WH-X A0405538 1301150342 1301160034 1301170070 1301180011 1301230083 1301230153 1301240273 1301250006 1302261238 1302261321 1302262552 1302263103 1302263178 1302263259 1302263816 1302263860 1302264375 1302264390 1301150343 1301160030 1301170050 1301170051 1301170061 1301180013 1301230086 1301230130 1301240054 1302260055 1302260376 1302261343 1302261344 1302262674 1302263095 1302263166 1302263209 1302263513 1302263851 1302263870 1302264137 1302264218 DD1/J AX101472 AX102007
```