## FiberRunner<sup>®</sup> Accessories



FR38DR



FR716DR



FR516DR



FRUIB-X



FRSSM2

-	Ø1.
1. o	1.1

FRSTRCLIP



FRTBKT-X

Part Number	Part Description	For Threaded Rod Size	Pkg.	Std. Ctn. Qty.	Optic Systems D. Power	
3/8" Nut Driver FR38DR	Used to disassemble 4x4, 6x4, and 12x4 FiberRunner® QuikLock <sup>™</sup> Couplers when required.	_	1	10	over Ethernet	
7/16" Nut Driver					E.	
FR716DR	7/16" nut driver for use with the FiberRunner <sup>®</sup> , GridRunner <sup>™</sup> , and Wyr-Grid <sup>™</sup> Systems.		1	10	Zone Cabling	
5/16" Nut Driver						
FR516DR	Used to disassemble 2x2 FiberRunner <sup>®</sup> QuikLock <sup>™</sup> Couplers when required.	_	1	10	F. Wireless	
Universal Innero	luct Bracket				G. Outlets H. Media	
FRUIB-X	Used to secure any size corrugated tubing or inner- duct to any surface including equipment racks and channel or fittings. Two 1/4" (6.3mm) holes must be	_	10	100		
	drilled through to secure brackets.					
Slack Spool Ma	nager with 2.37" Bend Radius Diameter				Distribution	
FRSSM2 The slack spool manager can be mounted 6x4, and 4x4 FiberRunner <sup>®</sup> Channels and Fiber-Duct <sup>™</sup> Channel to create an in-char management. It can be deployed in a vert	The slack spool manager can be mounted in 12x4, 6x4, and 4x4 FiberRunner <sup>®</sup> Channels and in 4x4 Fiber-Duct <sup>™</sup> Channel to create an in-channel slack management. It can be deployed in a vertical or horizontal channel run and can withstand a 20 lb. load		1	5	l. Physical Infrastructure Management	
	without pulling away from the base. Mounting fasteners are included.				J. Overhead & Underfloor Routing	
Strut Clip Kit						
FRSTRCLIP	Strut mounting clip assembly allows FiberRunner® Channel to be attached directly to standard 1 5/8" wide strut structures. Contains two clips and all hardware for	_	1	10	K. Surface Raceway	
	assembly. Bolts release with 7/16" nut driver.				L. Cabinets,	
1/4" T-Bolt Kit					Racks & Cable	
FRTBKT-X	T-bolts can be used for additional attachment when securing FiberRunner <sup>®</sup> Channel to mounting brackets.	_	10	100	Management M.	
	For example, a T-bolt can be inserted thru a 12x4 mounting bracket and positioned within the center rib structure on the underside of 12x4 channel. By tightening the nut, the 12x4 channel is more securely fastened to the mounting bracket.				M. Grounding & Bonding	

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

Table continued on next page

A. System **Overview** 

> B. Copper Systems

> C. Fiber Optic Systems D. Power over

B. Copper Systems

## PHYSICAL INFRASTRUCTURE SYSTEMS

## FiberRunner® Accessories (continued)

Optic Systems D. Power

C. Fiber

over Ethernet

E. Zone Cabling

F. Wireless

G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding & Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index



FRQMC-X



TR1-12-X TR1-58-X



TRC18FR-X8Y



CLT150F-X3

Part Number	Part Description	For Threaded Rod Size	Std. Pkg. Qty.						
FiberRunner <sup>®</sup> Quick Mount Clips									
FRQMC-X	Used wherever additional FiberRunner® Slide Clamps would be helpful. For example, use on 12x4 FiberRunner® QuikLock <sup>™</sup> Brackets to accommodate dual runs of 6x4 or 4x4 FiberRunner® Channel.	_	10	100					
Threaded Rod in One Foot Lengths									
TR1-12-X	Threaded rod can be used with various mounting brackets. Length = 12" (305mm).	1/2"	10						
TR1-58-X	Threaded rod can be used with various mounting brackets. Length = 12" (305mm).	5/8"	10						
Threaded Rod Cover									
TRC18FR-X8Y	Used to protect cabling from threaded rod. Vertical slit allows easy installation. For indoor use only. Gray.	1/2" – 5/8"	10	100					
Slit Corrugated Loom Tubing									
CLT150F-X3*	Slit corrugated loom tubing provides a vertical pathway as cables transfer from the FiberRunner® Fitting to the equipment below. Inside diameter is 1.48" (37.6mm) and outside diameter 1.73" (43.9mm). Sold in 10' rolls.		1						

\*For other colors replace suffix X3 (Orange) with X4 (Yellow) or X20 (Black).

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Screwdrivers, Nut Drivers & Socket Drivers category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

 272012M
 27850
 CE-16-03400-00-HNDLE-TORQ
 323451-000
 HMM-HH
 WUVT-1-120AC-P
 00-8987-YWPP
 TS-35
 32024
 XW4Z-00B

 49-22-4073
 96025
 96030
 96560
 96430
 31830
 92270
 96012
 96436
 96536
 92064
 72820
 96520
 92040
 96416
 96570
 72823
 96525
 96720

 31832
 92020
 96523
 96510
 96427
 92073
 92052
 72905
 72741
 72663
 32061
 30751
 KLEIN TOOLS SCREWDRIVER 4-IN-1
 612020B
 35 

 045
 6951
 83
 9058
 9977
 EMF
 PTE6