

QuickNet™ Signature Core™ Interconnect Cable Assemblies

general information

QuickNet™ Signature Core™ Interconnect Cable Assemblies allow for rapid deployment of high-density permanent links in a single assembly for data center applications requiring quick infrastructure deployment, such as main, horizontal, and zone distribution areas. These interconnect cable assemblies optimize cable routing requirements to ensure efficient use of pathway space and significantly reduce installation time and cost. They are built with modular MPO connectivity and provide compatibility, flexibility, and system performance in all permanent link applications.



technical information

Signature Core™ Fiber is a modal and chromatic dispersion compensating multimode fiber designed for optimum performance with high-speed Vertical Cavity Surfacing Emitting Lasers (VCSEL) transceivers. The refractive index profile is engineered to correct for the interaction between modal and chromatic dispersion increasing the total channel bandwidth. Current industry standards for OM3 and OM4 fibers neglect this interaction and as a result, channel reach can be significantly limited for a large population of VCSEL transceivers.

Like OM3 and OM4 fiber types, the actual supported reach for Signature Core™ Fiber depends on the electrical and optical characteristics of the VCSEL transceiver¹. Under worst-case conditions, Signature Core™ Fiber will provide at least a 20% increase in reach over uncompensated OM4 fibers. Under nominal conditions, Signature Core™ Fiber will support a 600m reach with 10GBASE-SR transceivers compared to a 400m maximum reach over OM4 as specified in IEEE 802.3². Applying the 20% minimum increase in reach for OM4 reach published in FC-PI-5 for Fibre Channel communication yields a reach of 225 meters with an 8G Fiber Channel transceiver (800-M5F-SN-I), and 150 meters with a 16G Fiber Channel transceiver (1 600-M5F-SN-I)³.

Signature Core™ Fiber is 100% standards compliant meeting all OM4 specifications, with an additional requirement for Differential Mode Delay (DMD) that compensates for modal and chromatic dispersion effects⁴.

application

Data centers requiring quick infrastructure deployment with extended reach that want to maintain bandwidth throughout the infrastructure.

construction

Cable type:	3.0mm round indoor
Cable jacket ratings:	Optical Fiber Non-Conductive Plenum (OFNP) Low Smoke Zero Halogen (LSZH)
Fiber types:	OM4+ Signature Core™ Fiber
Connector end 'A':	Type: MPO female Color: Black and Aqua Polarity: Method A
Connector end 'B':	Type: MPO female Color: Black and Aqua Polarity: Method A
Fiber count:	12
Jacket color:	Aqua

optical properties

Maximum cable attenuation:	2.3dB/km @ 850nm 0.6dB/km @ 1300nm
Maximum connector insertion loss:	0.25dB
Minimum connector return loss:	30dB

physical properties

Cable outside diameter (OD):	3.0mm
Minimum bend radius	Under load: 20 x cable OD Static: 10 x cable OD
Cable tensile strength (installation):	22N
Cable compressive load:	35N/cm short term 110N/cm long term
Cable flex:	25 cycles
Cable twist:	10 cycles

environmental properties

Storage and shipping temperature:	-40°C to +70°C (-40°F to 158°F)
Installation temperatures:	0°C to +40°C (32°F to 104°F)
Operating temperature:	0°C to +70°C (32°F to 158°F)

standards

Meets or exceeds ISO/IEC 11801, TIA/EIA-568-C.3, TIA-604-5 (FOCIS-5), TIA/EIA-568-C.1, RoHS compliant

¹The actual channel reach of a laser optimized, multimode fiber (OM3, OM4, or Signature Core™) depends on the optical and electrical parameters of the VCSEL transceiver. For worst-case optical and electrical parameters, Signature Core™ Fiber will provide at least 20% greater reach over standards un-compensated OM4 fiber.

²OM4 fiber was ratified in the IEEE802.3/D3.0 proceedings from 15-Dec-2011, Table 52-6 with an Operating Range of 2 to 400 meters.

³Reach values are a minimum.

⁴Differential Mode Delay (DMD) is a metric defined in telecommunications industry association standard EIA/TIA 455-220-A, January 2003, which describes a method for measuring the modal dispersion of laser optimized multimode mode fiber.

QuickNet™ Signature Core™ Interconnect Cable Assemblies

Part Number

Example: FSTRP5N5NKNM001 = Fiber OM4+ Signature Core™, 12-fiber, 3.0mm round indoor, plenum rated, MPO female with no breakout to MPO female with no breakout, polarity Method A, Ultra IL, no pulling eye, 1 meter

Character	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Example	F	S	T	R	P	5	N	5	N	K	N	M	0	0	1

1 – Type

F = Fiber product

2 – Fiber Type

S = OM4+ Signature Core™ Fiber

3 – Fiber Count

T = 12-fiber

4 – Cable Type

R = 3.0mm round indoor

5 – Flame Rating

L = Low Smoke Zero Halogen (LSZH)

P = Optical Fiber Non-conductive Plenum (OFNP)

6 – Connector Type End ‘A’

5 = MPO female

6 = MPO male

7 – Connector Variant

N = No variant

8 – Connector Type End ‘B’

5 = MPO female

6 = MPO male

9 – Connector Variant

N = No variant

10 – Performance/Polarity

K = Polarity A/Ultra IL

11 – Pulling Eye

N = No pulling eye


12 – Unit of Measure

M = meters

13, 14, and 15 – Length

001 – 030 meters

Interconnect Cable Assembly Detail



Notes:

- Standard lengths for MPO to MPO Signature Core™ Interconnect Cables are available from 1 – 30 meters in increments of 1 meter. For additional availability, please contact Panduit Customer Service.
- Cable Assembly lengths are measured as the distance between the furthest connector tips.
- For hybrid solutions and special cable constructions/ratings/colors/availability, consult Panduit.

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

PANDUIT®

©2013 Panduit Corp.
ALL RIGHTS RESERVED.
FBSP66--WW-ENG
9/2013

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fibre Optic Cable Assemblies](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[7-21002-9](#) [760-1518](#) [FA04390-50-M-72-LC-N](#) [MLB 501 V RED](#) [MLB 501 V YELLOW](#) [1-3636-600-5208](#) [2061529-7](#) [1-6693182-0](#)
[1754898-1](#) [21055-6](#) [FXBSCSCE2LM002](#) [3000005](#) [3-21053-2](#) [MLB 200/1 V BLACK](#) [5492011-6](#) [106284-7000](#) [5492011-5](#) [5492011-8](#)
[5492011-9](#) [8-21007-5](#) [2123524-2](#) [2123524-1](#) [106386-4447](#) [DFSM-SCSC-2M](#) [2123909-4](#) [2123909-8](#) [106273-0629](#) [2125046-1](#) [2821236-3](#)
[2821310-2](#) [2821310-3](#) [2821313-4](#) [FX2ERLNLNSNM0.5](#) [CF-980062-074](#) [CF-901200-394](#) [CF-980062-073](#) [CF-980062-071](#) [CF-980062-075](#)
[CF-980062-072](#) [17-300310-100](#) [2821236-2](#) [2821313-1](#) [G-FC-FC-S-002.0-DX-A-18-Y](#) [G-E2A-E2A-S-003.0-SX-A-18-Y](#) [956-322-502214](#)
[FA04474](#) [1083665](#) [1111540](#) [1111843](#) [1115533](#)