PANDUT[®] PHYSICAL INFRASTRUCTURE SYSTEMS



C. Fiber

Optic

Systems

D. Power

over Ethernet

E.

Zone

Cabling

F. Wireless

G.

Outlets

H. Media

Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

> K. Surface

Raceway

L.

Cabinets, Racks & Cable Management M. Grounding & Bonding

N.

Industrial

0. Labeling & Identificatio (ŸL

A. System

Overview

GP6[™] PLUS Category 6 High Density Kits

- Exceed ANSI/TIA-568-C.2 Category 6 standard
- Ideal for use in cross-connects and consolidation point applications
- Provides pre-packaged components necessary for termination



Part NumberPart DescriptionStd.
Pkg.
Qty.Std.
Ctn.
Qty.GPKBW144Y144-pair (36-port) Category 6 high-density punchdown field
termination kit with legs.110GPKBW432Y432-pair (108-port) Category 6 high-density punchdown field
termination kit with legs.110

• Kit includes required quantity of bases and 4-pair

Highly visible color-coded wiring slots ease wiring

connecting blocks, label holders and labels

GPKBW144Y



GPKBW432Y

	termination kit with legs.		
BW432Y	432-pair (108-port) Category 6 high-density punchdown field termination kit with legs.	1	
PVC or plenur	erminates most 22-26 AWG solid or stranded IWC wire with a 0.050" (1.27mm) m n rated.	ax o.d.	,

Termination tool available on page B.79 of SA-NCCB51.

To ensure optimal performance, Panduit recommends use with other Panduit Category 6 PLUS components. Can be clearly identified with labels found on page B.76 of SA-NCCB51.

(GP6[™] PLUS Category 6 Standard Density Kits

Cable either

- Exceed ANSI/TIA-568-C.2 Category 6 standard
- Ideal for use in cross-connects and consolidation point applications
- Provide pre-packaged components necessary for termination
- Kit includes required quantity of bases and 4-pair connecting blocks, label holders and labels
- · Highly visible color-coded wiring slots ease wiring

1000	4.
	Comparison of Source States of Source States
	and a loss of some dama where the
	and a started at the started at
-	
-	

GPKBW24Y



GPKBW72Y

Part Number	Part Description	Std. Pkg. Qty.	
GPKBW24Y	96-pair (24-port) Category 6 punchdown base field termination kit with legs.	1	10
GPKBW72Y	288-pair (72-port) Category 6 punchdown base field termination kit with legs.	1	10

Cable requirement: terminates most 22 - 26 AWG solid or stranded IWC wire with a 0.050" (1.27mm) max o.d., either PVC or plenum rated.

Termination tool available on page B.79 of SA-NCCB51.

To ensure optimal performance, Panduit recommends use with other Panduit Category 6 PLUS components. Can be clearly identified with labels found on page B.76 of SA-NCCB51.

P. Cable Management Accessories

> Q. Index

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Mounting & Accessories category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

582603-1
009333-000
727844N003
747
809090N001
843188-000
8666
967279N002
DB-11
1300840039
1300900096
1301800416

1302264450
1300830184
1300830729
1300900039
1301580036
1301850553
1301860939
1302261315
1302264431

1337706-2
APA18-AK
1724
1-787307-1
185491N001
1868
HP-6N
C-202-C
202C221-13-0
CA7308-000
8S23-75FR-CS8184
2684
9648

3089
988382-000
A72821-000
AA401
173506-000
1823
202C292-13-0
202C302-13-0
2109
300625
3330
3412
356247-1
M9142

M9143
M9143
M9143
M9144
M91