HIS COPY IS PROVIDED ON	A RESTRICTED BASIS AND IS NOT TO BE U	SED IN ANY WAY DETRIMENTAL	то тн	E INTE	RESTS OF PANDUIT CORP.		
Material	High Conductivity Seamless Copper Tube					63 R REF	
Coating	Clear Coating						or coded rel markings
Wire Size	2 AWG		7	2-B			
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	.75±.04	2 STR C	LCC2-12-B DB		PANDUIT	
Wire Strip Length	1-1/4 in.						
Stud Size	1/2 in.	.63±.04	— 1.7	′5±.02		.53±.02 DIA (2) PLS	
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. UL Listed per UL467 for grounding and bonding and suitable for direct burial in earth or concrete.	•			4.51±.06		<b>-</b>
UL Temperature Rating	90°C						Beveled wire entry
C.S.A Certified Wire Connector	N/A					←── 1.16±.04	
Panduit Color Code on Barrel	BROWN						.31±.01 .42±.01
Panduit Die Index No. on Barrel	P33						
Alternate Industry Die Index No. ( ) on Barrel	(10)	.08±.01					Barrel contains anti-oxidant joint compound
	DB ATED						
					ANDUIT	CORP.	TINLEY PARK, ILLINOIS
0 3/16 JHNU RGB	DRAWING RELEASED	00076FBB- LCC2-12-B-CUST	RGB	RGB		LCC2-12-B	

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Ducting & Raceways category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

 800A-LB
 801I-LSP
 802A-ECSP
 802I-ICSP
 923223-000
 PRAF6WH-X
 A0405538
 1301150342
 1301160034
 1301170070
 1301180011

 1301230083
 1301230153
 1301240273
 1301250006
 1302261238
 1302261321
 1302262552
 1302263103
 1302263178
 1302263259

 1302263816
 1302263860
 1302264375
 1302264390
 1301150343
 1301160030
 1301170051
 1301170061
 1301180013

 1301230086
 1301230130
 1301240054
 1302260055
 1302260376
 1302261343
 1302262674
 1302263095
 1302263166

 1302263209
 1302263513
 1302263870
 1302264137
 1302264218
 DD1/J
 AX101472
 AX102007