Material	5 014	A RESTRICTED BASIS AND IS NOT TO BE L High Conductivity			- 10 1		
		Seamless Copper Tube	-				
Plating		Clear Coating					
Wire Size		350 kcmil					/ R.63 REF / Knurled
Wire Type		Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric			CU 12-B		barrel markings
Wire Strip Length		1-9/16 in.	 1.62±.04		STR (e (
Stud Size		1/2 in.					
UL Listed Wire Connector		Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.63±.04 • • 1.75±.02 • (2) PLCS				
		UL Listed per UL467 for grounding and bonding and suitable for direct burial in earth or concrete.		-			- 5.32±.08
UL Temperature Rating		90° C		I			/Plastic plug
C.S.A Certified Wire Connector		N/A	Beveled wire				
Panduit Color Code on Barrel		BROWN	Wire inspection hole with plastic plug				
Panduit Die Index No. on Barrel		P87					
Alternate Industry Die Index No. () on Barrel	,	(20)					
CULUSTED				.43±.02			Barrel contains anti-oxidant joint compound
				NPI-PWRGRD-			
		REVISED BARREL LENGTH: 1.50 WAS 1.18 REVISED TOLERANCES		038781		RGB	
	RGB	ADDED IEEE LOGO		LCDT350-12-B-CUST	RGB	RGB	LCDT350-12-B-X Copper Lug - Two-Hole, Standard Barrel, Direct Buric
	RGB	DRAWING RELEASED					
V DATE BY (СНК	DESCRIPTION		ECN	-R	SUP	P SCALE N/A DRAWING NO / CAD FILE LCDT350-12-B-CUST

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

HT-13-10 71M-250-32-NB 01-2065-1-0216 00581P0075 M10-10RX M10BCK 60205-1 604200-1 60598-1-CUT-TAPE 60617-1-C 60873-1 M14-516R/SK M14-6RSX M18-10FLX M18-8FBX M18-8R/LX M18BCK 61314-6-C 61-S 61-SN 61-SN-A 62-NBM-A 62-SN 62-SP 63-S 640179-1 640917-2-CUT-TAPE 6501550002 66107-2-C 66107-4-C 696683-1 696834-1 696861-1 696931-1 696999-1 M8-516RK M86700006 MA250DMFMX-A 701-2007 701-2307 701-7761-03 70F-110-32-PB 718-N-A 71M-187-20-NBL 71M-250-32-NBL 72F-187-20-NBL 72M-250-32-NBL 7310 73F-250-32 73F-250-32-NBL