

18900 Panduit Drive Tinley Park, IL 60487

Customer Service: 800-777-3300

TDS:

Metal Marking **Plates** 

Effective Date: Revision:

09MAR18

### **Technical Data Sheet**

# **Panduit Stainless Steel Marker Plates and Tags**

This specification is intended to outline the physical and chemical properties of PANDUIT's stainless steel marker plates and tags and include the following material identifiers:

Part Number Prefixes			
MMP*	MT*		

#### **PRODUCT SPECIFICATIONS:**

Description:	Material is RoHS compliant (European Union directive 2002/95/EC). Panduit stainless steel marker plates and tags provide permanent identification of pipes conduits, valves, cables and equipment in harsh environments.	
	These marker plates and tags deliver long life when exposed to chemicals, vibrations, radiation, weathering and extreme temperatures	
Material:	304 and 316 grade stainless steel.	
Marking Method:	Embossed and Laser Etched.	
Thickness: Service Temperature Range:	0.010 inch, 0.015 inch and 0.035 inch -112°F to 1000°F (-80°C to 538°C)	
Service reimperature Range.	-112 1 to 1000 1 (-00 C to 330 C)	
Storage Conditions:	Store at 70°F (21°C) and 50% Relative Humidity.	

## **PERFORMANCE PROPERTIES:**

Embossed and laser etched marker plates and tags were tested for their performance properties. Unless otherwise noted results are for both marking methods.

PROPERTIES	TEST METHOD	PERFORMANCE
UV Resistance	1000 hours in Fluorescent UV	No visible change observed
	Weatherometer	
	ASTM G154	
Weatherability	1000 hours in Xenon Arc Weatherometer,	No visible change observed
	ASTM G155, Cycle 1	
High Service Temperature	30 days at 538°C(1000°F)	Discoloration observed but
		markings still legible
Low Service Temperature	30 days at -80°C(-112°F)	No visible change observed
Salt Fog Resistance	2000 hours in 5% salt fog solution chamber	No visible change observed
	ASTM B117	
Boiling Water Resistance	Soaked in boiling water for 1 hour	No visible change observed
Flame Resistance	Heated to cherry red	Discoloration observed but
		markings still legible
Liquid Nitrogen Resistance	Dipped in liquid nitrogen for 20 minutes	No visible change observed
Thermal Cycle Resistance	Heated to cherry red and then dipped in	Discoloration observed but
	liquid nitrogen	markings still legible

Page 1 of 2

**TDS: Metal Marking Plates** 

© 2018 PANDUIT Corp



18900 Panduit Drive Tinley Park, IL 60487

Customer Service: 800-777-3300

TDS:

Metal Marking Plates

09MAR18

Effective Date:

Ω

Revision:

#### **Technical Data Sheet**

#### **CHEMICAL RESISTANCE TEST:**

Embossed and laser etched marker plates and tags were tested for their chemical resistance properties. Unless otherwise noted results are for both marking methods.

CHEMICAL	1 hour immersion	24 hour immersion	7 day immersion
Water	NC	NC	NC
Isopropyl Alcohol	NC	NC	NC
Ethanol	NC	NC	NC
Gasoline	NC	NC	NC
Mineral Spirits	NC	NC	NC
Skydrol	NC	NC	NC
Motor Oil	NC	NC	NC
Acetone	NC	NC	NC
Methyl Ethyl Ketone	NC	NC	NC
Xylene	NC	NC	NC
25% Sodium Hydroxide	NC	NC	NC
20% Ammonium Hydroxide	NC	NC	NC
37% Hydrochloric Acid	Discolored but	Discolored but markings	Material Disintegrates
	markings still legible	still legible	
50% Sulfuric Acid	Discolored but	Embossed marking	Embossed marking
	markings still legible	discolored but legible.	discolored but legible.
		Laser etched marking is	Laser etched marking
		illegible	is illegible
Glacial Acetic Acid	NC	NC	NC

NC = No Change

#### LIMITED WARRANTY

All *PANDUIT* Identification Solution Products (except for Software programs) are warranted to be free from defects in material and workmanship at the time of sale but our obligation under this warranty is limited to replacement of the product proved to be defective within 6 months from the date of sale, or in the case of printers, within 90 days from the date of sale. This warranty is void if the products or printers are modified, altered or misused in any way. Use of *PANDUIT* printers with any product other than the specified *PANDUIT* products for which the printer was designed constitutes misuse. Before using, the user shall determine the suitability of the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers or seller and manufacturer.

NEITHER PANDUIT OR SELLER SHALL BE LIABLE FOR ANY OTHER INJURY, LOSS OR DAMAGE, WHETHER DIRECT OR CONSEQUENTIAL, ARISING OUT OF THE USE OF, OR THE INABILITY TO USE THE PRODUCT OR THE PRINTER.

THIS WARRANTY IS MADE IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS OF PARTICULAR USE ARE SPECIFICALLY EXCLUDED.

The information contained in this literature is based on our experience to date and is believed to be reliable. It is intended as a guide or use by persons having technical skill at their own discretion and risk. We do not guarantee favorable results or assume any liability in connection with its use. Dimensions contained herein are for reference purposes only. This publication is not to be taken as a license to operate under, or a recommendation to infringe any existing patents. This supersedes and voids all previous literature, etc.

Page 2 of 2

© 2018 PANDUIT Corp TDS: Metal Marking Plates

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Labels & Markers category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

89078GBEST 89082GBESR 89082GBEST PCL025-4 5761-2SF 58400 586R734H02 M1.040.0000.6 CRS-CM5M CRS-M18M CS1836000 CS8626-000 CU6337-000 CU6342-000 CU6343-000 CWD01-0 CWD012-0 CWD012-7 CWD015-3 CWD015-7 CWD02-0 CWD023 CWD02-4 CWD02-6 CWD02-8 CWD02-A CWD02-D CWD02-H CWD02-K CWD02-L CWD02-M CWD02-P CWD02-Q CWD02-R
CWD02-U CWD02-W CWD02-Y CWD03-+ CWD03-0 CWD03-P CWD06-0 CWD06-8 CWD06-9 CWD06-L CWD06-N CWD09-0
CWD09-5 CWD09-7 6806810001 CZ2857-000