

Pan-Steel® Strapping – MS Series

- Fold over design provides high-retained tension in mechanical fastening and cable bundling applications
- After tensioning, cut end is locked inside low profile buckle – no sharp edges
- Can be used in a wide range of indoor, outdoor, and underground (including direct burial) applications
- Smooth surfaces and rounded edges assures cable protection and worker safety
- Available in AISI 201 (3/4" width only) and 304 stainless steel for general-purpose applications
- Available in AISI 316 stainless steel for the most corrosive environments



| Part Number | Max. Bundle Diameter | | Length* | | Strap Breaking Strength | | Min. Bundle Diameter | | Width | | Thickness | | Recommended Installation Tool*** | Std. Pkg. Qty. | Std. Ctn. Qty. | |
|---------------------------------|----------------------|-----|---------|-----|-------------------------|-------|----------------------|------|-------|------|-----------|------|----------------------------------|----------------|----------------|-----|
| | In. | mm | In. | mm | Lbs. | N | In. | mm | In. | mm | In. | mm | | | | |
| AISI 201 Stainless Steel | | | | | | | | | | | | | | | | |
| MS4W75T30-Q2 | 4.0 | 102 | 20.2 | 513 | 2400 | 10656 | 1.00 | 25.4 | 0.75 | 19.1 | 0.030 | 0.76 | BT75SDT | 25 | 25 | |
| MS6W75T30-Q2 | 6.0 | 152 | 26.5 | 673 | 2400 | 10656 | 1.00 | 25.4 | 0.75 | 19.1 | 0.030 | 0.76 | | 25 | 25 | |
| MS8W75T30-Q2 | 8.0 | 203 | 32.7 | 831 | 2400 | 10656 | 1.00 | 25.4 | 0.75 | 19.1 | 0.030 | 0.76 | | 25 | 25 | |
| MS10W75T30-Q2 | 10.0 | 254 | 39.0 | 991 | 2400 | 10656 | 1.00 | 25.4 | 0.75 | 19.1 | 0.030 | 0.76 | | 25 | 25 | |
| AISI 304 Stainless Steel | | | | | | | | | | | | | | | | |
| MS2W38T15-L4 | 2.0 | 51 | 11.8 | 300 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | BT2HT | 50 | 250 | |
| MS4W38T15-L4 | 4.0 | 102 | 18.0 | 457 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | | 50 | 250 | |
| MS6W38T15-L4 | 6.0 | 152 | 24.4 | 620 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | | 50 | 250 | |
| MS8W38T15-L4 | 8.0 | 203 | 30.7 | 780 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | | 50 | 250 | |
| MS10W38T15-L4 | 10.0 | 254 | 37.0 | 940 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | | 50 | 250 | |
| MS4W50T15-L4 | 4.0 | 102 | 18.0 | 457 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | | 50 | 250 | |
| MS6W50T15-L4 | 6.0 | 152 | 24.4 | 620 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | | 50 | 250 | |
| MS8W50T15-L4 | 8.0 | 203 | 30.7 | 780 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | | 50 | 250 | |
| MS10W50T15-L4 | 10.0 | 254 | 37.0 | 940 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | | 50 | 250 | |
| MS4W63T15-L4 | 4.0 | 102 | 18.0 | 457 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | | 50 | 250 | |
| MS6W63T15-L4 | 6.0 | 152 | 24.4 | 620 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | | 50 | 250 | |
| MS8W63T15-L4 | 8.0 | 203 | 30.7 | 780 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | | 50 | 250 | |
| MS10W63T15-L4 | 10.0 | 254 | 37.0 | 940 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | | 50 | 250 | |
| AISI 316 Stainless Steel | | | | | | | | | | | | | | | | |
| MS2W38T15-L6 | 2.0 | 51 | 11.8 | 300 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | | BT2HT | 50 | 250 |
| MS4W38T15-L6 | 4.0 | 102 | 18.0 | 457 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | | | 50 | 250 |
| MS6W38T15-L6 | 6.0 | 152 | 24.4 | 620 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | 50 | | 250 | |
| MS8W38T15-L6 | 8.0 | 203 | 30.7 | 780 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | 50 | | 250 | |
| MS10W38T15-L6 | 10.0 | 254 | 37.0 | 940 | 502 | 2229 | 1.00 | 25.4 | 0.38 | 9.5 | 0.015 | 0.38 | 50 | | 250 | |
| MS4W50T15-L6 | 4.0 | 102 | 18.0 | 457 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | 50 | | 250 | |
| MS6W50T15-L6 | 6.0 | 152 | 24.4 | 620 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | 50 | | 250 | |
| MS8W50T15-L6 | 8.0 | 203 | 30.7 | 780 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | 50 | | 250 | |
| MS10W50T15-L6 | 10.0 | 254 | 37.0 | 940 | 671 | 2979 | 1.00 | 25.4 | 0.50 | 12.7 | 0.015 | 0.38 | 50 | | 250 | |
| MS4W63T15-L6 | 4.0 | 102 | 18.0 | 457 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | 50 | | 250 | |
| MS6W63T15-L6 | 6.0 | 152 | 24.4 | 620 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | 50 | | 250 | |
| MS8W63T15-L6 | 8.0 | 203 | 30.7 | 780 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | 50 | | 250 | |
| MS10W63T15-L6 | 10.0 | 254 | 37.0 | 940 | 839 | 3725 | 1.00 | 25.4 | 0.63 | 15.9 | 0.015 | 0.38 | 50 | | 250 | |

*Other lengths available, contact Panduit Customer Service.

***For information on installation tool, refer to page B3.26.

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Ties](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[20093-0](#) [SJ-3463](#) [SJ3518FR-1x50](#) [SJ3526N-Beige-2"x50yd](#) [SJ3526N BLACK 58" X 50YD](#) [SJ3571](#) [SJ-3571-1"x50yd-Black](#) [20113-0](#) [3-350087-0](#) [CTB75X75BKA-C](#) [3722](#) [561-B110120](#) [561-EZAB580T](#) [561-EZS375B40](#) [561-N3510](#) [561-TA250125](#) [08443-0](#) [08600-0](#) [08376-0](#) [10035-0](#) [10036-0](#) [10037-0](#) [10325-0](#) [10362-0](#) [10606-0](#) [561-EZ250](#) [561-EZ625](#) [561-EZ750](#) [561-TA00600](#) [SJ3519FR BLACK 1X50](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [157-00039](#) [3719](#) [08445-0](#) [08582-0](#) [08386-0](#) [10431-0](#) [08359-0](#) [10056-0](#) [10620-0](#) [10345-0](#) [08416-0](#) [08384-0](#) [08664-0](#) [10425-0](#) [08470-0](#) [13120B](#) [08354-0](#)