


## Component Labels for 110 Punchdown Designation Label Holders



Suggested Label Solutions for TIA/EIA-606-A Compliance				
Punchdown Holder Part Number	Laser/Ink Jet Desktop Printer Label	TDP43ME Thermal Transfer Desktop Printer Label	PanTher™ LS8E Hand-Held Printer Label	Cougar™ LS9 Hand-Held Printer Label
<b>P110LH</b>	<b>C750X050Y1J</b>	<b>C750X050Y1T</b>	<b>C750X050Y1C</b>	<b>T050X000VPC-BK‡</b>

For complete labeling solutions and product information, reference charts on pages O.1 – O.22.

‡For non-adhesive labeling solution, do not remove liner from label.



### 19" Rack Mount Bracket Kits

- Used to attach tower systems and vertical cable managers to 19" racks

- Use two towers side-by-side or a tower and a vertical wire manager side-by-side
- Include brackets and mounting screws



Part Number	Part Description	Std. Pkg. Qty.
<b>P110TB300Y</b>	Kit for 300-pair tower or vertical wire management.	1
<b>P110TB900Y</b>	Kit for 900-pair tower or vertical wire management.	1



### Pan-Punch® 110 Category 5e Connecting Blocks

- Exceeds ANSI/TIA-568-C.2 Category 5e standard
- Available in 3, 4, or 5-pair connection blocks
- Dual IDC terminates UTP cable on 110 base and UTP cable or 110 patch cords for cross-connecting
- Highly visible color-coded wiring slots ease wiring
- Can be used with single or multiple punchdown tools

- Can be utilized with discrete wires or Pan-Punch® Patch Cord Connector
- Constructed of UL 94V-0 high impact polycarbonate material
- Patented single piece robust construction



P110CB3-\*Y

P110CB4-\*Y

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
<b>3-Pair 110 Connecting Blocks</b>			
<b>P110CB3-XY</b>	3-pair connecting block.	10	1000
<b>P110CB3-CY</b>		100	1000
<b>4-Pair 110 Connecting Blocks</b>			
<b>P110CB4-XY</b>	4-pair connecting block.	10	1000
<b>P110CB4-CY</b>		100	1000
<b>5-Pair 110 Connecting Blocks</b>			
<b>P110CB5-XY</b>	5-pair connecting block.	10	1000
<b>P110CB5-CY</b>		100	1000



P110CB5-\*Y

Termination tool available on page B.87.

Cable requirement: terminates most 22 – 26 AWL solid or stranded IWO wire with a 0.050" (1.27mm) max o.d., either PVC or plenum rated.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wire Identification](#) category:*

*Click to view products by [Panduit](#) manufacturer:*

Other Similar products are found below :

[CU6337-000](#) [CU6342-000](#) [FCA-410-12](#) [11631010](#) [1-1768037-1](#) [1-1768037-2](#) [1-1768050-0](#) [PXLK-VI](#) [Q62184-1](#) [A64304-000](#) [QMT221](#)  
[HK032WE1NF038B](#) [1330-0519-10](#) [1395199-1](#) [1395200-1](#) [1395202-1](#) [DMVF050WE-300S6](#) [D-SCE-1K-2.4-50-4-CS7834](#) [1538738-1](#)  
[E90935-000](#) [EC1238-000](#) [EC1465-000](#) [EC1855-000](#) [EC1859-000](#) [EC1863-000](#) [EC5415-000](#) [EC7277-000](#) [EC7352-000](#) [EC7603-000](#)  
[EC7707-000](#) [EC7735-000](#) [EC7768-000](#) [EC7828-000](#) [EC7854-000](#) [EC7952-000](#) [EC8128-000](#) [1768037-8](#) [1768041-7](#) [NC-127191-10-9](#)  
[HS048WE2NF038B](#) [C03232-000](#) [HTCM-SCE-14-4H-9](#) [HTMS-3/16-9](#) [HT-SCE-1/4-2.0-4](#) [HT-SCE-3/16-2.0-4](#) [HTTMS-1/2-1.50-9](#) [HTTMS-](#)  
[CM-1/2-4H-9](#) [HX-SCE-19.0-50-9](#) [HX-SCE-6.4-50-4](#) [C25254-000](#)