



Comprehensive Cable Tie Solutions

Panduit offers a broad selection of industry approved styles, sizes, and materials to meet a full range of electrical, industrial, and networking applications.

PLT Pan-Ty® Cable Ties

Most comprehensive product offering

SG Super-Grip® Cable Ties

Withstand rough installations

BT Dome-Top® Barb Ty Cable Ties

Metal locking barb; infinite adjustability

Dura-Ty® Cable Ties

Acetal material; 20+ years outdoor service life

CBR Contour-Ty® Cable Ties

Low profile head, parallel-entry, outside teeth

HV Hyper-V™ Cable Ties

Teeth on both sides; 2-wedge locking design

SST Sta-Strap® Cable Ties

Two-piece design, low thread force, lightweight

ERT Elastomeric Cable Ties

Flexible, elastic material, UL 94V-0, releasable

			ION O	No.			Panc		
	Product Family	PLT	SG	BT	DT	CBR	HV	SST	ERT
	Locking	✓	✓	✓	✓	✓	✓	✓	
	Releasable	✓							✓
les	Marker	✓		✓				✓	
Styles	Clamp	✓		✓				✓	
	Push Mount	✓		✓					
	Specialty	✓		✓				✓	
(0)	Miniature	✓	✓	✓		✓		✓	✓
Sections	Intermediate	✓	✓	✓		✓		✓	
∺	Standard	✓	✓	✓		✓		✓	
Se	Heavy-Standard					✓			
SS	Light-Heavy	✓	✓	✓		✓	✓		
Cross	Heavy	✓	✓		✓			✓	
	Extra-Heavy	✓			✓				

Cable Tie Industry Approvals

Agency Spec/Approval		Requirement	Products				
UL (Underwriters Laboratory	UL 62275 (File E56854)	Types 1, 11, 2, 2S, 21, 21S (Note 1)	Select PLT, BT, SG, SST, and CBR Series				
CSA (Canadian Standards Association)	CSA-C22.2 No. 62275 (File 31212)	Types 1, 11, 2, 2S, 21, 21S (Note 1)	Select PLT, BT, SG, SST, and CBR Series				
ABS (American Bureau of Shipping)	05-HS463235-PDA	2005 Steel Vessel Rules 1-1-4/7.7,4-8-4/21.9.32001 MODU Rules 4-3-3/5.9.1	PLT and BT Series				
Bureau Veritas	Cert 05968/C0, BV File ACE 14/601/01 Product Code: 2535H	Bureau Veritas Rules for the Classification of Steel Ships	PLT, PRT, BT and CBR Series				
Det Norske Veritas	E-6405	Det Norske Veritas' Rules for Classification of Ships and Mobile Offshore Units	PLT, PLC, PLM, PRT, PLWP, PRWP and PRST Series				
Lloyd's Register of Shipping	89/60111 (E3)	Lloyd's Register Type Approval	PLT, PLC, PLP, PLWP, PLM, PRT, SST, SSC, SSM, BT, BC, BM, BF, B2M, B3M, BM, BW, BP, ILT and CBR Series				
Russian Maritime Register of Shipping	11130200	Russian Maritime Type Approval Certificate	PLT, PLC, PLM, PLF, SG, BT, BF, BM, BC, DT and CBR Series				
NRC (Nuclear Regulatory Commission)	NRC 10CFR50	Quality Assurance Criteria for Nuclear	All cable tie products				
US Military Aerospace Standard	QPL-AS23190	SAE spec AS23190	Select PLT, BT, SST, and CBR Series				

Material Selection Criteria

	-									
		Material	Test Method	Nylon 6.6	Weather Resistant Nylon 6.6	Impact Modified Weather Resistant Nylon 6.6	Heat Stabilized Nylon 6.6	Heat Stabilized Nylon 6.6	Heat Stabilized Weather Resistant Nylon 6.6	Flame Retardant Nylon 6.6
		Color	_	Natural (other colors available)	Black	Black	Black	Natural	Black	Black
		Part Number Suffix (Material Designation)	_	No Suffix	0	0	30	39	300	60
		Tensile @ Yield @ 73°F (psi)	ISO 527	12,000	12,000	9,700	12,000	12,000	12,000	11,000
lical	ties	Water Absorption (24 Hours)	ASTM D570	1.2%	1.2%	1.2%	1.2%	1.2%	1.2%	1.1%
char	Properties	Radiation Resistance (Rads)	-	1 x 10⁵	1 x 10 ⁵	1 x 10 ⁵	1 x 10 ⁵	1 x 10⁵	1 x 10 ⁵	1 x 10 ⁵
Me	ď	Weathering Life Expectancy (Years)/UV Resistance	_	1 – 2	7 – 9	7 – 9	4 – 5	1 – 2	7 – 9	1 – 2
		Impact Resistance	_							•
		Salts	_							
ca	Resistance	Hydrocarbons (Oil, Lubricants)	-	•	•		•	•		
Ĭ.	sta	Chlorinated Hydrocarbons	_							
l S	esi	Acids	_							
	ш	Bases	_							
		Acid Rain	-							
		Continuous Use Temperature Range	UL 746B	-76°F – 185°F -60°C – 85°C	-76°F – 185°F -60°C – 85°C		-76°F – 239°F -60°C – 115°C	-76°F – 239°F -60°C – 115°C	-76°F – 239°F -60°C – 115°C	-76°F – 212°F -60°C – 100°C
	Properties	Minimum Installation Temperature	UL 62275	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1)
	obe	Flammability Rating	UL 94	V-2	V-2	НВ	V-2	V-2	V-2	V-0
		Low Smoke	ASTM E662	PASS	PASS	PASS	PASS	PASS	PASS	PASS
	Thermal	Oxygen Index	BS ISO 4589	28	28	_	28	28	28	34
ľ	F	Halogen-Free	IEC 60754-2	Yes	Yes	Yes	Yes	Yes	Yes	Yes
		Burning Fume Toxicity	BSS-7239	PASS	PASS	PASS	PASS	PASS	PASS	PASS
		Heat Deflection Temperature @ 1.8 Mpa	ASTM D648 ISO 75 -1/-2	158°F 70°C	158°F 70°C	145°F 63°C	158°F 70°C	158°F 70°C	158°F 70°C	154°F 68°C
		Relative Price	_	Low	Low	Low	Low	Low	Med	Med
		Product Family			Cross Se	ections				
		Pan-Ty® Cable Ties PLT		3	SM, M, I, S	LH, H, EH	3	3	3	3
	≣.	Super-Grip® Cable Ties SG		3	M, I, S, LH	Н	3			
	Availabi	Dome-Top® Barb Ty Cable TiesBT		3	M, I, S	LH	3	3	3	
		Dura-Ty [™] Cable Ties DT								
	Material	Contour-Ty® Cable Ties CBR		3	M, I, S, HS, LH		3	3		
	Ma	Hyper-V™ Cable Ties HV				LH				
		Sta-Strap® Cable Ties SST		3	M, I, S, H		3			
		Elastomeric Cable Ties ERT								

Recommendation Legend									
Highest	High	Acceptable	Low	Lowest					
• •		0	•						

Check mark indicates material availability in that product family for all cross sections.

Cross Sections: SM = Subminiature, M = Miniature, I = Intermediate, S = Standard, HS = Heavy-Standard, LH = Light-Heavy, H = Heavy, EH = Extra-Heavy

Flame Retardant Nylon 6.6	Weather Resistant	Polypropylene	Weather Resistant Polypropylene	TEFZEL ¹	HALAR °	PEEK	Metal Detectable Nylon	Metal Detectable Polypropylene	DT Weather Resistant Acetal	ERT Flame Retardant TPU
Natural Ivory	Black	Green	Black	Aqua Blue	Maroon	Translucent Brown	Lt. Blue	Dark Blue	Black	Black
69	120	109	100	76	702Y	71	86	186	N/A	20
11,000	6,700	4,100	4,100	7,500	7,000	15,200	_	-	6,500	4,300
1.1%	0.3%	0.1%	0.1%	<0.03%	<0.05%	0.5%	1.2%	0.1%	<0.45%	0.25%
1 x 10 ⁵	3.5 x 10 ⁶	1 x 10 ⁶	1 x 10 ⁶	2 x 10 ⁸	2 x 10 ⁸	1 x 10 ⁹	_	1 x 10 ⁶	6 x 10 ⁵	_
1 – 2	12 – 15	1	7 – 9	>15	>15	_	_	1	>20	7 – 9
						•		-		
		0	0			•		0		0
						0				
-76°F – 212°F -60°C – 100°C	-76°F – 194°F -60°C – 90°C	-76°F – 239°F -60°C – 115°C	-76°F – 239°F -60°C – 115°C	-76°F – 338°F -60°C – 170°C		-76°F – 500°F -60°C – 260°C (Note 2)	-76°F – 185°F -60°C – 85°C	-76°F – 239°F -60°C – 115°C	76°F – 185°F -60°C – 85°C	
-4°F or +32°F -20°C or 0°C (Note 1) V-0	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1)	-4°F or +32°F -20°C or 0°C (Note 1) HB	-4°F or +32°F -20°C or 0°C (Note 1) V-0		-4°F or +32°F -20°C or 0°C (Note 1) V-0	-4°F or +32°F -20°C or 0°C (Note 1)		-4°F or +32°F -20°C or 0°C (Note 1) HB	
PASS	_	_	_	_	_	PASS	_	_	PASS	_
34	_	_	_	30	52	35	_	_	_	26
Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes
PASS	_	_	-	_	_	_	_	_	_	_
154°F 68°C	122°F 50°C	122°F 50°C	122°F 50°C	-	149°F 65°C	313°F 156°C	_	-	147°F 64°C	-
Med	Med	Med	Med	High	High	High	Low	Med	Med	High
		7 7 11 7	2,1							
3	3	3	3	3	3	3	3	3		
3										
									3	
3										
										3

Note 1: Check UL file for specific part number rating Note 2: Based upon UL RTI for electrical properties

[&]quot;TEFZEL is a registered trademark of E.I. du Pont de Nemours and Company.

^sHALAR is a registered trademark of Ausimont USA, Inc.

Cable Tie Installation Tools

Panduit offers the most preferred hand-operated tools in the industry. These versatile tools can be used for production, maintenance or construction applications. Panduit cable tie installation tools promote worker safety, help reduce downtime, improve productivity and provide the lowest total installed cost. As with all Panduit products, quality in design and production along with customer service excellence, are assured.

Cable Tie Tools



GTS-E

- Used with SM, M, I, and S cable ties
- Ergonomic design lowers the risk of repetitive motion injuries. Lowest activation and impact force to installer's hand



GTH-E

- Used with S, HS, LH, and H cable ties
- Ergonomic design lowers the risk of repetitive motion injuries. Lowest activation and impact force to installer's hand

Pneumatic Hand Tools



PTS

- Used with SM, M, I, and S cable ties
- Ergonomic design with impact resistant resin housing and black knob; replacement parts can be part of a scheduled maintenance program



GS2B-E

- Used with SM, M, I, and S cable ties
- Metal tool with a durable powder coat finish
- Ergonomic design lowers the risk of repetitive motion injuries. Lowest activation and impact force to installer's hand



GS4H-E

- Used with S, HS, LH, and H cable ties
- Metal tool with a durable powder coat finish
- Ergonomic design lowers the risk of repetitive motion injuries. Lowest activation and impact force to installer's hand



GS4EH-E

- Used with LH, H, and EH cable ties
- Metal tool with a durable powder coat finish
- Ergonomic design lowers the risk of repetitive motion injuries. Lowest activation and impact force to installer's hand



PTH

- Used with S, HS, LH, and H cable ties
- Ergonomic design with impact resistant resin housing and red knob; replacement parts can be part of a scheduled maintenance program



Pneumatic Tool Accessories

 Visit www.panduit.com for our complete line of pneumatic tool accessories

Complete Your Bundling System

Tools



Manual Cable Tie Installation Tools

- Designed to speed installation for lower installed cost
- Flush tie cut-off limits exposure to sharp edges
- A full line of lightweight, ergonomic hand tools available
- Panduit leads the industry in reliability and performance



Automatic Cable Tie Installation Systems

- An efficient solution for high volume harnessing, assembly, fastening and packaging applications
- High speed tools lower installed cost and reduce operator fatigue
- Wrap, tension, and cut off cable ties in less than one second
- Microprocessor based controller monitors system performance for production data and reporting

Services



Custom Imprinting Service

- Products available for custom imprinting include cable ties, marker plates, marker and flag ties, hook and loop wrap ties
- Results in a professional, high quality appearance for identification and labeling as well as promotional purposes
- Options include company logos, website addresses, sequential numbering, phone numbers, graphics and text

Related Products



Cable Accessories

- Comprehensive line of mounts, clips, and clamps that organizes and routes cables, speeds and simplifies installations, and lowers overall installed cost Installation methods include adhesive backed, user applied adhesive, screws, rivets and push barb
- Accessories provide long term reliability while cable clips and clamps offer a one-piece solution to save time and reduce inventory



Stainless Steel Cable Ties

- Durable method of bundling, fastening and permanent identification in applications where severe environmental conditions exist
- Engineered for safety, productivity and durability by providing round edges and smooth surfaces, easy threading, high loop tensile strength and tight clamping



Contact Customer Service by email: cs@panduit.com or by phone: 800-777-3300

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Labels & Markers category:

Click to view products by Panduit manufacturer:

Other Similar products are found below:

89078GBEST 89082GBESR 89082GBEST PCL025-4 5761-2SF 58400 586R734H02 M1.040.0000.6 CRS-CM5M CRS-M18M CS1836000 CS8626-000 CU6337-000 CU6342-000 CU6343-000 CWD01-0 CWD012-0 CWD012-7 CWD015-3 CWD015-7 CWD02-0 CWD023 CWD02-4 CWD02-6 CWD02-8 CWD02-A CWD02-D CWD02-H CWD02-K CWD02-L CWD02-M CWD02-P CWD02-Q CWD02-R
CWD02-U CWD02-W CWD02-Y CWD03-+ CWD03-0 CWD03-P CWD06-0 CWD06-8 CWD06-9 CWD06-L CWD06-N CWD09-0
CWD09-5 CWD09-7 6806810001 CZ2857-000