ELECTRICAL SOLUTIONS




Pan-Ty[®] Wing Push Mount Ties – Weather Resistant and Heat Stabilized Nylon 6.6

Mamina

- Weather resistant material has greater resistance to damage caused by ultraviolet light indoor or outdoor use
- · Heat stabilized material for high temperature applications up to 239°F (115°C) - indoor use
- · Cable tie, mount, and fastener in a single part
- · Used to attach bundles to another surface such as a flat panel



- · Anchor is easily pressed into a pre-formed hole and locks in place
- · Wings provide constant tension for a stable, secure, and rattle-free installation
- · Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



C2. Surface Raceway

A. System

Overview

B1. Cable Ties

B2. Cable

Accessories

B3.

Stainless **Steel Ties**

> **C**1. Wiring Duct

Part Number	Length		Width		Thickness		Nominal Hole Dia.		Max. Panel Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation	Std. Pkg.	Std. Ctn.	C3. Abrasion Protection
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	Ν	Tool	Qty.	Qty.	
Weather Re	esist	tant	Nylo	on 6	.6													C4.
Miniature Cros	Iniature Cross Section														Cable			
PLWP1M-D0	4.3	109	.098	2.5	.044	1.1	.187	4.7	.093	2.4	.87	22	18	80	GTS, GTSL,	500	5000	Managemen
															GS2B, PTS, PPTS, STS2			
Standard Cros	s Sec	tion													1			D1. Terminals
PLWP1S-C0	5.2	132	.190	4.8	.052	1.3	.250	6.4	.105	2.7	1.00	25	50	222	GTS, GTSL,	100	1000	
															GS2B, GTH, GS4H, PTS,			D2.
PLWP2S-C0	7.8	198	.190	4.8	.052	1.3	.250	6.4	.105	2.7	1.75	45	50	222	PTH, PPTS, STS2, STH2	100	1000	Power Connectors
Light-Heavy Cr	ross S	Sectio	n															
PLWP2H-TL0	8.9	226	.300	7.6	.075	1.9	.266	6.8	.105	2.7	2.00	51	120	534	GTH, GS4H,	250	2500	D3.
PLWP3H-TL0	12.0	305	.300	7.6	.075	1.9	.266	6.8	.105	2.7	3.00	76	120	534	GS4EH, PTH, STH2, ST3EH	250	2500	Grounding Connectors
Heat Stabil		-	on 6	6.6														E1.
Miniature Cros																		Labeling
PLWP1M-D30	4.3	109	.098	2.5	.044	1.1	.187	4.7	.093	2.4	.87	22	18	80	GTS, GTSL, GS2B, PTS, PPTS, STS2	500	5000	Systems
Intermediate C	ross	Sectio	on												1	1		E2.
PLWP1.5I-D30	6.0	152	.135	3.4	.045	1.2	.187	4.7	.093	2.4	1.25	32	40	178	GTS, GTSL, GS2B, PTS,	500	5000	Labels
															PPTS, STS2			E3.
Standard Cros	s Sec	tion																Pre-Printed & Write-On
PLWP1S-D30	5.2	132	.190	4.8	.052	1.3	.250	6.4	.105	2.7	1.00	25	50	222	GTS, GTSL,	500	5000	Markers
PLWP1.5S-D30	6.8	173	.190	4.8	.052	1.3	.250	6.4	.105	2.7	1.50	38	50	222	GS2B, GTH, GS4H, PTS,	500	5000	E4.
PLWP2S-D30	7.8	198	.190	4.8	.052	1.3	.250	6.4	.105	2.7	1.75	45	50	222	PTH, PPTS, STS2, STH2	500	5000	Permanent Identification
Light-Heavy Cr						1									1			
PLWP2H-TL30	8.9	226	.300	7.6	.075	1.9	.266	6.8	.105	2.7	2.00	51	120	534	GTH, GS4H, GS4EH, PTH, STH2, ST3EH	250	2500	E5. Lockout/ Tagout & Safety
																		Colutions

Note: UL Recognized and CSA Certified except PLWP2H/3H.

F. Index

Solutions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Labels & Markers category:

Click to view products by Panduit manufacturer:

Other Similar products are found below :

89078GBEST 89082GBESR 89082GBEST PCL025-4 5761-2SF 58400 586R734H02 M1.040.0000.6 CRS-CM5M CRS-M18M CS1836-000 CS8626-000 CU6337-000 CU6342-000 CU6343-000 CWD01-0 CWD012-0 CWD012-7 CWD015-3 CWD015-7 CWD02-0 CWD02-3 CWD02-4 CWD02-6 CWD02-8 CWD02-A CWD02-D CWD02-H CWD02-K CWD02-L CWD02-M CWD02-P CWD02-Q CWD02-R CWD02-U CWD02-W CWD02-Y CWD03-+ CWD03-0 CWD03-P CWD06-0 CWD06-8 CWD06-9 CWD06-L CWD06-N CWD09-0 CWD09-5 CWD09-7 6806810001 CZ2857-000