


UL LISTED CERTIFIED SF Ring Terminal, Nylon Insulated – Funnel Entry

- Ring tongue design assures a secure connection in high vibration applications
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications

- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B




Part Number	Wire Range		Color Code	Max. Ins.		Stud Size		Length		Width		Clearance		Panduit Crimping Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	AWG	mm ²		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
PNF14-8R-C	16 – 14 AWG	1.5 – 2.5	Blue	0.162	4.12	#8	M4	0.87	22.1	0.31	7.9	0.25	6.4	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	100	500
PNF14-10R-C				0.162	4.12	#10	M5	0.85	21.6	0.31	7.9	0.29	7.4		100	500
PNF14-14R-C				0.162	4.12	1/4"	M6	1.06	26.9	0.46	11.7	0.40	10.2		100	500
PNF14-56R-C				0.162	4.12	5/16"	M8	1.06	26.9	0.46	11.7	0.40	10.2		100	500
PNF14-38R-L	12 – 10 AWG	4.0 – 6.0	Yellow	0.162	4.12	3/8"	M10	1.14	29.0	0.53	13.5	0.45	11.4	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	50	500
PNF10-8R-L				0.225	5.75	#8	M4	1.06	26.9	0.37	9.4	0.31	7.9		50	500
PNF10-10R-L				0.225	5.75	#10	M5	1.06	26.9	0.37	9.4	0.31	7.9		50	500
PNF10-14R-L				0.225	5.75	1/4"	M6	1.21	30.7	0.52	13.2	0.38	9.7		50	500
PNF10-56R-L				0.225	5.75	5/16"	M8	1.21	30.7	0.52	13.2	0.38	9.7		50	500
PNF10-38R-L	0.225	5.75	3/8"	M10	1.29	32.8	0.58	14.7	0.43	10.9	50	500				

‡UL and CSA approved tooling/product combinations. For crimping tool information, see page M.46. For the full selection of Panduit Crimping Tools see www.panduit.com.

UL LISTED CERTIFIED SF Multiple Stud Terminal, Nylon Insulated

- Teardrop shaped mounting hole of multiple stud terminals permits use with #6, #8, or #10 size studs
- Ring tongue design assures a secure connection in high vibration applications
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications

- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



Part Number	Wire Range		Color Code	Max. Ins.		Stud Size		Length		Width		Clearance		Panduit Crimping Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	AWG	mm ²		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
PN14-610R-C	16 – 14 AWG	1.5 – 2.5	Blue	0.165	4.25	#6, #8, #10	M3.5 – M5	0.95	24.1	0.31	7.9	0.25	6.4	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡, CT-400, CT-460	100	500
PN10-610R-L	12 – 10 AWG	4.0 – 6.0	Yellow	0.225	5.75	#6, #8, #10	M3.5 – M5	1.17	29.7	0.37	9.4	0.33	8.4	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡, CT-460	50	500

‡UL and CSA approved tooling/product combinations. For crimping tool information, see page M.46. For the full selection of Panduit Crimping Tools see www.panduit.com.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [Panduit](#) manufacturer:

Other Similar products are found below :

[00-054007-01074-6](#) [00-054007-70206-1](#) [00-054007-70210-8](#) [00-054007-70217-7](#) [00-054007-70226-9](#) [00-054007-70228-3](#) [00-054007-70248-1](#) [00-054007-70256-6](#) [00-054007-70301-3](#) [00-054007-70316-7](#) [0-0320562-0](#) [00-054007-49560-4](#) [00-054007-70209-2](#) [00-054007-70225-2](#) [00-054007-70227-6](#) [00-054007-70231-3](#) [00-054007-70241-2](#) [00-054007-70242-9](#) [00-054007-70244-3](#) [00-054007-70246-7](#) [00-054007-70263-4](#) [00-054007-70288-7](#) [00-054007-70290-0](#) [00-054007-70300-6](#) [00-054007-70304-4](#) [01-2065-1-0216](#) [01-2900-1-04412](#) [00581P0075](#) [600TS-10](#) [60205-1](#) [604200-1](#) [605601-1](#) [60598-1-CUT-TAPE](#) [61314-6-C](#) [61810-3](#) [61-S](#) [61-SN](#) [626-0194](#) [62-NBM-A](#) [62-SN](#) [62-SP](#) [63-S](#) [640179-1](#) [M55155/059I03](#) [M55155/079C01](#) [M55155/099H02](#) [M55155/109H01](#) [M55155/109H02](#) [M55155/12XH05](#) [M55155/16XH02](#)